



TestKingonline.com

No Pass No Pay!

MCSE, CCNA, CCNP, OCP, CIW, JAVA, Sun Solaris, Checkpoint

World No 1 Cert Guides

**TS: Microsoft .NET Framework 2.0-Application Development Foundation
Exam 70-536**

Congratulations!

You have purchased a TestKingonline. Study Guide.

This study guide is a complete collection of questions and answers that have been developed by our professional & certified team. You must study the contents of this guide properly in order to prepare for the actual certification test. The average time that we would suggest you for studying this study guide is approximately 10 to 20 hours and you will surely pass your exam. We guarantee it!

GOOD LUCK!

DISCLAIMER

This study guide and/or material is not sponsored by, endorsed by or affiliated with Microsoft, Cisco, Oracle, Citrix, CIW, Checkpoint, Novell, Sun/Solaris, CWNA, LPI, ISC, etc. All trademarks are properties of their respective owners.

Guarantee

If you use this study guide correctly and still fail the exam, send a scanned copy of your official score notice at:

Sales@Testkingonline.com

We will gladly refund the cost of this study guide or give you an exchange of study guide of your choice of the Free.

This material is protected by copyright law and international treaties. Unauthorized reproduction or distribution of this material, or any portion thereof, may result in severe civil and criminal penalties, and will be prosecuted to the maximum extent possible under law.

Total No of Questions:- 255

Question: 1

You are writing a custom dictionary. The custom-dictionary class is named MyDictionary. You need to ensure that the dictionary is type safe.

Which code segment should you use?

- A. Class MyDictionaryImplements Dictionary(Of String, String)
- B. Class MyDictionary Inherits HashTable
- C. Class MyDictionary Implements IDictionary
- D. Class MyDictionary
End Class
Dim t As New Dictionary(Of String, String)
Dim dict As MyDictionary = CType(t, MyDictionary)

Answer: A

Question: 2

You write a class named Employee that includes the following code segment.

```
Private m_EmployeeId As String
Private m_EmployeeName As String
Private m_JobTitleName As String
Public Function GetName() As String
Return m_EmployeeName
End Function
Public Function GetTitle() As String
Return m_JobTitleName
End Function
End Class
```

You need to expose this class to COM in a type library. The COM interface must also facilitate forward-compatibility across new versions of the Employee class. You need to choose a method for generating the COM interface.

What should you do?

- A. Add the following attribute to the class definition.<ClassInterface(ClassInterfaceType.None)> _Public Class Employee
- B. Add the following attribute to the class definition.<ClassInterface(ClassInterfaceType.AutoDual)> _Public Class Employee
- C. Add the following attribute to the class definition.<ComVisible(True)> _Public Class Employee
- D. Define an interface for the class and add the following attribute to the class definition.<ClassInterface(ClassInterfaceType.None)> _Public Class EmployeeImplements IEmployee

Answer: D

Question: 3

You are developing a custom event handler to automatically print all open documents. The event handler helps specify the number of copies to be printed. You need to develop a custom event arguments class to pass as a parameter to the event handler. Which code segment should you use?

- A. public class PrintingArgs {
private int copies;
public PrintingArgs(int numberOfCopies) {

```

this.copies = numberOfCopies;
}
public int Copies {
get { return this.copies; }
}}
B. public class PrintingArgs : EventArgs {
private int copies;
public PrintingArgs(int numberOfCopies) {
this.copies = numberOfCopies;
}
public int Copies {
get { return this.copies; }
}}
C. public class PrintingArgs {
private EventArgs eventArgs;
public PrintingArgs(EventArgs ea) {
this.eventArgs = ea;
}public EventArgs Args {get { return eventArgs; }}}
D. public class PrintingArgs : EventArgs {
private int copies;}

```

Answer: B

Question: 4

You use Reflection to obtain information about a method named MyMethod.

You need to ascertain whether MyMethod is accessible to a derived class. What should you do?

- A. Call the IsAssembly property of the MethodInfo class.
- B. Call the IsVirtual property of the MethodInfo class.
- C. Call the IsStatic property of the MethodInfo class.
- D. Call the IsFamily property of the MethodInfo class.

Answer: D

Question: 5

You are creating a class that uses unmanaged resources. This class maintains references to managed resources on other objects. You need to ensure that users of this class can explicitly release resources when the class instance ceases to be needed. Which three actions should you perform? (Each correct answer presents part of the solution. Choose three.)

- A. Define the class such that it inherits from the WeakReference class.
- B. Define the class such that it implements the IDisposable interface.
- C. Create a class destructor that calls methods on other objects to release the managed resources.
- D. Create a class destructor that releases the unmanaged resources.
- E. Create a Dispose method that calls System.GC.Collect to force garbage collection.
- F. Create a Dispose method that releases unmanaged resources and calls methods on other objects to release the managed resources.

Answer: B, D, F

Question: 6

You are working on a debug build of an application.

You need to find the line of code that caused an exception to be thrown. Which property of the Exception class should you use to achieve this goal?

- A. Data
- B. Message
- C. StackTrace
- D. Source

Answer: C

Question: 7

You need to write a code segment that performs the following tasks:

- * Retrieves the name of each paused service.**
- * Passes the name to the Add method of Collection1.**

Which code segment should you use?

- A.** `ManagementObjectSearcher^ searcher =
gcnew ManagementObjectSearcher(
"Select * from Win32_Service where State = 'Paused'");for each (ManagementObject^
svc in searcher->Get()) {
Collection1->Add(svc["DisplayName"]);}`
- B.** `ManagementObjectSearcher^ searcher =
gcnew ManagementObjectSearcher(
"Select * from Win32_Service", "State = 'Paused'");for each (ManagementObject^ svc in
searcher->Get()) {
Collection1->Add(svc["DisplayName"]);}`
- C.** `ManagementObjectSearcher^ searcher =
gcnew ManagementObjectSearcher(
"Select * from Win32_Service");for each (ManagementObject^ svc in searcher->Get()) {
if ((String^) svc["State"] == "Paused") {
Collection1->Add(svc["DisplayName"]);
}}}`
- D.** `ManagementObjectSearcher^ searcher =
gcnew ManagementObjectSearcher();searcher->Scope = gcnew
ManagementScope("Win32_Service");for each (ManagementObject^ svc in
searcher->Get()) {
if ((String^)svc["State"] == "Paused") {
Collection1->Add(svc["DisplayName"]);
}}}`

Answer: A

Question: 8

You need to serialize an object of type List(Of Integer) in a binary format. The object is named data. Which code segment should you use?

- A.** `Dim formatter As New BinaryFormatter()
Dim ms As New MemoryStream()
formatter.Serialize(ms, data)`
- B.** `Dim formatter As New BinaryFormatter()
Dim ms As New MemoryStream()
For i As Integer = 1 To 20
formatter.Serialize(ms, data(i - 1))
Next`
- C.** `Dim formatter As New BinaryFormatter()
Dim buffer As New Byte(data.Count) {}
Dim ms As New MemoryStream(buffer, True)
formatter.Serialize(ms, data)`
- D.** `Dim formatter As New BinaryFormatter()
Dim ms As New MemoryStream()
While ms.CanRead
formatter.Serialize(ms, data)
End While`

Answer: A

Question: 9

You are developing an application that dynamically loads assemblies from an application directory.

You need to write a code segment that loads an assembly named Company1.dll into the current application domain. Which code segment should you use?

- A.** AppDomain^ domain = AppDomain::CurrentDomain;String^ myPath = Path::Combine(domain->BaseDirectory, "Company1.dll");Assembly^ assm = Assembly::LoadFrom(myPath);
- B.** AppDomain ^ domain = AppDomain::CurrentDomain;String^ myPath = Path::Combine(domain->BaseDirectory, "Company1.dll");Assembly^ assm = Assembly::Load(myPath);
- C.** AppDomain^ domain = AppDomain::CurrentDomain;String^ myPath = Path::Combine(domain->DynamicDirectory, "Company1.dll");Assembly^ assm = AppDomain::CurrentDomain::Load(myPath);
- D.** AppDomain^ domain = AppDomain::CurrentDomain;Assembly^ assm = Domain->GetData("Company1.dll");

Answer: A

Question: 10

parameter of type EventLogEntry. This method does not return a value. You need to create a code segment that helps you to test the method. The code segment must read entries from the application log of local computers and then pass the entries on to the PersistToDB method. The code block must pass only events of type Error or Warning from the source MySource to the PersistToDB method.

Which code segment should you use?

- A.** EventLog myLog = new EventLog("Application", ".");
foreach (EventLogEntry entry in myLog.Entries)
{
if (entry.Source == "MySource")
{
PersistToDB(entry);
}}}
- B.** EventLog myLog = new EventLog("Application", ".");
myLog.Source = "MySource";
foreach (EventLogEntry entry in myLog.Entries)
{
if (entry.EntryType == (EventLogEntryType.Error & EventLogEntryType.Warning))
{
PersistToDB(entry);
}}}
- C.** EventLog myLog = new EventLog("Application", ".");
foreach (EventLogEntry entry in myLog.Entries)
{
if (entry.Source == "MySource")
{
if (entry.EntryType == EventLogEntryType.Error ||
{
PersistToDB(entry);
}}}
- D.** EventLog myLog = new EventLog("Application", ".");
myLog.Source = "MySource";
foreach (EventLogEntry entry in myLog.Entries)
{

```

if (entry.EntryType == EventLogEntryType.Error ||
entry.EntryType == EventLogEntryType.Warning)
{
PersistToDB(entry);
}

```

Answer: C

Question: 11

You are developing a class library. Portions of your code need to access system environment variables.

You need to force a runtime `SecurityException` only when callers that are higher in the call stack do not have the necessary permissions.

Which call method should you use?

- A. Set->Demant();
- B. Set->Assert();
- C. Set->PermitOnly();
- D. Set->Deny();

Answer: A

Question: 12

You create the definition for a `Vehicle` class by using the following code segment.

```

Public Class Vehicle
<XmlAttribute(AttributeName:="category")> _
Public vehicleType As String
Public model As String
<XmlIgnore> _
Public year As Integer
<XmlElement(ElementName:="mileage")> _
Public miles As Integer
Public condition As ConditionType
Public Sub New()
End Sub
Public Enum ConditionType
<XmlEnum("Poor")> BelowAverage
<XmlEnum("Good")> Average
<XmlEnum("Excellent")> AboveAverage
End Enum
End Class

```

You create an instance of the `Vehicle` class. You populate the public fields of the `Vehicle` class instance as shown in the following table:

Member	Value
<code>vehicleType</code>	car
<code>model</code>	racer
<code>year</code>	2002
<code>miles</code>	15000
<code>condition</code>	AboveAverage

You need to identify the XML block that is produced when this `Vehicle` class instance is serialized.

Which block of XML represents the output of serializing the `Vehicle` instance?

- A. `<?xml version="1.0" encoding="utf-8"?>`
`<Vehicle`
`xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"`
`xmlns:xsd="http://www.w3.org/2001/XMLSchema"`
`vehicleType="car">`
`<model>racer</model>`
`<miles>15000</miles>`
`<condition>AboveAverage</condition>`

```

</Vehicle>
B. <?xml version="1.0" encoding="utf-8"?>
<Vehicle
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema"
category="car">
<model>racer</model>
<mileage>15000</mileage>
<condition>Excellent</condition>
</Vehicle>
C. <?xml version="1.0" encoding="utf-8"?>
<Vehicle
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema"
category="car">
<model>racer</model>
<mileage>15000</mileage>
<conditionType>Excellent</conditionType>
</Vehicle>
D. <?xml version="1.0" encoding="utf-8"?>
<Vehicle
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
<category>car</category>
<model>racer</model>
<mileage>15000</mileage>
<condition>Excellent</condition>
</Vehicle>

```

Answer: B

Question: 13

You are developing an application for a client residing in Hong Kong.

You need to display negative currency values by using a minus sign. Which code segment should you use?

```

A. Dim objCulture As NumberFormatInfo = _
  New CultureInfo("zh-HK").NumberFormatobjCulture.NumberNegativePattern = 1
  Return NumberToPrint.ToString("C", objCulture)
B. Dim objCulture As NumberFormatInfo = _
  New CultureInfo("zh-HK").NumberFormatobjCulture.CurrencyNegativePattern =
  1Return NumberToPrint.ToString("C", objCulture)
C. Dim objCulture As NumberFormatInfo = _
  New CultureInfo("zh-HK").NumberFormatReturn NumberToPrint.ToString("-{0}",
  objCulture)
D. Dim objCulture As NumberFormatInfo = _
  New CultureInfo("zh-HK").NumberFormatReturn NumberToPrint.ToString("()",
  objCulture)

```

Answer: B

Question: 14

Your application uses two threads, named thread One and thread Two.

You need to modify the code to prevent the execution of thread One until thread Two completes execution.

What should you do?

- A. Configure threadOne to run at a lower priority.
- B. Configure threadTwo to run at a higher priority.
- C. Use a WaitCallback delegate to synchronize the threads.
- D. Call the Sleep method of threadOne.
- E. Call the SpinLock method of threadOne.

Answer: C

Question: 15

You are developing a method to hash data with the Secure Hash Algorithm. The data is passed to your method as a byte array named message. You need to compute the hash of the incoming parameter by using SHA1. You also need to place the result into a byte array named hash. Which code segment should you use?

- A. Dim objSHA As New SHA1CryptoServiceProviderDim hash() As Byte = NothingobjSHA.TransformBlock(message, 0, message.Length, hash, 0)
- B. Dim objSHA As New SHA1CryptoServiceProviderDim hash() As Byte = BitConverter.GetBytes(objSHA.GetHashCode)
- C. Dim objSHA As New SHA1CryptoServiceProviderDim hash() As Byte = objSHA.ComputeHash(message)
- D. Dim objSHA As New SHA1CryptoServiceProviderobjSHA.GetHashCode()Dim hash() As Byte = objSHA.Hash

Answer: C

Question: 16

You are writing a custom dictionary. The custom-dictionary class is named MyDictionary. You need to ensure that the dictionary is type safe. Which code segment should you use?

- A. class MyDictionary : Dictionary<string, string>
 - B. class MyDictionary : HashTable
 - C. class MyDictionary : IDictionary
 - D. class MyDictionary { ... }
- Dictionary<string, string> t = new Dictionary<string, string>();MyDictionary dictionary = (MyDictionary)t;

Answer: A

Question: 17

You work as a developer at Company.com. You are creating an application that provides information about the local computer. The application contains a form that lists each logical drive with the drive properties, such as type, volume label, and capacity. You are required to write a procedure that retrieves properties of each logical drive on the local computer.

What should you do?

Arrange the appropriate actions in the correct order.

Actions, select from these	Actions, place here
Retrieve an instance of the FileSystemInfo class.	Place first, if any, here
Retrieve an instance of the DriveInfo class.	Place second, if any, here
Retrieve the drive capacity by using the DriveInfo.TotalSize property.	Place third, if any, here
Determine if the drive is available by using the FileSystemInfo.Attributes property.	Place fourth, if any, here
Retrieve the drive names of all logical drives on a computer by using the DriveInfo.GetDrives method.	Place fifth, if any, here
Retrieve the drive capacity by using the FileSystemInfo.Attributes property.	Place sixth, if any, here

Answer:

Actions, select from these	Actions, place here
Retrieve an instance of the FileSystemInfo class.	Retrieve the drive names of all logical drives on a computer by using the DriveInfo.GetDrives method.
	Retrieve an instance of the DriveInfo class.
	Retrieve the drive capacity by using the DriveInfo.TotalSize property.
Determine if the drive is available by using the FileSystemInfo.Attributes property.	Place fourth, if any, here
	Place fifth, if any, here
Retrieve the drive capacity by using the FileSystemInfo.Attributes property.	Place sixth, if any, here

Question: 18

You are developing an application for a client residing in Hong Kong.

You need to display negative currency values by using a minus sign. Which code segment should you use?

- A. `NumberFormatInfo^ culture =
gcnew CultureInfo("zh-HK"); NumberFormat; culture->NumberNegativePattern = 1;
return numberToPrint->ToString("C", culture);`
- B. `NumberFormatInfo^ culture =
gcnew CultureInfo("zh-HK"); NumberFormat; culture->CurrencyNegativePattern = 1;
return numberToPrint->ToString("C", culture);`
- C. `CultureInfo^ culture =
gcnew CultureInfo("zh-HK"); return numberToPrint->ToString("-(0)", culture);`
- D. `CultureInfo^ culture =
gcnew CultureInfo("zh-HK"); return numberToPrint->ToString("()", culture);`

Answer: B

Question: 19

You are developing a method to hash data with the Secure Hash Algorithm. The data is passed to your method as a byte array named **message**. You need to compute the hash of the incoming parameter by using **SHA1**. You also need to place the result into a byte array named **hash**. Which code segment should you use?

- A. `SHA1 ^sha = gcnew SHA1CryptoServiceProvider(); array<Byte>^hash = nullptr; sha->TransformBlock(message, 0, message->Length, hash, 0);`
- B. `SHA1 ^sha = gcnew SHA1CryptoServiceProvider(); array<Byte>^hash = BitConverter::GetBytes(sha->GetHashCode());`
- C. `SHA1 ^sha = gcnew SHA1CryptoServiceProvider(); array<Byte>^hash = sha->ComputeHash(message);`
- D. `SHA1 ^sha = gcnew SHA1CryptoServiceProvider(); sha->GetHashCode(); array<Byte>^hash = sha->Hash;`

Answer: C

Question: 20

You are writing an application that uses SOAP to exchange data with other applications. You use a Department class that inherits from ArrayList to send objects to another application. The Department object is named dept. You need to ensure that the application serializes the Department object for transport by using SOAP. Which code should you use?

- A. `SoapFormatter^ formatter = gcnew SoapFormatter();array<Byte>^ buffer = gcnew array<Byte>(dept->Capacity);MemoryStream^ stream = gcnew MemoryStream(buffer);for each (Object^ o in dept) {formatter->Serialize(stream, o);}`
- B. `SoapFormatter^ formatter = gcnew SoapFormatter();array<Byte>^ buffer = gcnew array<Byte>(dept->Capacity);MemoryStream^ stream = gcnew MemoryStream(buffer);formatter->Serialize(stream, dept);`
- C. `SoapFormatter^ formatter = gcnew SoapFormatter();MemoryStream^ stream = gcnew MemoryStream();for each (Object^ o in dept) {formatter->Serialize(stream, o);}`
- D. `SoapFormatter^ formatter = gcnew SoapFormatter();MemoryStream^ stream = gcnew MemoryStream();formatter->Serialize(stream, dept);`

Answer: D

Question: 21

You need to write a code segment that will create a common language runtime (CLR) unit of isolation within an application. Which code segment should you use?

- A. `Dim mySetup As AppDomainSetup = _AppDomain.CurrentDomain.SetupInformationmySetup.ShadowCopyFiles = "true"`
- B. `Dim myProcess As System.Diagnostics.Process myProcess = New System.Diagnostics.Process()`
- C. `Dim domain As AppDomain domain = AppDomain.CreateDomain("CompanyDomain")`
- D. `Dim myComponent As System.ComponentModel.ComponentmyComponent = New System.ComponentModel.Component()`

Answer: C

Question: 22

You work as a developer at Company.com. You are creating an assembly named Company1. Company1 contains a public method. The global cache contains a second assembly named Company2. You must ensure that the public method is only called from Company2. Which permission class should you use?

- A. `GacIdentityPermission`
- B. `PublisherIdentityPermission`
- C. `DataProtectionPermission`
- D. `StrongNameIdentityPermission`

Answer: D

Question: 23

You are developing an application that will use custom authentication and role-based security. You need to write a code segment to make the runtime assign an unauthenticated principal object to each running thread.

Which code segment should you use?

- A.** AppDomain^ domain =
AppDomain::CurrentDomain;domain->SetPrincipalPolicy(PrincipalPolicy::WindowsPrincipal);
- B.** AppDomain^ domain =
AppDomain::CurrentDomain;domain->SetThreadPrincipal(gcnew WindowsPrincipal(nullptr));
- C.** AppDomain^ domain =
AppDomain::CurrentDomain;domain->SetAppDomainPolicy(PolicyLevel::CreateAppDomainLevel());
- D.** AppDomain^ domain =
AppDomain::CurrentDomain;domain->SetPrincipalPolicy(PrincipalPolicy::UnauthenticatedPrincipal);

Answer: D

Question: 24

You write the following code. public delegate void FaxDocs(Object^ sender, FaxArgs^ args); You need to create an event that will invoke FaxDocs. Which code segment should you use?

- A.** public : static event FaxDocs^ Fax;
- B.** public : static event Fax^ FaxDocs;
- C.** public ref class FaxArgs : public EventArgs {
public :
String^ CoverPageInfo;
FaxArgs (String^ coverInfo) {
this->CoverPageInfo = coverInfo;
}};
- D.** public ref class FaxArgs : public EventArgs {
public :
String^ CoverPageInfo;};

Answer: A

Question: 25

You create an application to send a message by e-mail. An SMTP server is available on the local subnet. The SMTP server is named smtp.Company.com. To test the application, you use a source address, me@Company.com, and a target address, you@Company.com. You need to transmit the e-mail message. Which code segment should you use?

- A.** MailAddress addrFrom =
new MailAddress("me@Company.com", "Me");MailAddress addrTo =
new MailAddress("you@Company.com", "You");MailMessage message = new
MailMessage(addrFrom, addrTo);message.Subject = "Greetings!";message.Body =
"Test";message.Dispose();
- B.** string strSmtpClient = "mstp.Company.com";string strFrom = "me@Company.com";string strTo =
"you@Company.com";string strSubject = "Greetings!";string strBody = "Test";MailMessage
msg = new MailMessage(strFrom, strTo, strSubject, strSmtpClient);
- C.** MailAddress addrFrom = new MailAddress("me@Company.com");MailAddress addrTo = new
MailAddress("you@Company.com");MailMessage message = new MailMessage(addrFrom,
addrTo);message.Subject = "Greetings!";message.Body = "Test";SmtpClient client = new
SmtpClient("smtp.Company.com");client.Send(message);
- D.** MailAddress addrFrom =
new MailAddress("me@Company.com", "Me");MailAddress addrTo = new
MailAddress("you@Company.com", "You");MailMessage message = new
MailMessage(addrFrom, addrTo);message.Subject = "Greetings!";message.Body =

```
"Test";SocketInformation info = new SocketInformation();Socket client = new
Socket(info);System.Text.ASCIIEncoding enc = new System.Text.ASCIIEncoding();byte[]
msgBytes = enc.GetBytes(message.ToString());client.Send(msgBytes);
```

Answer: C

Question: 26

You are developing a custom-collection class.

You need to create a method in your class. You need to ensure that the method you create in your class returns a type that is compatible with the Foreach statement. Which criterion should the method meet?

- A.** The method must return a type of either IEnumerator or IEnumerable.
- B.** The method must return a type of IComparable.
- C.** The method must explicitly contain a collection.
- D.** The method must be the only iterator in the class.

Answer: A

Question: 27

You are developing an application to perform mathematical calculations. You develop a class named CalculationValues. You write a procedure named PerformCalculation that operates on an instance of the class. You need to ensure that the user interface of the application continues to respond while calculations are being performed. You need to write a code segment that calls the PerformCalculation procedure to achieve this goal. Which code segment should you use?

- A.**

```
private void PerformCalculation() {...} private void DoWork(){
Calculation Values myValues = new Calculation Values();
Thread newThread = new Thread(
new ThreadStart(PerformCalculation));
new Thread.Start(myValues);}
```
- B.**

```
private void PerformCalculation() {...} private void DoWork(){
Calculation Values myValues = new Calculation Values();
ThreadStart delStart = new
ThreadStart(PerformCalculation);
Thread newThread = new Thread(delStart);if (newThread.IsAlive)
{newThread.Start(myValues);}}
```
- C.**

```
private void PerformCalculation (CalculationValues values) {...} private void
DoWork(){
Calculation Values myValues = new Calculation Values();
Application.DoEvents();
PerformCalculation(myValues);
Application.DoEvents();}
```
- D.**

```
private void PerformCalculation(object values) {...} private void DoWork(){
Calculation Values myValues = new Calculation Values();
Thread newThread = new Thread(
new ParameterizedThreadStart(PerformCalculation));
newThread.Start(myValues);}
```

Answer: D

Question: 28

You write the following code. public delegate void FaxDocs(object sender, FaxArgs args); You need to create an event that will invoke FaxDocs. Which code segment should you use?

A. public static event FaxDocs Fax;
B. public static event Fax FaxDocs;
C. public class FaxArgs : EventArgs {
 private string coverPageInfo;
 public FaxArgs(string coverInfo) {
 this.coverPageInfo = coverPageInfo;
 }
 public string CoverPageInformation {
 get {return this.coverPageInfo;}
 }
 }
D. public class FaxArgs : EventArgs {
 private string coverPageInfo;
 public string CoverPageInformation {
 get {return this.coverPageInfo;}
 }
 }

Answer: A

Question: 29

You are developing a custom event handler to automatically print all open documents.
 The event handler helps specify the number of copies to be printed. You need to develop a
 custom event arguments class to pass as a parameter to the event handler.
 Which code segment should you use?

A. Public Class PrintingArgs
 Private _copies As Integer
 Public Sub New(ByVal numberOfCopies As Integer)
 Me._copies = numberOfCopies
 End Sub
 Public ReadOnly Property Copies() As Integer
 Get
 Return Me._copies
 End Get
 End PropertyEnd Class
B. Public Class PrintingArgs
 Inherits EventArgs
 Private _copies As Integer
 Public Sub New(ByVal numberOfCopies As Integer)
 Me._copies = numberOfCopies
 End Sub
 Public ReadOnly Property Copies() As Integer
 Get
 Return Me._copies
 End Get
 End PropertyEnd Class
C. Public Class PrintingArgs
 Private EventArgs As EventArgs
 Public Sub New(ByVal args As EventArgs)
 Me.EventArgs = args
 End Sub
 Public ReadOnly Property Args() As EventArgs
 Get
 Return EventArgs
 End Get
 End PropertyEnd Class
D. Public Class PrintingArgs

Inherits EventArgs
Private copies As Integer End Class

Answer: B

Question: 30

You write the following code segment to call a function from the Win32 Application Programming Interface (API) by using platform invoke.

`string personName = "N?el"; string msg = "Welcome" + personName + "to club!"; bool rc = User32API.MessageBox(0, msg, personName, 0);` You need to define a method prototype that can best marshal the string data. Which code segment should you use?

- A.** `[DllImport("user32", CharSet = CharSet.Ansi)] public static extern bool MessageBox(int hWnd, String text, String caption, uint type);`
- B.** `[DllImport("user32", EntryPoint = "MessageBoxA", CharSet = CharSet.Ansi)] public static extern bool MessageBox(int hWnd, [MarshalAs(UnmanagedType.LPWStr)] String text, [MarshalAs(UnmanagedType.LPWStr)] String caption, uint type);`
- C.** `[DllImport("user32", CharSet = CharSet.Unicode)] public static extern bool MessageBox(int hWnd, String text, String caption, uint type);`
- D.** `[DllImport("user32", EntryPoint = "MessageBoxA", CharSet = CharSet.Unicode)] public static extern bool MessageBox(int hWnd, [MarshalAs(UnmanagedType.LPWStr)] String text, [MarshalAs(UnmanagedType.LPWStr)] String caption, uint type);`

Answer: C

Question: 31

You are developing an application that dynamically loads assemblies from an application directory.

You need to write a code segment that loads an assembly named Company1.dll into the current application domain. Which code segment should you use?

- A.** `Dim domain As AppDomain = AppDomain.CurrentDomain Dim myPath As String = _ Path.Combine(domain.BaseDirectory, "Company1.dll") Dim asm As [Assembly] = [Assembly].LoadFrom(myPath)`
- B.** `Dim domain As AppDomain = AppDomain.CurrentDomain Dim myPath As String = _ Path.Combine(domain.BaseDirectory, "Company1.dll") Dim asm As [Assembly] = [Assembly].Load(myPath)`
- C.** `Dim domain As AppDomain = AppDomain.CurrentDomain Dim myPath As String = _ Path.Combine(domain.DynamicDirectory, "Company1.dll") Dim asm As [Assembly] = _ AppDomain.CurrentDomain.Load(myPath)`
- D.** `Dim domain As AppDomain = AppDomain.CurrentDomain Dim asm As [Assembly] = domain.GetData("Company1.dll")`

Answer: A

Question: 32

You need to read the entire contents of a file named Message.txt into a single string variable.

Which code segment should you use?

- A.** Dim result As String = Nothing
Dim reader As New StreamReader("Message.txt")
result = reader.Read().ToString()
- B.** Dim result As String = Nothing
Dim reader as New StreamReader("Message.txt")
result = reader.ReadToEnd()
- C.** Dim result As String = string.Empty
Dim reader As New StreamReader("Message.txt")
While Not reader.EndOfStream
result &= reader.ToString()
End While
- D.** Dim result as String = Nothing
Dim reader As New StreamReader("Message.txt")
result = reader.ReadLine()

Answer: B

Question: 33

You are developing an application that receives events asynchronously. You create a WqlEventQuery instance to specify the events and event conditions to which the application must respond. You also create a ManagementEventWatcher instance to subscribe to events matching the query. You need to identify the other actions you must perform before the application can receive events asynchronously. Which two actions should you perform? (Each correct answer presents part of the solution. Choose two.)

- A.** Start listening for events by calling the Start method of the ManagementEventWatcher.
- B.** Set up a listener for events by using the EventArrived event of the ManagementEventWatcher.
- C.** Use the WaitForNextEvent method of the ManagementEventWatcher to wait for the events.
- D.** Create an event handler class that has a method that receives an ObjectReadyEventArgs parameter.
- E.** Set up a listener for events by using the Stopped event of the ManagementEventWatcher.

Answer: A, B

Question: 34

You need to write a code segment that transfers the contents of a byte array named dataToSend by using a NetworkStream object named netStream. You need to use a cache of size 8,192 bytes. Which code segment should you use?

- A.** MemoryStream^ memStream = gcnew MemoryStream(8192);
memStream->Write(dataToSend, 0, (int) netStream->Length);
- B.** MemoryStream^ memStream = gcnew MemoryStream(8192);
netStream->Write(dataToSend, 0, (int) memStream->Length);
- C.** BufferedStream^ bufStream = gcnew BufferedStream(netStream, 8192);
bufStream->Write(dataToSend, 0, dataToSend->Length);
- D.** BufferedStream^ bufStream = gcnew BufferedStream(netStream);
bufStream->Write(dataToSend, 0, 8192);

Answer: C

Question: 35

You are writing a method to compress an array of bytes. The array is passed to the method in a parameter named document. You need to compress the incoming array of bytes and return the result as an array of bytes. Which code segment should you use?

- A.** MemoryStream strm = new MemoryStream(document);
DeflateStream deflate = new

```

DeflateStream(strm,
CompressionMode.Compress); byte[] result = new byte[document.Length];deflate.Write(result,
0, result.Length); return result;
B. MemoryStream strm = new MemoryStream(document);DeflateStream deflate = new
DeflateStream(strm,
CompressionMode.Compress);deflate.Write(docemtn, 0,
document.Length);deflate.Close();return strm.ToArray();
C. MemoryStream strm = new MemoryStream();DeflateStream deflate = new
DeflateStream(strm, CompressionMode.Compress);deflate.Write(document, 0,
document.Length);deflate.Close();return strm.ToArray();
D. MemoryStream inStream = new MemoryStream(document);DeflateStream deflate =
new DeflateStream(inStream, CompressionMode.Compress); MemoryStream outStream =
new MemoryStream();int b;while ((b = deflate.ReadByte()) != -1) {
outStream.WriteByte((byte)b);} return outStream.ToArray();

```

Answer: C

Question: 36

You need to select a class that is optimized for key-based item retrieval from both small and large collections. Which class should you choose?

- A. OrderedDictionary class
- B. HybridDictionary class
- C. ListDictionary class
- D. Hashtable class

Answer: B

Question: 37

You are writing an application that uses SOAP to exchange data with other applications. You use a Department class that inherits from ArrayList to send objects to another application. The Department object is named dept. You need to ensure that the application serializes the Department object for transport by using SOAP. Which code should you use?

- A. SoapFormatter formatter = new SoapFormatter();byte[] buffer = new byte[dept.Capacity];MemoryStream stream = new MemoryStream(buffer); foreach (object o in dept) { formatter.Serialize(stream, o);}
- B. SoapFormatter formatter = new SoapFormatter();byte[] buffer = new byte[dept.Capacity];MemoryStream stream = new MemoryStream(buffer); formatter.Serialize(stream, dept);
- C. SoapFormatter formatter = new SoapFormatter();MemoryStream stream = new MemoryStream();foreach (object o in dept) { Formatter.Serialize(stream, o);}
- D. SoapFormatter formatter = new SoapFormatter();MemoryStream stream = new MemoryStream(); formatter.Serialize(stream, dept);

Answer: D

Question: 38

You create a class library that contains the class hierarchy defined in the following code segment. (Line numbers are included for reference only.)

```

01. public ref class Employee {02.03. public : 04.
String^ Name;05. };06.07. public ref class Manager : public Employee {08.09.
public :10.

```

int Level;11. };12.13. public ref class Group {14.15. public : 16. array<Employee^>^ Employees;17. }; You create an instance of the Group class. You populate the fields of the instance. When you attempt to serialize the instance by using the Serialize method of the XmlSerializer class, you receive InvalidOperationException. You also receive the following error message: "There was an error generating the XML document."

You need to modify the code segment so that you can successfully serialize instances of the Group class by using the XmlSerializer class. You also need to ensure that the XML output contains an element for all public fields in the class hierarchy. What should you do?

A. Insert the following code between lines 14 and 15 of the code segment:

```
[XmlElement(Type = typeof(Employee))]
```

```
[XmlElement(Type = typeof(Manager))]
```

B. Insert the following code between lines 14 and 15 of the code segment:

```
[XmlElement(Type = typeof(Employees))]
```

C. Insert the following code between lines 14 and 15 of the code segment:

```
[XmlAttribute(ElementName="Employees")]
```

D. Insert the following code between lines 3 and 4 of the code segment:

```
[XmlElement(Type = typeof(Employee))]
```

andInsert the following code segment between lines 8 and 9 of the code segment:

```
[XmlElement(Type = typeof(Manager))]
```

Answer: A

Question: 39

You need to write a code segment that performs the following tasks: ?

Retrieves the name of each paused service. ?

Passes the name to the Add method of Collection1. Which code segment should you use?

A. Dim searcher As ManagementObjectSearcher = _New ManagementObjectSearcher(_

```
"Select * from Win32_Service where State = 'Paused'")For Each svc As
```

```
ManagementObject In searcher.Get()
```

```
Collection1.Add(svc("DisplayName"))Next
```

B. Dim searcher As ManagementObjectSearcher = _New ManagementObjectSearcher (_

```
"Select * from Win32_Service", "State = 'Paused'")For Each svc As ManagementObject
```

```
In searcher.Get()
```

```
Collection1.Add(svc("DisplayName"))Next
```

C. Dim searcher As ManagementObjectSearcher = _New ManagementObjectSearcher(_

```
"Select * from Win32_Service")For Each svc As ManagementObject In searcher.Get()
```

```
If svc("State").ToString() = "Paused" Then
```

```
Collection1.Add(svc("DisplayName"))
```

```
End IfNext
```

D. Dim searcher As New ManagementObjectSearcher()searcher.Scope = New

```
ManagementScope("Win32_Service")For Each svc As ManagementObject In
```

```
searcher.Get()
```

```
If svc("State").ToString() = "Paused" Then
```

```
Collection1.Add(svc("DisplayName"))
```

```
End IfNext
```

Answer: A

Question: 40

You are writing a method that accepts a string parameter named message.

Your method must break the message parameter into individual lines of text and pass each line to

a second method named Process.

Which code segment should you use?

A. Dim reader As New
 StreamReader(message)ProcessMessage(reader.ReadToEnd())reader.Close()
B. Dim reader As New StreamReader(message)While reader.Peek() <> -1
 Dim line as String = reader.Read().ToString()
 ProcessMessage(line)End Whilereader.Close()
C. Dim reader As New
 StreamReader(message)ProcessMessage(reader.ToString())reader.Close()
D. Dim reader As New StreamReader(message)While reader.Peek() <> -1
 ProcessMessage(reader.ReadLine())End Whilereader.Close()

Answer: D

Question: 41

You need to create a class definition that is interoperable along with COM. You need to ensure that COM applications can create instances of the class and can call the GetAddress method. Which code segment should you use?

A. public class Customer {
 string addressString;
 public Customer(string address) { addressString = address; }
 public string GetAddress() { return addressString; }
B. public class Customer {
 static string addressString;
 public Customer() { }
 public static string GetAddress() { return addressString; }
C. public class Customer {
 string addressString;
 public Customer() { }
 public string GetAddress() { return addressString; }
D. public class Customer {
 string addressString;
 public Customer() { }
 internal string GetAddress() { return addressString; }
 }

Answer: C

Question: 42

You are creating a class that performs complex financial calculations. The class contains a method named GetCurrentRate that retrieves the current interest rate and a variable named currRate that stores the current interest rate.

You write serialized representations of the class.

You need to write a code segment that updates the currRate variable with the current interest rate when an instance of the class is deserialized. Which code segment should you use?

A. [OnSerializing]void UpdateValue (StreamingContext^ context) {
 currRate = GetCurrentRate();}
B. [OnSerializing]void UpdateValue(SerializationInfo^ info) {
 info->AddValue("currentRate", GetCurrentRate());}
C. [OnDeserializing]void UpdateValue(SerializationInfo^ info) {
 info->AddValue("currentRate", GetCurrentRate());}
D. [OnDeserialized]void UpdateValue(StreamingContext^ context) {
 currRate = GetCurrentRate();}

Answer: D

Question: 43

You are developing a class library. Portions of your code need to access system environment

variables.

You need to force a runtime `SecurityException` only when callers that are higher in the call stack do not have the necessary permissions.

Which call method should you use?

- A. `set.Demand();`
- B. `set.Assert();`
- C. `set.PermitOnly();`
- D. `set.Deny();`

Answer: A

Question: 44

You are developing a fiscal report for a customer. Your customer has a main office in the United States and a satellite office in Mexico.

You need to ensure that when users in the satellite office generate the report, the current date is displayed in Mexican Spanish format. Which code segment should you use?

- A. `CultureInfo^ culture = gcnew CultureInfo("es-MX", false);DateTimeFormatInfo^ dtfi = culture->DateTimeFormat;DateTime^ dt = gcnew DateTime(DateTime::Today::Year, DateTime::Today::Month, DateTime::Today::Day);String^ dateString = dt->ToString(dtfi->LongDatePattern);`
- B. `Calendar^ cal = gcnew CultureInfo("es-MX", false)::Calendar; DateTime^dt = gcnew DateTime(DateTime::Today::Year, DateTime::Today::Month, DateTime::Today::Day);String^dateString = dt-> ToString();`
- C. `String^ dateString = DateTimeFormatInfo::CurrentInfo::GetMonthName(DateTime::Today::Month);`
- D. `String^ dateString = DateTime::Today::Month::ToString("es-MX");`

Answer: A

Question: 45

You create an application that stores information about your customers who reside in various regions. You are developing internal utilities for this application.

You need to gather regional information about your customers in Canada.

Which code segment should you use?

- A. `for each (CultureInfo^ culture in CultureInfo::GetCultures(CultureTypes::SpecificCultures)) {
// Output the region information...}`
- B. `CultureInfo^ cultureInfo = gcnew CultureInfo("CA");
// Output the region information...`
- C. `RegionInfo^ regionInfo = gcnew RegionInfo("CA
// Output the region information...`
- D. `RegionInfo^ regionInfo = gcnew RegionInfo("");if(regionInfo->Name == "CA"){
// Output the region information...}`

Answer: C

Question: 46

You need to generate a report that lists language codes and region codes.

Which code segment should you use?

- A. `for each (CultureInfo^ culture in CultureInfo::GetCultures(CultureTypes::SpecificCultures)) {
// Output the culture information...}`
- B. `CultureInfo^ culture = gcnew CultureInfo(""); CultureTypes^ types = culture->CultureTypes;`

```
// Output the culture information...
C. for each (CultureInfo^ culture in
CultureInfo::GetCultures(CultureTypes::NeutralCultures)) {
// Output the culture information...}
D. for each (CultureInfo^ culture in
CultureInfo::GetCultures(CultureTypes::ReplacementCultures)) {
// Output the culture information...}
```

Answer: A

Question: 47

You are developing a method to hash data with the Secure Hash Algorithm. The data is passed to your method as a byte array named message. You need to compute the hash of the incoming parameter by using SHA1. You also need to place the result into a byte array named hash. Which code segment should you use?

- A. SHA1 sha = new SHA1CryptoServiceProvider();byte[] hash = null;sha.TransformBlock(message, 0, message.Length, hash, 0);
- B. SHA1 sha = new SHA1CryptoServiceProvider();byte[] hash = BitConverter.GetBytes(sha.GetHashCode());
- C. SHA1 sha = new SHA1CryptoServiceProvider();byte[] hash = sha.ComputeHash(message);
- D. SHA1 sha = new SHA1CryptoServiceProvider();sha.GetHashCode();byte[] hash = sha.Hash;

Answer: C

Question: 48

You are developing a method to hash data for later verification by using the MD5 algorithm. The data is passed to your method as a byte array named message. You need to compute the hash of the incoming parameter by using MD5. You also need to place the result into a byte array. Which code segment should you use?

- A. HashAlgorithm algo = HashAlgorithm.Create("MD5");byte[] hash = algo.ComputeHash(message);
- B. HashAlgorithm algo = HashAlgorithm.Create("MD5");byte[] hash = BitConverter.GetBytes(algo.GetHashCode());
- C. HashAlgorithm algo;algo = HashAlgorithm.Create(message.ToString());byte[] hash = algo.Hash;
- D. HashAlgorithm algo = HashAlgorithm.Create("MD5");byte[] hash = null;algo.TransformBlock(message, 0, message.Length, hash, 0);

Answer: A

Question: 49

You create a method that runs by using the credentials of the end user. You need to use Microsoft Windows groups to authorize the user. You must add a code segment that identifies whether a user is in the local group named Clerk. Which code segment should you use?

- A. Dim objUser As WindowsIdentity = WindowsIdentity.GetCurrentFor Each objGroup As IdentityReference In objUser.Groups Dim objNT As NTAccount = _ DirectCast(objGroup.Translate(_ Type.GetType("NTAccount")), NTAccount) Dim blnAuth As Boolean = objNT.Value.Equals(_ Environment.MachineName & "\Clerk") If blnAuth Then Exit ForNext

B. Dim objUser As WindowsPrincipal = _
DirectCast(Thread.CurrentPrincipal, WindowsPrincipal)Dim blnAuth As Boolean =
objUser.IsInRole("Clerk")

C. Dim objUser As GenericPrincipal = _
DirectCast(Thread.CurrentPrincipal, GenericPrincipal)Dim blnAuth As Boolean =
objUser.IsInRole("Clerk")

D. Dim objUser As WindowsPrincipal = _
DirectCast(Thread.CurrentPrincipal, WindowsPrincipal)Dim blnAuth As Boolean = _
objUser.IsInRole(Environment.MachineName)

Answer: B

Question: 50

You write the following code to call a function from the Win32 Application Programming Interface (API) by using platform invoke.

int rc = MessageBox(hWnd, text, caption, type); You need to define a method prototype. Which code segment should you use?

A. [DllImport("user32")]extern int MessageBox(int hWnd, String^ text,
String^ caption, uint type);

B. [DllImport("user32")]extern int MessageBoxA(int hWnd, String^ text,
String^ caption, uint type);

C. [DllImport("user32")]extern int Win32API_User32_MessageBox(
Int hWnd, String^ text, String^ caption, uint type);

D. [DllImport("C:\\WINDOWS\\system32\\user32.dll")]extern int MessageBox(int
hWnd, String^ text,
String^ caption, uint type);

Answer: A

Question: 51

You need to create a dynamic assembly named MyAssembly. You also need to save the assembly to disk. Which code segment should you use?

A. AssemblyName myAssemblyName =
new AssemblyName();myAssemblyName.Name = "MyAssembly";AssemblyBuilder
myAssemblyBuilder =
AppDomain.CurrentDomain.DefineDynamicAssembly
(myAssemblyName,
AssemblyBuilderAccess.Run);myAssemblyBuilder.Save("MyAssembly.dll");

B. AssemblyName myAssemblyName =
new AssemblyName();myAssemblyName.Name = "MyAssembly";AssemblyBuilder
myAssemblyBuilder =
AppDomain.CurrentDomain.DefineDynamicAssembly
(myAssemblyName,
AssemblyBulderAccess.Save);myAssemblyBuilder.Save("MyAssembly.dll");

C. AssemblyName myAssemblyName =
new AssemblyName();AssemblyBuilder myAssemblyBuilder =
AppDomain.CurrentDomain.DefineDynamicAssembly
(myAssemblyName,
AssemblyBuilderAccess.RunAndSave);myAssemblyBuilder.Save("MyAssembly.dll");

D. AssemblyName myAssemblyName =
new AssemblyName("MyAssembly");AssemblyBuilder myAssemblyBuilder =
AppDomain.CurrentDomain.DefineDynamicAssembly
(myAssemblyName,
AssemblyBuilderAccess.Save);myAssemblyBuilder.Save("c:\\MyAssembly.dll");

Answer: B

Question: 52

You need to call an unmanaged function from your managed code by using platform invoke services. What should you do?

- A.** Create a class to hold DLL functions and then create prototype methods by using managed code.
- B.** Register your assembly by using COM and then reference your managed code from COM.
- C.** Export a type library for your managed code.
- D.** Import a type library as an assembly and then create instances of COM object.

Answer: A

Question: 53

You use Reflection to obtain information about a method named MyMethod.

You need to ascertain whether MyMethod is accessible to a derived class. What should you do?

- A.** Call the IsAssembly property of the MethodInfo class.
- B.** Call the IsVirtual property of the MethodInfo class.
- C.** Call the IsStatic property of the MethodInfo class.
- D.** Call the IsFamily property of the MethodInfo class.

Answer: D

Question: 54

You need to identify a type that meets the following criteria: ?

Is always a number.?

Is not greater than 65,535. Which type should you choose?

- A.** System.UInt16
- B.** int
- C.** System.String
- D.** System.IntPtr

Answer: A

Question: 55

You are writing code for user authentication and authorization. The username, password, and roles are stored in your application data store.

You need to establish a user security context that will be used for authorization checks such as IsInRole. You write the following code segment to authorize the user.

if (!TestPassword(userName, password))

throw new Exception("could not authenticate user");String[] userRolesArray =

LookupUserRoles(userName); You need to complete this code so that it establishes the user security context. Which code segment should you use?

- A.** GenericIdentity ident = new GenericIdentity(userName);GenericPrincipal currentUser = new GenericPrincipal(ident, userRolesArray);Thread.CurrentPrincipal = currentUser;
- B.** WindowsIdentity ident = new WindowsIdentity(userName);WindowsPrincipal currentUser = new WindowsPrincipal(ident);Thread.CurrentPrincipal = currentUser;
- C.** NTAccount userNTName = new NTAccount(userName);GenericIdentity ident = new GenericIdentity(userNTName.Value);GenericPrincipal currentUser= new GenericPrincipal(ident, userRolesArray);Thread.CurrentPrincipal = currentUser;
- D.** IntPtr token = IntPtr.Zero;token = LogonUserUsingInterop(username,

```
encryptedPassword);WindowsImpersonationContext ctx =  
WindowsIdentity.Impersonate(token);
```

Answer: A

Question: 56

You are developing an application for a client residing in Hong Kong.

You need to display negative currency values by using a minus sign. Which code segment should you use?

- A.** `NumberFormatInfo culture = new CultureInfo("zh-HK").NumberFormat;
culture.NumberNegativePattern = 1; return numberToPrint.ToString("C", culture);`
- B.** `NumberFormatInfo culture = new CultureInfo("zh-HK").NumberFormat;
culture.CurrencyNegativePattern = 1; return numberToPrint.ToString("C", culture);`
- C.** `CultureInfo culture = new CultureInfo("zh-HK");return numberToPrint.ToString("-(0)", culture);`
- D.** `CultureInfo culture = new CultureInfo("zh-HK"); return numberToPrint.ToString("()", culture);`

Answer: B

Question: 57

You are developing an application that will perform mathematical calculations.

You need to ensure that the application is able to perform multiple calculations simultaneously. What should you do?

- A.** Set the `IdealProcessor` property of the `ProcessThread` object.
- B.** Set the `ProcessorAffinity` property of the `ProcessThread` object.
- C.** For each calculation, call the `QueueUserWorkItem` method of the `ThreadPool` class.
- D.** Set the `Process.GetCurrentProcess().BasePriority` property to `High`.

Answer: C

Question: 58

You develop a service application named `PollingService` that periodically calls long-running procedures. These procedures are called from the `DoWork` method.

You use the following service application code.

```
ref class PollingService : public ServiceBase {  
public :  
static bool blnExit = false;  
protected :  
override void OnStart(String^ args) {  
do {  
DoWork();  
} while (!blnExit);  
}  
override void OnStop() {  
blnExit = true;  
}  
private :  
void DoWork() {} };
```

When you attempt to start the service, you receive the following error message: Could not start the `PollingService` service on the local computer. Error 1053: The service did not respond to the start or control request in a timely fashion. You need to modify the service application code so that the service starts properly. What should you do?

- A.** Move the loop code into the constructor of the service class from the `OnStart` method.
- B.** Drag a timer component onto the design surface of the service. Move the calls to the longrunning

procedure from the OnStart method into the Tick event procedure of the timer, set the Enabled property of the timer to True, and call the Start method of the timer in the OnStart method.

C. Add a class-level System.Timers.Timer variable to the service class code. Move the call to the DoWork method into the Elapsed event procedure of the timer, set the Enabled property of the timer to True, and call the Start method of the timer in the OnStart method.

D. Move the loop code from the OnStart method into the DoWork method.

Answer: C

Question: 59

You are creating an assembly named Company1. Company1 contains a public method.

The global cache contains a second assembly named Company2.

You must ensure that the public method is only called from Company2.

Which permission class should you use?

- A.** GacIdentityPermission
- B.** PublisherIdentityPermission
- C.** DataProtectionPermission
- D.** StrongNameIdentityPermission

Answer: D

Question: 60

You are creating a strong-named assembly named Company1 that will be used in multiple applications. Company1 will be rebuilt frequently during the development cycle. You need to ensure that each time the assembly is rebuilt it works correctly with each application that uses it. You need to configure the computer on which you develop Company1 such that each application uses the latest build of Company1.

Which two actions should you perform? (Each correct answer presents part of the solution.

Choose two.)

A. Create a DEVPATH environment variable that points to the build output directory for the strong-named assembly.

B. Add the following XML element to the machine configuration file:

```
<developmentMode developerInstallation="true"/>
```

C. Add the following XML element to the machine configuration file:

```
<dependentAssembly>
<assemblyIdentity name="Company1"
publicKeyToken="32ab4ba45e0a69a1"
language="en-US" version="*. *.*.*" />
<publisherPolicy apply="no" />
</dependentAssembly>
```

D. Add the following XML element to the configuration file of each application that uses the strong-named assembly:

```
<supportedRuntime version="*. *.*.*" />
```

E. Add the following XML element to the configuration file of each application that uses the strong-named assembly:

```
<dependentAssembly>
<assemblyIdentity name="Company1"
publicKeyToken="32ab4ba45e0a69a1"
language="en-US" version="*. *.*.*" />
<bindingRedirect newVersion="*. *.*.*"/>
</dependentAssembly>
```

Answer: A, B

Question: 61

You are creating a class to compare a specially-formatted string. The default collation comparisons do not apply. You need to implement the `IComparable<string>` interface. Which code segment should you use?

- A.** `public ref class Person : public IComparable<String^>{
public : virtual Int32 CompareTo(String^ other){
}}}`
- B.** `public ref class Person : public IComparable<String^>{
public : virtual Int32 CompareTo(Object^ other){
}}}`
- C.** `public ref class Person : public IComparable<String^>{
public : virtual Boolean CompareTo(String^ other){
}}}`
- D.** `public ref class Person : public IComparable<String^>{
public : virtual Boolean CompareTo(Object^ other){
}}}`

Answer: A

Question: 62

You are developing a method to hash data for later verification by using the MD5 algorithm. The data is passed to your method as a byte array named `message`. You need to compute the hash of the incoming parameter by using MD5. You also need to place the result into a byte array. Which code segment should you use?

- A.** `Dim objAlgo As HashAlgorithm = HashAlgorithm.Create("MD5")Dim hash() As Byte = objAlgo.ComputeHash(message)`
- B.** `Dim objAlgo As HashAlgorithm = HashAlgorithm.Create("MD5")Dim hash() As Byte = BitConverter.GetBytes(objAlgo.GetHashCode)`
- C.** `Dim objAlgo As HashAlgorithmobjAlgo = HashAlgorithm.Create(message.ToString)Dim hash() As Byte = objAlgo.Hash`
- D.** `Dim objAlgo As HashAlgorithm = HashAlgorithm.Create("MD5")Dim hash() As ByteobjAlgo.TransformBlock(message, 0, message.Length, hash, 0)`

Answer: A

Question: 63

You are creating a strong-named assembly named `Company1` that will be used in multiple applications. `Company1` will be rebuilt frequently during the development cycle. You need to ensure that each time the assembly is rebuilt it works correctly with each application that uses it. You need to configure the computer on which you develop `Company1` such that each application uses the latest build of `Company1`. Which two actions should you perform? (Each correct answer presents part of the solution. Choose two.)

- A.** Create a `DEVPATH` environment variable that points to the build output directory for the strong-named assembly.
- B.** Add the following XML element to the machine configuration file:
`<developmentMode developerInstallation="true"/>`
- C.** Add the following XML element to the machine configuration file:
`<dependentAssembly>
<assemblyIdentity name="Company1"
publicKeyToken="32ab4ba45e0a69a1"
language="en-US" version="*. *.*.*" />
<publisherPolicy apply="no" />`

</dependentAssembly>

D. Add the following XML element to the configuration file of each application that uses the strong-named assembly:

```
<supportedRuntime version="*.*.*" />
```

E. Add the following XML element to the configuration file of each application that uses the strong-named assembly:

```
<dependentAssembly>
```

```
<assemblyIdentity name="Company1"
```

```
publicKeyToken="32ab4ba45e0a69a1"
```

```
language="en-US" version="*.*.*" />
```

```
<bindingRedirect newVersion="*.*.*" />
```

```
</dependentAssembly>
```

Answer: A, B

Question: 64

You need to return the contents of an isolated storage file as a string. The file is machine-scoped and is named Settings.dat. Which code segment should you use?

A. IsolatedStorageFileStream^ isoStream;isoStream = gcnew IsolatedStorageFileStream("Settings.dat", FileMode::Open); String^ result = (gcnew StreamReader(isoStream))->ReadToEnd();

B. IsolatedStorageFile^ isoFile;isoFile = IsolatedStorageFile::GetMachineStoreForAssembly(); IsolatedStorageFileStream^ isoStream;isoStream = gcnew IsolatedStorageFileStream("Settings.dat", FileMode::Open, isoFile); String^ result = (gcnew StreamReader(isoStream))->ReadToEnd();

C. IsolatedStorageFileStream^ isoStream;isoStream = gcnew IsolatedStorageFileStream("Settings.dat", FileMode::Open);String^ result = isoStream->ToString();

D. IsolatedStorageFile^ isoFile;isoFile = IsolatedStorageFile::GetMachineStoreForAssembly(); IsolatedStorageFileStream^ isoStream;isoStream = gcnew IsolatedStorageFileStream("Settings.dat", FileMode::Open, isoFile); String^ result = isoStream->ToString();

Answer: B

Question: 65

You are developing a fiscal report for a customer. Your customer has a main office in the United States and a satellite office in Mexico.

You need to ensure that when users in the satellite office generate the report, the current date is displayed in Mexican Spanish format. Which code segment should you use?

A. Dim DTFORMAT As DateTimeFormatInfo = _
New CultureInfo("es-MX", False).DateTimeFormatDim DT As New DateTime(_
DateTime.Today.Year, DateTime.Today.Month, DateTime.Today.Day)Dim strDate As
String = _
DT.ToString(DTFORMAT.LongDatePattern)

B. Dim objCalendar As Calendar = _
New CultureInfo("es-MX", False).CalendarDim DT As New DateTime(_
DateTime.Today.Year, DateTime.Today.Month, DateTime.Today.Day)Dim strDate As
String = DT.ToString

C. Dim strDate As String = _
DateTimeFormatInfo.CurrentInfo.GetMonthName(_
DateTime.Today.Month)

D. Dim strDate As String = _
DateTime.Today.Month.ToString("es-MX")

Answer: A

Question: 66

You are defining a class named `CompanyClass` that contains several child objects. `CompanyClass` contains a method named `ProcessChildren` that performs actions on the child objects. `CompanyClass` objects will be serializable. You need to ensure that the `ProcessChildren` method is executed after the `CompanyClass` object and all its child objects are reconstructed. Which two actions should you perform? (Each correct answer presents part of the solution. Choose two.)

- A. Apply the `OnDeserializing` attribute to the `ProcessChildren` method.
- B. Specify that `CompanyClass` implements the `IDeserializationCallback` interface.
- C. Specify that `CompanyClass` inherits from the `ObjectManager` class.
- D. Apply the `OnSerialized` attribute to the `ProcessChildren` method.
- E. Create a `GetObjectData` method that calls `ProcessChildren`.
- F. Create an `OnDeserialization` method that calls `ProcessChildren`.

Answer: B, F

Question: 67

You need to create a method to clear a `Queue` named `q`. Which code segment should you use?

- A.

```
for each (Object^ e in q) {  
    q.Dequeue();  
}
```
- B.

```
for each (Object^ e in q) {  
    q.Enqueue(0);  
}
```
- C.

```
q.Clear();
```
- D.

```
q.Dequeue();
```

Answer: C

Question: 68

You need to write a code segment that transfers the first 80 bytes from a stream variable named `stream1` into a new byte array named `byteArray`. You also need to ensure that the code segment assigns the number of bytes that are transferred to an integer variable named `bytesTransferred`. Which code segment should you use?

- A.

```
bytesTransferred = stream1->Read(byteArray, 0, 80);
```
- B.

```
for(int i = 0; i < 80; i++){  
    stream1->WriteByte(byteArray[i]);  
    bytesTransferred = i;  
    if (!stream1->CanWrite) {  
        break;  
    }  
}
```
- C.

```
while (bytesTransferred < 80) {  
    stream1->Seek(1, SeekOrigin::Current);  
    byteArray[bytesTransferred++] =  
        Convert::ToByte(stream1->ReadByte());  
}
```
- D.

```
stream1->Write(byteArray, 0, 80); bytesTransferred = byteArray->Length;
```

Answer: A

Question: 69

You are developing an application that dynamically loads assemblies from an application directory. You need to write a code segment that loads an assembly named `Company1.dll` into the current

application domain. Which code segment should you use?

- A.** AppDomain domain = AppDomain.CurrentDomain;string myPath = Path.Combine(domain.BaseDirectory, "Company1.dll");Assembly asm = Assembly.LoadFrom(myPath);
- B.** AppDomain domain = AppDomain.CurrentDomain;string myPath = Path.Combine(domain.BaseDirectory, "Company1.dll");Assembly asm = Assembly.Load(myPath);
- C.** AppDomain domain = AppDomain.CurrentDomain;string myPath = Path.Combine(domain.DynamicDirectory, "Company1.dll");Assembly asm = AppDomain.CurrentDomain.Load(myPath);
- D.** AppDomain domain = AppDomain.CurrentDomain;Assembly asm = domain.GetData("Company1.dll");

Answer: A

Question: 70

You are developing an application that will use custom authentication and role-based security.

You need to write a code segment to make the runtime assign an unauthenticated principal object to each running thread.

Which code segment should you use?

- A.** Dim objDomain As AppDomain = AppDomain.CurrentDomainobjDomain.SetPrincipalPolicy(_ PrincipalPolicy.WindowsPrincipal)
- B.** Dim objDomain As AppDomain = AppDomain.CurrentDomainobjDomain.SetThreadPrincipal(New WindowsPrincipal(Nothing))
- C.** Dim objDomain As AppDomain = AppDomain.CurrentDomainobjDomain.SetAppDomainPolicy(_ PolicyLevel.CreateAppDomainLevel())
- D.** Dim objDomain As AppDomain = AppDomain.CurrentDomainobjDomain.SetPrincipalPolicy(_ PrincipalPolicy.UnauthenticatedPrincipal)

Answer: D

Question: 71

You need to create a method to clear a Queue named q. Which code segment should you use?

- A.** Dim e As ObjectFor Each e In qq.Dequeue()Next
- B.** Dim e As ObjectFor Each e In qq.Enqueue(Nothing)Next
- C.** q.Clear()
- D.** q.Dequeue()

Answer: C

Question: 72

You develop a service application that needs to be deployed. Your network administrator creates a specific user account for your service application. You need to configure your service application to run in the context of this specific user account. What should you do?

- A.** Prior to installation, set the StartType property of the ServiceInstaller class.
- B.** Prior to installation, set the Account, Username, and Password properties of the ServiceProcessInstaller class.

- C. Use the CONFIG option of the net.exe command-line tool to install the service.
- D. Use the installutil.exe command-line tool to install the service.

Answer: B

Question: 73

You need to create a class definition that is interoperable along with COM. You need to ensure that COM applications can create instances of the class and can call the GetAddress method. Which code segment should you use?

- A.** Public Class Customer
Private m_AddressString As String
Public Sub New(ByVal Address As String)
m_AddressString = Address
End Sub
Public Function GetAddress() As String
Return m_AddressString
End FunctionEnd Class
- B.** Public Class Customer
Shared m_AddressString As String
Public Sub New()
End Sub
Public Shared Function GetAddress() As String
Return m_AddressString
End FunctionEnd Class
- C.** Public Class Customer
Private m_AddressString As String
Public Sub New()
End Sub
Public Function GetAddress() As String
Return m_AddressString
End FunctionEnd Class
- D.** Public Class Customer
Private m_AddressString As String
Public Sub New()
End Sub
Private Function GetAddress() As String
Return m_AddressString
End FunctionEnd Class

Answer: C

Question: 74

You are creating a class that uses unmanaged resources. This class maintains references to managed resources on other objects. You need to ensure that users of this class can explicitly release resources when the class instance ceases to be needed. Which three actions should you perform? (Each correct answer presents part of the solution. Choose three.)

- A.** Define the class such that it inherits from the WeakReference class.
- B.** Define the class such that it implements the IDisposable interface.
- C.** Create a class destructor that calls methods on other objects to release the managed resources.
- D.** Create a class destructor that releases the unmanaged resources.
- E.** Create a Dispose method that calls System.GC.Collect to force garbage collection.
- F.** Create a Dispose method that releases unmanaged resources and calls methods on other objects to release the managed resources.

Answer: B, D, F

Question: 75

You develop a service application that needs to be deployed. Your network administrator creates a specific user account for your service application. You need to configure your service application to run in the context of this specific user account. What should you do?

- A.** Prior to installation, set the StartType property of the ServiceInstaller class.
- B.** Prior to installation, set the Account, Username, and Password properties of the ServiceProcessInstaller class.
- C.** Use the CONFIG option of the net.exe command-line tool to install the service.
- D.** Use the installutil.exe command-line tool to install the service.

Answer: B

Question: 76

You use Reflection to obtain information about a method named MyMethod. You need to ascertain whether MyMethod is accessible to a derived class. What should you do?

- A.** Call the IsAssembly property of the MethodInfo class.
- B.** Call the IsVirtual property of the MethodInfo class.
- C.** Call the IsStatic property of the MethodInfo class.
- D.** Call the IsFamily property of the MethodInfo class.

Answer: D

Question: 77

You need to generate a report that lists language codes and region codes. Which code segment should you use?

- A.** For Each objCulture As CultureInfo In
_CultureInfo.GetCultures(CultureTypes.SpecificCultures)
...Next
- B.** Dim objCulture As New CultureInfo("")Dim objTypes As CultureTypes =
objCulture.CultureTypes
...
- C.** For Each objCulture As CultureInfo In
_CultureInfo.GetCultures(CultureTypes.NeutralCultures)
...Next
- D.** For Each objCulture As CultureInfo In
_CultureInfo.GetCultures(CultureTypes.ReplacementCultures)
...Next

Answer: A

Question: 78

You are developing a class library that will open the network socket connections to computers on the network. You will deploy the class library to the global assembly cache and grant it full trust. You write the following code to ensure usage of the socket connections.

```
Dim objPermission As SocketPermission = New  
_SocketPermission(System.Security.Permissions.PermissionState.Unrestricted)objPermission.As  
sert()
```

Some of the applications that use the class library might not have the necessary permissions to open the network socket connections.

You need to cancel the assertion.

Which code segment should you use?

- A. CodeAccessPermission.RevertAssert()
- B. CodeAccessPermission.RevertDeny()
- C. objPermission.Deny()
- D. objPermission.PermitOnly()

Answer: A

Question: 79

You are writing an application that uses SOAP to exchange data with other applications. You use a Department class that inherits from ArrayList to send objects to another application. The Department object is named dept. You need to ensure that the application serializes the Department object for transport by using SOAP. Which code should you use?

- A. Dim formatter As New SoapFormatter()Dim buffer As Byte() = New Byte(dept.Capacity) {}Dim myStream As New MemoryStream(buffer) Dim o As ObjectFor Each o In deptformatter.Serialize(myStream, o)Next
- B. Dim formatter As New SoapFormatter()Dim buffer As Byte() = New Byte(dept.Capacity)Dim myStream As New MemoryStream(buffer)formatter.Serialize(myStream, dept)
- C. Dim formatter As New SoapFormatter()Dim myStream As New MemoryStream()Dim o as ObjectFor Each o In deptformatter.Serialize(myStream, o)Next
- D. Dim formatter As New SoapFormatter()Dim myStream As New MemoryStream()formatter.Serialize(myStream, dept)

Answer: D

Actions, select from these	Actions, place here
	Create a new FileSecurity object.
	Create a new FileSystemAccessRule object for each permission that you need, and add each rule to the FileSecurity object.
Apply the permissions by using the File class.	Create the file by using a new FileStream object by passing the FileSecurity object as a parameter to the FileStream constructor.
	Place fourth, if any, here
Create a new FileSystemAuditRule object and add it to the FileSecurity object.	Place fifth, if any, here

Question: 80

You work as a developer at Company.com. You are developing an application to create a new file on the local file system. You need to define specific security settings for the file. You must deny the file inheritance of any default security settings. What should you do?

Actions, select from these	Actions, place here
Create the file by using a new FileStream object by passing the FileSecurity object as a parameter to the FileStream constructor.	Place first, if any, here
Create a new FileSecurity object.	Place second, if any, here
Apply the permissions by using the File class.	Place third, if any, here
Create a new FileSystemAccessRule object for each permission that you need, and add each rule to the FileSecurity object.	Place fourth, if any, here
Create a new FileSystemAuditRule object and add it to the FileSecurity object.	Place fifth, if any, here

Answer:

Question: 81

You are creating a strong-named assembly named Company1 that will be used in multiple

applications. Company1 will be rebuilt frequently during the development cycle. You need to ensure that each time the assembly is rebuilt it works correctly with each application that uses it. You need to configure the computer on which you develop Company1 such that each application uses the latest build of Company1. Which two actions should you perform? (Each correct answer presents part of the solution. Choose two.)

- A. Create a DEVPATH environment variable that points to the build output directory for the strong-named assembly.
- B. Add the following XML element to the machine configuration file:
<developmentMode developerInstallation="true"/>
- C. Add the following XML element to the machine configuration file:
<dependentAssembly>
<assemblyIdentity name="Company1"
publicKeyToken="32ab4ba45e0a69a1"
language="en-US" version="*. *. *. *" />
<publisherPolicy apply="no" />
</dependentAssembly>
- D. Add the following XML element to the configuration file of each application that uses the strong-named assembly:
<supportedRuntime version="*. *. *. *" />
- E. Add the following XML element to the configuration file of each application that uses the strong-named assembly:
<dependentAssembly>
<assemblyIdentity name="Company1"
publicKeyToken="32ab4ba45e0a69a1"language="en-US" version="*. *. *. *" />
<bindingRedirect newVersion="*. *. *. *" />
</dependentAssembly>

Answer: A, B

Question: 82

You work as a developer at Company.com. You create a service application that monitors free space on a hard disk drive. You must ensure that the service application runs in the background and monitors the free space every minute. What should you do?

Actions, select from these	Actions, place here
Add code to the default constructor of the Service class to monitor the free space on the hard disk drive.	Place first, if any, here
Add code to the OnStart method of the Service class to monitor the free space on the hard disk drive.	Place second, if any, here
Add an instance of the System.Windows.Forms.Timer class to the Service class and configure it to fire every minute.	Place third, if any, here
Add an instance of the System.Timers.Timer class to the Service class and configure it to fire every minute.	Place fourth, if any, here
Add code to the OnStart method of the Service class to start the timer.	Place fifth, if any, here
Add code to the Elapsed event handler of the timer to monitor the free space on the hard disk drive.	Place sixth, if any, here
Add code to the Tick event handler of the timer to monitor the free space on the hard disk drive.	Place 7th, if any, here

Answer:

Actions, select from these	Actions, place here
Add code to the default constructor of the Service class to monitor the free space on the hard disk drive.	Add an instance of <code>System.Timers.Timer</code> class to the Service class and configure it to fire every minute.
Add code to the <code>OnStart</code> method of the Service class to monitor the free space on the hard disk drive.	Add code to the <code>OnStart</code> method of the Service class to start the timer.
Add an instance of <code>System.Windows.Forms.Timer</code> class to the Service class and configure it to fire every minute.	Add code to the <code>Elapsed</code> event handler of the timer to monitor the free space on the hard disk drive.
	Place fourth, if any, here
	Place fifth, if any, here
	Place sixth, if any, here
Add code to the <code>Tick</code> event handler of the timer to monitor the free space on the hard disk drive.	Place seventh, if any, here

Question: 83

You are creating a class that performs complex financial calculations. The class contains a method named `GetCurrentRate` that retrieves the current interest rate and a variable named `currRate` that stores the current interest rate. You write serialized representations of the class. You need to write a code segment that updates the `currRate` variable with the current interest rate when an instance of the class is deserialized. Which code segment should you use?

- A. `[OnSerializing]internal void UpdateValue (StreamingContext context) { currRate = GetCurrentRate();}`
- B. `[OnSerializing]internal void UpdateValue(SerializationInfo info) { info.AddValue("currentRate", GetCurrentRate());}`
- C. `[OnDeserializing]internal void UpdateValue(SerializationInfo info) { info.AddValue("currentRate", GetCurrentRate());}`
- D. `[OnDeserialized]internal void UpdateValue(StreamingContext context) { currRate = GetCurrentRate();}`

Answer: D

Question: 84

You need to write a multicast delegate that accepts a `DateTime` argument. Which code segment should you use?

- A. `Public Delegate Function PowerDeviceOn( _ ByVal result As Boolean, _ ByVal autoPowerOff As DateTime) _ As Integer`
- B. `Public Delegate Function PowerDeviceOn( _ ByVal sender As Object, _ ByVal autoPowerOff As EventArgs) _ As Boolean`
- C. `Public Delegate Sub PowerDeviceOn( _ ByVal autoPowerOff As DateTime)`
- D. `Public Delegate Function PowerDeviceOn( _ ByVal autoPowerOff As DateTime) _ As Boolean`

Answer: C

Question: 85

You create a class library that is used by applications in three departments of your company. The library contains a `Department` class with the following definition. `public ref class Department { public : String^ name;`

String^ manager;}; Each application uses a custom configuration section to store department-specific values in the application configuration file as shown in the following code.

```
<Department>
<name>Hardware</name>
<manager>Company</manager>
</Department>
```

You need to write a code segment that creates a Department object instance by using the field values retrieved from the application configuration file. Which code segment should you use?

- A.** public ref class deptElement : public ConfigurationElement {
protected :
override void DeserializeElement(XmlReader^ reader,
bool^ serializeCollectionKey) {
Department^ dept = gcnew Department();
dept->name = ConfigurationManager::AppSettings["name"];
dept->manager = ConfigurationManager::AppSettings["manager"];
return dept;
}};
- B.** public ref class deptElement : public ConfigurationElement {
protected :
override void DeserializeElement(XmlReader^ reader,
bool^ serializeCollectionKey) {
Department^ dept = gcnew Department();
dept->name = reader->GetAttribute("name");
dept->manager = reader->GetAttribute("manager");
}};
- C.** public ref class deptHandler :
public IConfigurationSectionHandler {
public :
Object^ Create(Object^ parent, Object^ configContext,
System.Xml.XmlNode section) {
Department^ dept = gcnew Department();
dept->name = section->SelectSingleNode("name")->InnerText;
dept->manager = section->SelectSingleNode("manager")->InnerText;
return dept;
}};
- D.** public ref class deptHandler : public IConfigurationSectionHandler {
public :
Object^ Create(Object^ parent, Object^ configContext,
System.Xml.XmlNode^ section) {
Department^ dept = gcnew Department();
dept->name = section->Attributes["name"].Value;
dept->manager = section->Attributes["manager"].Value;
return dept;
}};

Answer: C

Question: 86

You are developing a custom-collection class.

You need to create a method in your class. You need to ensure that the method you create in your class returns a type that is compatible with the Foreach statement. Which criterion should the method meet?

- A.** The method must return a type of either IEnumerator or IEnumerable.

- B. The method must return a type of IComparable.
- C. The method must explicitly contain a collection.
- D. The method must be the only iterator in the class.

Answer: A

Question: 87

You write the following code to call a function from the Win32 Application Programming Interface (API) by using platform invoke.

```
Dim r As Integer = MessageBox(hWnd, strText, strCaption, strType)
```

You need to define a method prototype. Which code segment should you use?

- A. <DllImport("user32")> _Function MessageBox(_
ByVal hWnd As IntPtr, ByVal text As String, _
ByVal Caption As String, ByVal t As UInt32) As IntegerEnd Function**
- B. <DllImport("user32")> _Function MessageBoxA(_
ByVal hWnd As IntPtr, ByVal text As String, _
ByVal Caption As String, ByVal t As UInt32) As IntegerEnd Function**
- C. <DllImport("user32")> _Function Win32API_User32_MessageBox (_
ByVal hWnd As IntPtr, ByVal text As String, _
ByVal Caption As String, ByVal t As UInt32) As IntegerEnd Function**
- D. <DllImport("C:\WINDOWS\system32\user32.dll ")> _Function MessageBox(_
ByVal hWnd As IntPtr, ByVal text As String, _
ByVal Caption As String, ByVal t As UInt32) As IntegerEnd Function**

Answer: A

Question: 88

You are writing an application that uses isolated storage to store user preferences. The application uses multiple assemblies. Multiple users will use this application on the same computer. You need to create a directory named Preferences in the isolated storage area that is scoped to the current Microsoft Windows identity and assembly.

Which code segment should you use?

- A. IsolatedStorageFile^ store;store = IsolatedStorageFile::GetUserStoreForAssembly();store->CreateDirectory("Preferences");**
- B. IsolatedStorageFile^ store;store = IsolatedStorageFile::GetMachineStoreForAssembly();store->CreateDirectory("Preferences");**
- C. IsolatedStorageFile^ store;store = IsolatedStorageFile::GetUserStoreForDomain();store->CreateDirectory("Preferences");**
- D. IsolatedStorageFile^ store;store = IsolatedStorageFile::GetMachineStoreForApplication();store->CreateDirectory("Preferences");**

Answer: A

Question: 89

You are writing an application that uses isolated storage to store user preferences. The application uses multiple assemblies. Multiple users will use this application on the same computer. You need to create a directory named Preferences in the isolated storage area that is scoped to the current Microsoft Windows identity and assembly.

Which code segment should you use?

- A. IsolatedStorageFile store;store = IsolatedStorageFile.GetUserStoreForAssembly();store.CreateDirectory("Preferences");**
- B. IsolatedStorageFile store;store =**

```
IsolatedStorageFile.GetMachineStoreForAssembly();store.CreateDirectory("Preferences");  
C. IsolatedStorageFile store;store =  
IsolatedStorageFile.GetUserStoreForDomain();store.CreateDirectory("Preferences");  
D. IsolatedStorageFile store;store =  
IsolatedStorageFile.GetMachineStoreForApplication();store.CreateDirectory("Preferences");
```

Answer: A

Question: 90

You are developing a method to call a COM component. You need to use declarative security to explicitly request the runtime to perform a full stack walk. You must ensure that all callers have the required level of trust for COM interop before the callers execute your method. Which attribute should you place on the method?

- A. [SecurityPermission(
SecurityAction::Demand,
Flags=SecurityPermissionFlag::UnmanagedCode)]
- B. [SecurityPermission(
SecurityAction::LinkDemand,
C. [SecurityPermission(
SecurityAction::Assert,
Flags = SecurityPermissionFlag::UnmanagedCode)]
- D. [SecurityPermission(
SecurityAction::Deny,
Flags = SecurityPermissionFlag::UnmanagedCode)]

Answer: A

Question: 91

You are using the Microsoft Visual Studio 2005 IDE to examine the output of a method that returns a string. You assign the output of the method to a string variable named fName. You need to write a code segment that prints the following on a single line The message: "Test Failed: " The value of fName if the value of fName does not equal "Company" You also need to ensure that the code segment simultaneously facilitates uninterrupted execution of the application. Which code segment should you use?

- A. Debug::Assert(fName == "Company", "Test Failed: ", fName);
- B. Debug::WriteLine(fName != "Company", fName, "Test Failed");
- C. if (fName != "Company") {
Debug::Print("Test Failed: ");
Debug::Print(fName);}
- D. if (fName != "Company") {
Debug::WriteLine("Test Failed: ");
Debug::WriteLine(fName);}

Answer: B

Question: 92

Your company uses an application named Application1 that was compiled by using the .NET Framework version 1.0. The application currently runs on a shared computer on which the .NET Framework versions 1.0 and 1.1 are installed. You need to move the application to a new computer on which the .NET Framework versions 1.1 and 2.0 are installed. The application is compatible with the .NET Framework 1.1, but it is incompatible with the .NET Framework 2.0. You need to ensure that the application will use the .NET Framework version 1.1 on the new computer. What should you do?

A. Add the following XML element to the application configuration file.

```
<configuration>
<startup>
<supportedRuntime version="1.1.4322" />
<startup>
</configuration>
```

B. Add the following XML element to the application configuration file.

```
<configuration>
<runtime>
<assemblyBinding
xmlns="urn:schemas-microsoft-com:asm.v1">
<dependentAssembly>
<assemblyIdentity name="Application1"
publicKeyToken="32ab4ba45e0a69a1"
culture="neutral" />
<bindingRedirect oldVersion="1.0.3075.0"
newVersion="1.1.4322.0"/>
</dependentAssembly>
</assemblyBinding>
</runtime>
</configuration>
```

C. Add the following XML element to the machine configuration file.

```
<configuration>
<startup>
<requiredRuntime version="1.1.4322" />
<startup>
</configuration>
```

D. Add the following XML element to the machine configuration file.

```
<configuration>
<runtime>
<assemblyBinding
xmlns="urn:schemas-microsoft-com:asm.v1">
<dependentAssembly>
<assemblyIdentity name="Application1"
publicKeyToken="32ab4ba45e0a69a1"
culture="neutral" />
<bindingRedirect oldVersion="1.0.3075.0"
newVersion="1.1.4322.0"/>
</dependentAssembly>
</assemblyBinding>
</runtime>
</configuration>
```

Answer: A

Question: 93

You are developing a method that searches a string for a substring. The method will be localized to Italy.

Your method accepts the following parameters: The string to be searched, which is named searchListThe string for which to search, which is named searchValue You need to write the code. Which code segment should you use?

A. return searchList->IndexOf(searchValue);

B. CompareInfo^ comparer =

gcnew CultureInfo("it-IT")::CompareInfo; return comparer->Compare(searchList, search Value);

C. CultureInfo^ comarer = gcnew CultureInfo("it-IT");if

```
(searchList->IndexOf(searchValue)
> 0) {
return true;} else {
return false;}
D. CompareInfo^ comparer =
gcnew CultureInfo("it-IT")::CompareInfo; if (comparer->IndexOf(searchList,
searchValue) > 0) {
return true;} else {
return false;}

```

Answer: D

Question: 94

You need to write a code segment that will create a common language runtime (CLR) unit of isolation within an application. Which code segment should you use?

```
A. AppDomainSetup^ mySetup =
AppDomain::CurrentDomain::SetupInformation;mySetup->ShadowCopyFiles = "true";
B. System::Diagnostics::Process^ myProcess;myProcess = gcnew
System::Diagnostics::Process();
C. AppDomain^ domain; domain = AppDomain::CreateDomain("CompanyDomain");
D. System::ComponentModel::Component^ myComponent;myComponent = gcnew
System::ComponentModel::Component();

```

Answer: C

Question: 95

You are loading a new assembly into an application. You need to override the default evidence for the assembly. You require the common language runtime (CLR) to grant the assembly a permission set, as if the assembly were loaded from the local intranet zone. You need to build the evidence collection. Which code segment should you use?

```
A. Evidence evidence = new Evidence(
Assembly.GetExecutingAssembly().Evidence
);
B. Evidence evidence = new Evidence();evidence.AddAssembly(new
Zone(SecurityZone.Intranet));
C. Evidence evidence = new Evidence();evidence.AddHost(new Zone(SecurityZone.Intranet));
D. Evidence evidence = new Evidence(
AppDomain.CurrentDomain.Evidence
);

```

Answer: C

Question: 96

You are developing a class library that will open the network socket connections to computers on the network. You will deploy the class library to the global assembly cache and grant it full trust. You write the following code to ensure usage of the socket connections.

```
SocketPermission permission = new
SocketPermission(PermissionState.Unrestricted);permission.Assert();
```

Some of the applications that use the class library might not have the necessary permissions to open the network socket connections.

You need to cancel the assertion.

Which code segment should you use?

```
A. CodeAccessPermission.RevertAssert();
```

- B. `CodeAccessPermission.RevertDeny();`
- C. `permission.Deny();`
- D. `permission.PermitOnly();`

Answer: A

Question: 97

You are changing the security settings of a file named `MyData.xml`.

You need to preserve the existing inherited access rules. You also need to prevent the access rules from inheriting changes in the future.

Which code segment should you use?

- A. `Dim objSecurity As New FileSecurity(_
"MyData.xml", AccessControlSections.All)objSecurity.SetAccessRuleProtection(True,
True)File.SetAccessControl("MyData.xml", objSecurity)`
- B. `Dim objSecurity As New FileSecurity()objSecurity.SetAccessRuleProtection(True,
True)File.SetAccessControl("MyData.xml", objSecurity)`
- C. `Dim objSecurity As FileSecurity =
_File.GetAccessControl("MyData.xml")objSecurity.SetAccessRuleProtection(True,
True)`
- D. `Dim objSecurity As FileSecurity =
_File.GetAccessControl("MyData.xml")objSecurity.SetAuditRuleProtection(True,
True)File.SetAccessControl("myData.xml", objSecurity)`

Answer: A

Question: 98

You develop a service application named `FileService`. You deploy the service application to multiple servers on your network. You implement the following code segment. (Line numbers are included for reference only.)

```
01 public void StartService(string serverName){
02     ServiceController ctrl = new
03     ServiceController("FileService");
04     if (ctrl.Status == ServiceControllerStatus.Stopped){
05     }
06 }
```

You need to develop a routine that will start `FileService` if it stops. The routine must start `FileService` on the server identified by the `serverName` input parameter.

Which two lines of code should you add to the code segment? (Each correct answer presents part of the solution. Choose two.)

- A. Insert the following line of code between lines 03 and 04: `ctrl.ServiceName = serverName;`
- B. Insert the following line of code between lines 03 and 04: `ctrl.MachineName = serverName;`
- C. Insert the following line of code between lines 03 and 04: `ctrl.Site.Name = serverName;`
- D. Insert the following line of code between lines 04 and 05: `ctrl.Continue();`
- E. Insert the following line of code between lines 04 and 05: `ctrl.Start();`
- F. Insert the following line of code between lines 04 and 05: `ctrl.ExecuteCommand(0);`

Answer: B,E

Question: 99

You are using the Microsoft Visual Studio 2005 IDE to examine the output of a method that returns a string. You assign the output of the method to a string variable named `fName`. You need to write a code segment that prints the following on a single line The message: "Test Failed: " The value of `fName` if the value of `fName` does not equal "Company" You also need to ensure that the code segment simultaneously facilitates uninterrupted execution of the application. Which code

segment should you use?

- A. Debug.Assert(fName = "Company", "Test Failed: ", fName)
- B. Debug.WriteLineIf(fName <> "Company", _ fName, "Test Failed")
- C. If fName <> "Company" Then
Debug.Print("Test Failed: ")
Debug.Print(fName)End If
- D. If fName <> "Company" Then
Debug.WriteLine("Test Failed: ")
Debug.WriteLine(fName)End If

Answer: B

Question: 100

You are writing code for user authentication and authorization. The username, password, and roles are stored in your application data store.

You need to establish a user security context that will be used for authorization checks such as IsInRole. You write the following code segment to authorize the user.

**if (!TestPassword(userName, password))
throw new Exception("could not authenticate user");String[] userRolesArray =
LookupUserRoles(userName); You need to complete this code so that it establishes the user
security context. Which code segment should you use?**

- A. GenericIdentity ident = new GenericIdentity(userName);GenericPrincipal currentUser =
New GenericPrincipal(ident, userRolesArray);Thread.CurrentPrincipal = currentUser;
- B. WindowsIdentity ident = new WindowsIdentity(userName);WindowsPrincipal currentUser =
new WindowsPrincipal(ident);Thread.CurrentPrincipal = currentUser;
- C. NTAccount userNTName = new NTAccount(userName);GenericIdentity ident = new
GenericIdentity(userNTName.Value);GenericPrincipal currentUser = new
GenericPrincipal(ident, userRolesArray);Thread.CurrentPrincipal = currentUser;
- D. IntPtr token = IntPtr.Zero;token = LogonUserUsingInterop(username,
encryptedPassword);WindowsImpersonationContext ctx =
WindowsIdentity.Impersonate(token);

Answer: A

Question: 101

You create an application that stores information about your customers who reside in various regions. You are developing internal utilities for this application.

You need to gather regional information about your customers in Canada.

Which code segment should you use?

- A. For Each objCulture As CultureInfo In
_CultureInfo.GetCultures(CultureTypes.SpecificCultures)
...Next
- B. Dim objCulture As New CultureInfo("CA")
...
- C. Dim objRegion As New RegionInfo("CA")
...
- D. Dim objRegion As New RegionInfo("")If objRegion.Name = "CA" Then
...End If

Answer: C

Question: 102

You create an application to send a message by e-mail. An SMTP server is available on the local

subnet. The SMTP server is named smtp.Company.com.
 To test the application, you use a source address, me@Company.com, and a target address, you@Company.com.
 You need to transmit the e-mail message. Which code segment should you use?

- A.** MailAddress addrFrom("me@Company.com", "Me");MailAddress
 addrTo("you@Company.com", "You");MailMessage message(%addrFrom,
 %addrTo);message.Subject = "Greetings!";message.Body = "Test";message.Dispose();
- B.** String^strSmtpClient = "smtp.Company.com";String^ strFrom = "me@Company.com";String^
 strTo = "you@Company.com";String^ strSubject = "Greetings!";String^ strBody =
 "Test";MailMessage msg(strFrom, strTo, strSubject, strSmtpClient);
- C.** MailAddress addrFrom("me@Company.com");MailAddress
 addrTo("you@Company.com");MailMessage message(%addrFrom,
 %addrTo);message.Subject = "Greetings!";message.body = "Test";SmtpClient
 client("smtp.Company.com");client.Send(%message);
- D.** MailAddress^ addrFrom = gcnew MailAddress("me@Company.com", "Me");MailAddress^
 addrTo = gcnew MailAddress("you@Company.com", "You");MailMessage^ message = gcnew
 MailMessage(addrFrom, addrTo);message->Subject = "Greetings!";message->Body =
 "Test";SocketInformation info;Socket^ client = gcnew
 Socket(info);System::Text::ASCIIEncoding^ enc = gcnew
 System::Text::ASCIIEncoding();array<unsigned char>^ msgBytes = enc-
 >GetBytes(message->ToString());client->Send(msgBytes);

Answer: C

Question: 103

You write the following code segment to call a function from the Win32 Application Programming Interface (API) by using platform invoke.
String^ personName = "N?el";String^ msg = "Welcome " + personName + " to club '!";bool rc = User32API::MessageBox(0, msg, personName, 0); You need to define a method prototype that can best marshal the string data. Which code segment should you use?

- A.** [DllImport("user32", CharSet = CharSet::Ansi)]extern bool MessageBox(int hWnd,
 String^ text,
 String^ caption,
 unsigned int type);}
- B.** [DllImport("user32", EntryPoint = "MessageBoxA", CharSet = CharSet::Ansi)]extern
 bool MessageBox(int hWnd,
 [MarshalAs(UnmanagedType::LPWStr)]String^ text,
 [MarshalAs(UnmanagedType::LPWStr)]String^ caption,
 unsigned int type);}
- C.** [DllImport("user32", CharSet = CharSet::Unicode)]extern bool MessageBox(int
 hWnd,
 String^ text,
 String^ caption,
 unsigned int type);}
- D.** [DllImport("user32", EntryPoint = "MessageBoxA", CharSet =
 CharSet::Unicode)]extern bool MessageBox(int hWnd,
 [MarshalAs(UnmanagedType.LPWStr)]String^ text,
 [MarshalAs(UnmanagedType.LPWStr)]String^ caption,
 unsigned int type);}

Answer: C

Question: 104

You are creating an application that retrieves values from a custom section of the application

configuration file. The custom section uses XML as shown in the following block.

```
<ProjectSection name="ProjectCompany">
<role name="administrator" />
<role name="manager" />
<role name="support" />
</ProjectSection>
```

You need to write a code segment to define a class named Role. You need to ensure that the Role class is initialized with values that are retrieved from the custom section of the configuration file. Which code segment should you use?

A. public ref class Role : public ConfigurationElement {
protected :
static String^ _ElementName = "name";
public :
[ConfigurationProperty("role")]
property String^ Name {
String^ get() {return ((String^)base["role"]);}
}};

B. public ref class Role : public ConfigurationElement {
protected :
static String^ _ElementName = "role";
public :
[ConfigurationProperty("name", IsRequired = true)]
property String^ Name {
String^ get() {return ((String^)base["name"]);}
}};

C. public ref class Role : public ConfigurationElement {
private :
String^ _name;
protected :
static String^ _ElementName = "role";
public :
[ConfigurationProperty("name")]
property String^ Name {
String^ get() {return _name;}
}};

D. public ref class Role : public ConfigurationElement {
private :
String^ _name;
protected :
static String^ _ElementName = "name";
public :
[ConfigurationProperty("role", IsRequired = true)]
property String^ Name {
String^ get() {return _name;}
}};

Answer: B

Question: 105

You create a method that runs by using the credentials of the end user. You need to use Microsoft Windows groups to authorize the user. You must add a code segment that identifies whether a user is in the local group named Clerk. Which code segment should you use?

A. WindowsIdentity currentUser = WindowsIdentity.GetCurrent();foreach

```
(IdentityReference grp in currentUser.Groups) {
NTAccount grpAccount =
((NTAccount)grp.Translate(typeof(NTAccount)));
isAuthorized = grpAccount.Value.Equals(Environment.MachineName + @"\Clerk");
if(isAuthorized) break;}
B. WindowsPrincipal currentUser =
(WindowsPrincipal)Thread.CurrentPrincipal;isAuthorized = currentUser.IsInRole("Clerk");
C. GenericPrincipal currentUser =
(GenericPrincipal) Thread.CurrentPrincipal;isAuthorized = currentUser.IsInRole("Clerk");
D. WindowsPrincipal currentUser =
(WindowsPrincipal)Thread.CurrentPrincipal;isAuthorized =
currentUser.IsInRole(Environment.MachineName);
```

Answer: B

Question: 106

You create an application to send a message by e-mail. An SMTP server is available on the local subnet. The SMTP server is named smtp.Company.com.

To test the application, you use a source address, me@Company.com, and a target address, you@Company.com.

You need to transmit the e-mail message. Which code segment should you use?

```
A. Dim MailFrom As New MailAddress("me@Company.com", "Me")
Dim MailTo As New MailAddress("you@Company.com", "You")
Dim Message As New MailMessage(MailFrom, MailTo)Message.Subject =
"Greetings"Message.Body = "Test"Message.Dispose()
B. Dim SMTPClient As String = "smtp.Company.com"
Dim MailFrom As String = me@Company.com
Dim MailTo As String = you@Company.com
Dim Subject As String = "Greetings"
Dim Body As String = "Test"Dim Message As New MailMessage(MailFrom, MailTo,
Subject, SMTPClient)
C. Dim MailFrom As New MailAddress("me@Company.com", "Me")
Dim MailTo As New MailAddress("you@Company.com", "You")
Dim Message As New MailMessage(MailFrom, MailTo)Message.Subject =
"Greetings"Message.Body = "Test"
Dim objClient As New SmtplibClient("smtp.Company.com")objClient.Send(Message)
D. Dim MailFrom As New MailAddress("me@Company.com", "Me")
Dim MailTo As New MailAddress("you@Company.com", "You")
Dim Message As New MailMessage(MailFrom, MailTo)Message.Subject =
"Greetings"Message.Body = "Test"
Dim Info As New SocketInformationDim Client As New Socket(Info)
Dim Enc As New ASCTEncodingDim Bytes() As Byte =
Enc.GetBytes(Message.ToString)Client.Send(Bytes)
```

Answer: C

Question: 107

You need to write a code segment that performs the following tasks: ?

Retrieves the name of each paused service. ?

Passes the name to the Add method of Collection1. Which code segment should you use?

```
A. ManagementObjectSearcher searcher =
new ManagementObjectSearcher(
"Select * from Win32_Service where State = 'Paused'"); foreach (ManagementObject svc
in searcher.Get()) {
```

```

Collection1.Add(svc["DisplayName"]);}
B. ManagementObjectSearcher searcher =
new ManagementObjectSearcher( "Select * from Win32_Service", "State =
'Paused'");foreach (ManagementObject svc in searcher.Get()) {
Collection1.Add(svc["DisplayName"]);}
C. ManagementObjectSearcher searcher =
new ManagementObjectSearcher(
"Select * from Win32_Service");foreach (ManagementObject svc in searcher.Get()) {
if ((string) svc["State"] == "Paused") {
Collection1.Add(svc["DisplayName"]);
}}
D. ManagementObjectSearcher searcher =
new ManagementObjectSearcher();searcher.Scope = new
ManagementScope("Win32_Service");foreach (ManagementObject svc in
searcher.Get()) {
if ((string)svc["State"] == "Paused") {
Collection1.Add(svc["DisplayName"]);
}}

```

Answer: A

Question: 108

You are developing an application that will perform mathematical calculations.

You need to ensure that the application is able to perform multiple calculations simultaneously.

What should you do?

- A. Set the IdealProcessor property of the ProcessThread object.
- B. Set the ProcessorAffinity property of the ProcessThread object.
- C. For each calculation, call the QueueUserWorkItem method of the ThreadPool class.
- D. Set the Process.GetCurrentProcess().BasePriority property to High.

Answer: C

Question: 109

You need to write a code segment that transfers the first 80 bytes from a stream variable named stream1 into a new byte array named byteArray. You also need to ensure that the code segment assigns the number of bytes that are transferred to an integer variable named bytesTransferred. Which code segment should you use?

- A. bytesTransferred = stream1.Read(byteArray, 0, 80);
- B. for (int i = 0; i < 80; i++) {
stream1.WriteByte(byteArray[i]);
bytesTransferred = i;
if (!stream1.CanWrite) {
break;
}}
- C. while (bytesTransferred < 80) {
stream1.Seek(1, SeekOrigin.Current);
byteArray[bytesTransferred++] =
Convert.ToByte(stream1.ReadByte());}
- D. stream1.Write(byteArray, 0, 80);bytesTransferred = byteArray.Length;

Answer: A

Question: 110

You are testing a component that serializes the Meeting class instances so that they can be

saved to the file system. The Meeting class has the following definition: public ref

```
class Meeting {  
private :  
String^ title;  
public :  
int roomNumber;  
array<String^>^ invitees;  
Meeting(){}  
Meeting(String^ t){  
title = t;  
} };
```

The component contains a procedure with the following code segment.

```
Meeting^ myMeeting = gcnew Meeting("Goals"); myMeeting->roomNumber = 1100;  
array<String^>^ attendees = gcnew array<String^>(2)  
{ "Company", "Mary" }; myMeeting->invitees = attendees;  
XmlSerializer^ xs = gcnew XmlSerializer(__typeof(Meeting));  
StreamWriter^ writer = gcnew StreamWriter("C:\\Meeting.xml");  
xs->Serialize(writer, myMeeting);  
writer->Close();
```

You need to identify the XML block that is written to the C:\\Meeting.xml file as a result of running this procedure. Which XML block represents the content that will be written to the C:\\Meeting.xml file?

A. <?xml version="1.0" encoding="utf-8"?>
<Meeting xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
<title>Goals</title>
<roomNumber>1100</roomNumber>
<invitee>Company</invitee>
<invitee>Mary</invitee>
</Meeting>

B. <?xml version="1.0" encoding="utf-8"?>
<Meeting xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
<roomNumber>1100</roomNumber>
<invitees>
<string>Company</string>
<string>Mary</string>
</invitees>
</Meeting>

C. <?xml version="1.0" encoding="utf-8"?>
<Meeting xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
title="Goals">
<roomNumber>1100</roomNumber>
<invitees>
<string>Company</string>
<string>Mary</string>
</invitees>
</Meeting>

D. <?xml version="1.0" encoding="utf-8"?>
<Meeting xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
<roomNumber>1100</roomNumber>
<invitees>
<string>Company</string>

```

</invitees>
<invitees>
<string>Mary</string>
</invitees>
</Meeting>

```

Answer: B

Question: 111

You are developing a fiscal report for Company.com. Company.com has a main office in the United States and a satellite office in the UK.

You need to ensure that when users in the satellite office generate the report, the current date is displayed in Mexican Spanish format. Which code segment should you use?

- A.** Dim DTFmt As DateTimeFormatInfo = _ New CultureInfo("es-MX", False).DateTimeFormatDim DT As New DateTime(_ DateTime.Today.Year, DateTime.Today.Month, DateTime.Today.Day)Dim strDate As String = _ DT.ToString(DTFmt.LongDatePattern)
- B.** Dim objCalendar As Calendar = _ New CultureInfo("es-MX", False).CalendarDim DT As New DateTime(_ DateTime.Today.Year, DateTime.Today.Month, DateTime.Today.Day)Dim strDate As String = DT.ToString
- C.** Dim strDate As String = _ DateTimeFormatInfo.CurrentInfo.GetMonthName(_ DateTime.Today.Month)
- D.** Dim strDate As String = _ DateTime.Today.Month.ToString("es-MX")

Answer: A

Question: 112

You create an application that stores information about your customers who reside in various regions. You are developing internal utilities for this application.

You need to gather regional information about your customers in Canada. Which code segment should you use?

- A.** foreach (CultureInfo culture in CultureInfo.GetCultures(CultureTypes.SpecificCultures)) { // Output the region information...}
- B.** CultureInfo cultureInfo = new CultureInfo("CA"); // Output the region information...
- C.** RegionInfo regionInfo = new RegionInfo("CA"); // Output the region information...
- D.** RegionInfo regionInfo = new RegionInfo("");if(regionInfo.Name == "CA") { // Output the region information...}

Answer: C

Question: 113

You need to serialize an object of type List<int> in a binary format. The object is named data. Which code segment should you use?

- A.** BinaryFormatter^ formatter = gcnew BinaryFormatter();MemoryStream^ stream = gcnew MemoryStream();formatter->Serialize(stream, data);
- B.** BinaryFromatter^ formatter = gcnew BinaryFormatter();MemoryStream^ stream = gcnew MemoryStream(); for (int i = 0; i < data->Count; i++) { formatter->Serialize(stream, data[i]);}
- C.** BinaryFormatter^ formatter = gcnew BinaryFormatter();array<Byte>^ buffer = gcnew array<Byte>(data->Count);MemoryStream^ stream = gcnew MemoryStream(buffer, true); formatter->Serialize(stream, data);
- D.** BinaryFormatter^ formatter = gcnew BinaryFormatter();MemoryStream^ stream = gcnew MemoryStream();Capture c(formatter, stream);data->ForEach(gcnew Action<int>(%c,

&Capture::Action));

Answer: A

Question: 114

You are developing a server application that will transmit sensitive information on a network. You create an `X509Certificate` object named `certificate` and a `TcpClient` object named `client`. You need to create an `SslStream` to communicate by using the Transport Layer Security 1.0 protocol. Which code segment should you use?

- A. `SslStream ssl = new SslStream(client.GetStream());ssl.AuthenticateAsServer(certificate, false, SslProtocols.None, true);`
- B. `SslStream ssl = new SslStream(client.GetStream());ssl.AuthenticateAsServer(certificate, false, SslProtocols.Ssl3, true);`
- C. `SslStream ssl = new SslStream(client.GetStream());ssl.AuthenticateAsServer(certificate, false, SslProtocols.Ssl2, true);`
- D. `SslStream ssl = new SslStream(client.GetStream()); ssl.AuthenticateAsServer(certificate, false, SslProtocols.Tls, true);`

Answer: D

Question: 115

You are working on a debug build of an application. You need to find the line of code that caused an exception to be thrown. Which property of the Exception class should you use to achieve this goal?

- A. `Data`
- B. `Message`
- C. `StackTrace`
- D. `Source`

Answer: C

Question: 116

You are writing a method that accepts a string parameter named `message`. Your method must break the message parameter into individual lines of text and pass each line to a second method named `Process`. Which code segment should you use?

- A. `StringReader reader = new StringReader(message);Process(reader.ReadToEnd());reader.Close();`
- B. `StringReader reader = new StringReader(message);while (reader.Peek() != -1) { string line = reader.Read().ToString(); Process(line);}reader.Close();`
- C. `StringReader reader = new StringReader(message);Process(reader.ToString());reader.Close();`
- D. `StringReader reader = new StringReader(message);while (reader.Peek() != -1) { Process(reader.ReadLine());}reader.Close();`

Answer: D

Question: 117

You are developing a method to encrypt sensitive data with the Data Encryption Standard (DES) algorithm. Your method accepts the following parameters:
The byte array to be encrypted, which is named `message`
An encryption key, which is named `key`
An initialization vector, which is named `iv`

You need to encrypt the data. You also need to write the encrypted data to a MemoryStream object. Which code segment should you use?

A. DES des = new DESCryptoServiceProvider();
des.BlockSize = message.Length; ICryptoTransform crypto = des.CreateEncryptor(key, iv);
MemoryStream cipherStream = new MemoryStream();
CryptoStream cryptoStream = new CryptoStream(cipherStream, crypto, CryptoStreamMode.Write);
cryptoStream.Write(message, 0, message.Length);

B. DES des = new DESCryptoServiceProvider();
ICryptoTransform crypto = des.CreateDecryptor(key, iv);
MemoryStream cipherStream = new MemoryStream(); CryptoStream cryptoStream = new CryptoStream(cipherStream, crypto, CryptoStreamMode.Write);
cryptoStream.Write(message, 0, message.Length);

C. DES des = new DESCryptoServiceProvider(); ICryptoTransform crypto = des.CreateEncryptor();
MemoryStream cipherStream = new MemoryStream(); CryptoStream cryptoStream = new CryptoStream(cipherStream, crypto, CryptoStreamMode.Write);
cryptoStream.Write(message, 0, message.Length);

D. DES des = new DESCryptoServiceProvider(); ICryptoTransform crypto = des.CreateEncryptor(key, iv);
MemoryStream cipherStream = new MemoryStream(); CryptoStream cryptoStream = new CryptoStream(cipherStream, crypto, CryptoStreamMode.Write); cryptoStream.Write(message, 0, message.Length);

Answer: D

Question: 118

You are creating a new security policy for an application domain. You write the following lines of code.

```
PolicyLevel policy = PolicyLevel.CreateAppDomainLevel();  
PolicyStatement noTrustStatement =  
new PolicyStatement(  
policy.GetNamedPermissionSet("Nothing"));  
PolicyStatement fullTrustStatement =  
new PolicyStatement(  
policy.GetNamedPermissionSet("FullTrust"));
```

You need to arrange code groups for the policy so that loaded assemblies default to the Nothing permission set. If the assembly originates from a trusted zone, the security policy must grant the assembly the FullTrust permission set. Which code segment should you use?

A. CodeGroup group1 = new FirstMatchCodeGroup(
new ZoneMembershipCondition(SecurityZone.Trusted),
fullTrustStatement); CodeGroup group2 = new UnionCodeGroup(
new AllMembershipCondition(),
noTrustStatement); group1.AddChild(group2);

B. CodeGroup group1 = new FirstMatchCodeGroup(
new AllMembershipCondition(),
noTrustStatement); CodeGroup group2 = new UnionCodeGroup(
new ZoneMembershipCondition(SecurityZone.Trusted),
fullTrustStatement); group1.AddChild(group2);

C. CodeGroup group = new UnionCodeGroup(
new ZoneMembershipCondition(SecurityZone.Trusted),

```
fullTrustStatement);  
D. CodeGroup group = new FirstMatchCodeGroup(  
new AllMembershipCondition(),  
noTrustStatement);
```

Answer: B

Question: 119

You develop a service application named **PollingService** that periodically calls long-running procedures. These procedures are called from the **DoWork** method.

You use the following service application code: partial class **PollingService** :

```
ServiceBase {  
    bool blnExit = false; public PollingService() {}  
    protected override void OnStart(string[] args) {  
        do {  
            DoWork();  
        } while (!blnExit);  
    }  
    protected override void OnStop() {  
        blnExit = true;  
    }  
    private void DoWork() {  
        ...  
    }  
}
```

When you attempt to start the service, you receive the following error message: **Could not start the PollingService service on the local computer. Error 1053: The service did not respond to the start or control request in a timely fashion.** You need to modify the service application code so that the service starts properly. What should you do?

- A. Move the loop code into the constructor of the service class from the **OnStart** method.
- B. Drag a timer component onto the design surface of the service. Move the calls to the longrunning procedure from the **OnStart** method into the **Tick** event procedure of the timer, set the **Enabled** property of the timer to **True**, and call the **Start** method of the timer in the **OnStart** method.
- C. Add a class-level **System.Timers.Timer** variable to the service class code. Move the call to the **DoWork** method into the **Elapsed** event procedure of the timer, set the **Enabled** property of the timer to **True**, and call the **Start** method of the timer in the **OnStart** method.
- D. Move the loop code from the **OnStart** method into the **DoWork** method.

Answer: C

Question: 120

You need to write a code segment that transfers the contents of a byte array named **dataToSend** by using a **NetworkStream** object named **netStream**. You need to use a cache of size 8,192 bytes. Which code segment should you use?

- A. `MemoryStream memStream = new MemoryStream(8192);memStream.Write(dataToSend, 0, (int) netStream.Length);`
- B. `MemoryStream memStream = new MemoryStream(8192);netStream.Write(dataToSend, 0, (int) memStream.Length);`
- C. `BufferedStream bufStream = new BufferedStream(netStream, 8192);bufStream.Write(dataToSend, 0, dataToSend.Length);`
- D. `BufferedStream bufStream = new BufferedStream(netStream);bufStream.Write(dataToSend, 0, 8192);`

Answer: C

Question: 121

You need to return the contents of an isolated storage file as a string. The file is machine-scoped and is named **Settings.dat**. Which code segment should you use?

- A.** Dim objStream As IsolatedStorageFileStreamobjStream = New IsolatedStorageFileStream(_
"Settings.dat", FileMode.Open)Dim result As String = New
StreamReader(objStream).ReadToEnd
- B.** Dim objFile As IsolatedStorageFileobjFile =
IsolatedStorageFile.GetMachineStoreForAssemblyDim objStream As
IsolatedStorageFileStreamobjStream = New IsolatedStorageFileStream(_
"Settings.dat", FileMode.Open, objFile)Dim result As String = New
StreamReader(objStream).ReadToEnd
- C.** Dim objStream As IsolatedStorageFileStreamobjStream = New
IsolatedStorageFileStream(_
"Settings.dat", FileMode.Open)Dim result As String objStream.ToString
- D.** Dim objFile As IsolatedStorageFileobjFile =
IsolatedStorageFile.GetMachineStoreForAssemblyDim objStream As
IsolatedStorageFileStreamobjStream = New IsolatedStorageFileStream(_
"Settings.dat", FileMode.Open, objFile)Dim result As String = objStream.ToString

Answer: B

Question: 122

You are developing a utility screen for a new client application. The utility screen displays a thermometer that conveys the current status of processes being carried out by the application. You need to draw a rectangle on the screen to serve as the background of the thermometer as shown in the exhibit. The rectangle must be filled with gradient shading. Which code segment should you choose?

Exhibit:



- A.** Rectangle rectangle = new Rectangle(10, 10, 450, 25); LinearGradientBrush
rectangleBrush =
new LinearGradientBrush(rectangle, Color.AliceBlue,
Color.CornflowerBlue,
LinearGradientMode.ForwardDiagonal); Pen rectanglePen = new Pen(rectangleBrush);
Graphics g = this.CreateGraphics(); g.DrawRectangle(rectanglePen, rectangle);
- B.** Rectangle rectangle = new Rectangle(10, 10, 450, 25); LinearGradientBrush
rectangleBrush =
new LinearGradientBrush(rectangle, Color.AliceBlue,
Color.CornflowerBlue,
LinearGradientMode.ForwardDiagonal); Pen rectanglePen = new Pen(rectangleBrush);
Graphics g = this.CreateGraphics(); g.FillRectangle(rectangleBrush, rectangle);
- C.** RectangleF rectangle = new RectangleF(10f, 10f, 450f, 25f); Point[] points = new
Point[] {new Point(0, 0),
new Point(110, 145)}; LinearGradientBrush rectangelBrush =
new LinearGradientBrush(rectangle, Color.AliceBlue,
Color.CornflowerBlue,
LinearGradientMode.ForwardDiagonal); Pen rectanglePen = new Pen(rectangleBrush);
Graphics g = this.CreateGraphics(); g.DrawPolygon(rectanglePen, points);
- D.** RectangleF rectangle = new RectangleF(10f, 10f, 450f, 25f); SolidBrush
rectangleBrush =
new SolidBrush(Color.AliceBlue); Pen rectanglePen = new Pen(rectangleBrush);

Graphics g = this.CreateGraphics(); g.DrawRectangle(rectangleBrush, rectangle);

Answer: B

Question: 123

You are developing an application to perform mathematical calculations. You develop a class named **CalculationValues**. You write a procedure named **PerformCalculation** that operates on an instance of the class.

You need to ensure that the user interface of the application continues to respond while calculations are being performed. You need to write a code segment that calls the **PerformCalculation** procedure to achieve this goal. Which code segment should you use?

A. public ref class CalculationValues {}; public ref class Calculator {
public :
void PerformCalculation() {} }; public ref class ThreadTest{
private :
void DoWork (){
CalculationValues^ myValues = gnew CalculationValues();
Calculator^ calc = gnew Calculator();
Thread^ newThread = gnew Thread(
gnew ThreadStart(calc, &Calculator::PerformCalculation));
newThread->Start(myValues);
}};

B. public ref class Calculation Values {}; public ref class Calculator {
public :void PerformCalculation() {} }; public ref class ThreadTest{
private :
void DoWork (){
CalculationValues^ myValues = gnew CalculationValues();
Calculator^ calc = gnew Calculator();
ThreadStart^ delStart = gnew
ThreadStart(calc, &Calculator::PerformCalculation);
Thread^ newThread = gnew Thread(delStart);
if (newThread->IsAlive) {
newThread->Start(myValues);
}
}};

C. public ref class Calculation Values {}; public ref class Calculator {
public :
void PerformCalculation(CalculationValues^ values) {} }; public ref class ThreadTest{
private :
void DoWork (){
CalculationValues^ myValues = gnew CalculationValues();
Calculator^ calc = gnew Calculator();
Application::DoEvents();
calc->PerformCalculation(myValues);
Application::DoEvents();
}};

D. public ref class Calculation Values {}; public ref class Calculator {
public :
void PerformCalculation(Object^ values) {} }; public ref class ThreadTest{
private :
void DoWork (){
CalculationValues^ myValues = gnew CalculationValues();
Calculator^ calc = gnew Calculator();
Thread^ newThread = gnew Thread(

```

gcnew ParameterizedThreadStart(calc,
&Calculator::PerformCalculation));
newThread->Start(myValues);
}
};

```

Answer: D

Question: 124

You are developing a method to decrypt data that was encrypted with the Triple DES Algorithm. The method accepts the following parameters: The byte array to be decrypted, which is named cipherMessageThe key, which is named keyAn initialization vector, which is named iv You need to decrypt the message by using the TripleDES class and place the result in a string. Which code segment should you use?

- A.** Dim objDES As New TripleDESCryptoServiceProviderobjDES.BlockSize = cipherMessage.LengthDim objCrypto As ICryptoTransform = _objDES.CreateDecryptor(key, iv)Dim cipherStream As New MemoryStream(cipherMessage)Dim cryptoStream As New CryptoStream(_cipherStream, objCrypto, CryptoStreamMode.Read)Dim message As Stringmessage = New StreamReader(cryptoStream).ReadToEnd
- B.** Dim objDES As New TripleDESCryptoServiceProviderobjDES.FeedbackSize = cipherMessage.LengthDim objCrypto As ICryptoTransform = _objDES.CreateDecryptor(key, iv)Dim cipherStream As New MemoryStream(cipherMessage)Dim cryptoStream As New CryptoStream(_cipherStream, objCrypto, CryptoStreamMode.Read)Dim message As Stringmessage = New StreamReader(cryptoStream).ReadToEnd
- C.** Dim objDES As New TripleDESCryptoServiceProviderDim objCrypto As ICryptoTransform = _objDES.CreateDecryptor()Dim cipherStream As New MemoryStream(cipherMessage)Dim cryptoStream As New CryptoStream(_cipherStream, objCrypto, CryptoStreamMode.Read)Dim message As Stringmessage = New StreamReader(cryptoStream).ReadToEnd
- D.** Dim objDES As New TripleDESCryptoServiceProviderDim objCrypto As ICryptoTransform = _objDES.CreateDecryptor(key, iv)Dim cipherStream As New MemoryStream(cipherMessage)Dim cryptoStream As New CryptoStream(_cipherStream, objCrypto, CryptoStreamMode.Read)Dim message As Stringmessage = New StreamReader(cryptoStream).ReadToEnd

Answer: D

Question: 125

You are developing an application that receives events asynchronously. You create a WqlEventQuery instance to specify the events and event conditions to which the application must respond. You also create a ManagementEventWatcher instance to subscribe to events matching the query. You need to identify the other actions you must perform before the application can receive events asynchronously. Which two actions should you perform? (Each correct answer presents part of the solution. Choose two.)

- A.** Start listening for events by calling the Start method of the ManagementEventWatcher.
- B.** Set up a listener for events by using the EventArrived event of the ManagementEventWatcher.
- C.** Use the WaitForNextEvent method of the ManagementEventWatcher to wait for the events.
- D.** Create an event handler class that has a method that receives an

ObjectReadyEventArgs parameter.

E. Set up a listener for events by using the Stopped event of the ManagementEventWatcher.

Answer: A, B

Question: 126

Your company uses an application named Application1 that was compiled by using the .NET Framework version 1.0. The application currently runs on a shared computer on which the .NET Framework versions 1.0 and 1.1 are installed.

You need to move the application to a new computer on which the .NET Framework versions 1.1 and 2.0 are installed. The application is compatible with the .NET Framework 1.1, but it is incompatible with the .NET Framework 2.0. You need to ensure that the application will use the .NET Framework version 1.1 on the new computer. What should you do?

A. Add the following XML element to the application configuration file.

```
<configuration>
<startup>
<supportedRuntime version="1.1.4322" />
</startup>
</configuration>
```

B. Add the following XML element to the application configuration file.

```
<configuration>
<runtime>
<assemblyBinding
xmlns="urn:schemas-microsoft-com:asm.v1">
<dependentAssembly>
<assemblyIdentity name="Application1"
publicKeyToken="32ab4ba45e0a69a1"
culture="neutral" />
<bindingRedirect oldVersion="1.0.3075.0"
newVersion="1.1.4322.0"/>
</dependentAssembly>
</assemblyBinding>
</runtime>
</configuration>
```

C. Add the following XML element to the machine configuration file.

```
<configuration>
<startup>
<requiredRuntime version="1.1.4322" />
</startup>
</configuration>
```

D. Add the following XML element to the machine configuration file.

```
<configuration>
<runtime>
<assemblyBinding
xmlns="urn:schemas-microsoft-com:asm.v1">
<dependentAssembly>
<assemblyIdentity name="Application1"
publicKeyToken="32ab4ba45e0a69a1"
culture="neutral" />
<bindingRedirect oldVersion="1.0.3075.0"
newVersion="1.1.4322.0"/>
</dependentAssembly>
</assemblyBinding>
</runtime>
```

</configuration>

Answer: A

Question: 127

You are creating a class that performs complex financial calculations. The class contains a method named `GetCurrentRate` that retrieves the current interest rate and a variable named `currRate` that stores the current interest rate.

You write serialized representations of the class.

You need to write a code segment that updates the `currRate` variable with the current interest rate when an instance of the class is deserialized. Which code segment should you use?

A. `<OnSerializing> _Friend Sub UpdateValue (ByVal context As StreamingContext)`

`currRate = GetCurrentRate()End Sub`

B. `<OnSerializing> _ Friend Sub UpdateValue(ByVal info As SerializationInfo)`

`info.AddValue("currentRate", GetCurrentRate())End Sub`

C. `<OnDeserializing> _ Friend Sub UpdateValue(ByVal info As SerializationInfo)`

`info.AddValue("currentRate", GetCurrentRate())End Sub`

D. `<OnDeserialized> _Friend Sub UpdateValue (ByVal context As StreamingContext)`

`currRate = GetCurrentRate()End Sub`

Answer: D

Question: 128

You are writing an application that uses isolated storage to store user preferences. The application uses multiple assemblies. Multiple users will use this application on the same computer. You need to create a directory named `Preferences` in the isolated storage area that is scoped to the current Microsoft Windows identity and assembly.

Which code segment should you use?

A. `Dim objStore As IsolatedStorageFileobjStore =`

`IsolatedStorageFile.GetUserStoreForAssemblyobjStore.CreateDirectory("Preferences")`

B. `Dim objStore As IsolatedStorageFileobjStore =`

`IsolatedStorageFile.GetMachineStoreForAssemblyobjStore.CreateDirectory("Preferences")`

C. `Dim objStore As IsolatedStorageFileobjStore =`

`IsolatedStorageFile.GetUserStoreForDomainobjStore.CreateDirectory("Preferences")`

D. `Dim objStore As IsolatedStorageFileobjStore =`

`IsolatedStorageFile.GetUserStoreForApplicationobjStore.CreateDirectory("Preferences")`

Answer: A

Question: 129

You are developing a method that searches a string for a substring. The method will be localized to Italy.

Your method accepts the following parameters: The string to be searched, which is named `searchList` The string for which to search, which is named `searchValue` You need to write the code. Which code segment should you use?

A `return searchList.IndexOf(searchValue);`

B. `CompareInfo comparer =`

`new CultureInfo("it-IT").CompareInfo; return comparer.Compare(searchList, searchValue);`

C. `CultureInfo Comparer = new CultureInfo("it-IT");if(searchList.IndexOf(searchValue)`

`> 0) {`

`return true;} else {`

`return false;}`

D. `CompareInfo comparer =`

```
new CultureInfo("it-IT").CompareInfo; if (comparer.IndexOf(searchList,
searchValue) > 0) {
return true;} else {
return false;}
```

Answer: D

Question: 130

You are creating a class named Age.

You need to ensure that the Age class is written such that collections of Age objects can be sorted. Which code segment should you use?

A. Public Class Age
Public Value As Integer
Public Function CompareTo(ByVal obj As Object) As Object
If TypeOf obj Is Age Then
Dim _age As Age = CType(obj, Age)
Return Value.CompareTo(obj)
End If
Throw New ArgumentException("object not an Age")
End FunctionEnd Class

B. Public Class Age
Public Value As Integer
Public Function CompareTo(ByVal iValue As Integer) As Object
Try
Return Value.CompareTo(iValue)
Catch
Throw New ArgumentException ("object not an Age")
End Try
End FunctionEnd Class

C. Public Class Age
Implements IComparable
Public Value As Integer
Public Function CompareTo(ByVal obj As Object) As Integer _
Implements IComparable.CompareTo
If TypeOf obj Is Age Then
Dim _age As Age = CType(obj, Age)
Return Value.CompareTo(_age.Value)
End If
Throw New ArgumentException("object not an Age")
End FunctionEnd Class

D. Public Class Age
Implements IComparable
Public Value As Integer
Public Function CompareTo(ByVal obj As Object) As Integer _
Implements IComparable.CompareTo
Try
Return Value.CompareTo((CType(obj, Age)).Value)
Catch
Return -1
End Try
End FunctionEnd Class

Answer: C

Question: 131

You create a method that runs by using the credentials of the end user. You need to use Microsoft Windows groups to authorize the user. You must add a code segment that identifies whether a user is in the local group named Clerk. Which code segment should you use?

A. WindowsIdentity currentUser = WindowsIdentity.GetCurrent();foreach
(IdentityReference grp in currentUser.Groups) {
NTAccount grpAccount =
((NTAccount)grp.Translate(typeof(NTAccount)));
isAuthorized = grpAccount.Value.Equals(Environment.MachineName + @"\Clerk");
if(isAuthorized) break;}
B. WindowsPrincipal currentUser =
(WindowsPrincipal)Thread.CurrentPrincipal;isAuthorized = currentUser.IsInRole("Clerk");
C. GenericPrincipal currentUser =
(GenericPrincipal)Thread.CurrentPrincipal;isAuthorized = currentUser.IsInRole("Clerk");
D. WindowsPrincipal currentUser =
(WindowsPrincipal)Thread.CurrentPrincipal;isAuthorized =
currentUser.IsInRole(Environment.MachineName);

Answer: B

Question: 132

You are testing a component that serializes the Meeting class instances so that they can be saved to the file system. The Meeting class has the following definition:

```
Public Class Meeting  
Private title As String  
Public roomNumber As Integer  
Public invitees As String()  
Public Sub New()End Sub  
Public Sub New(ByVal t As String)  
title = t
```

End Sub End Class The component contains a procedure with the following code segment.

```
Dim myMeeting As New Meeting("Goals") myMeeting.roomNumber = 1100 Dim  
attendees As String() = New String(1) {"Company", "Mary"} myMeeting.invitees =  
attendees  
Dim xs As New XmlSerializer(GetType(Meeting)) Dim writer As New  
StreamWriter("C:\Meeting.xml") xs.Serialize(writer, myMeeting) writer.Close() You need to  
identify the XML block that is written to the C:\Meeting.xml file as a result of running this  
procedure. Which XML block represents the content that will be written to the C:\Meeting.xml file?
```

A. <?xml version="1.0" encoding="utf-8"?>
<Meeting xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
<title>Goals</title>
<roomNumber>1100</roomNumber>
<invitee>Company</invitee>
<invitee>Mary</invitee>
</Meeting>

B. <?xml version="1.0" encoding="utf-8"?>
<Meeting xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
<roomNumber>1100</roomNumber>
<invitees>
<string>Company</string>
<string>Mary</string>
</invitees>
</Meeting>

C. <?xml version="1.0" encoding="utf-8"?>
 <Meeting xmlns:xsd="http://www.w3.org/2001/XMLSchema"
 xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
 title="Goals">
 <roomNumber>1100</roomNumber>
 <invitees>
 <string>Company</string>
 <string>Mary</string>
 </invitees>
 </Meeting>

D. <?xml version="1.0" encoding="utf-8"?>
 <Meeting xmlns:xsd="http://www.w3.org/2001/XMLSchema"
 xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
 <roomNumber>1100</roomNumber>
 <invitees>
 <string>Company</string>
 </invitees>
 <invitees>
 <string>Mary</string>
 </invitees>
 </Meeting>

Answer: B

Question: 133

You are developing a method that searches a string for a substring. The method will be localized to Italy.

Your method accepts the following parameters: The string to be searched, which is named SearchList The string for which to search, which is named SearchValue You need to write the code. Which code segment should you use?

A. Return SearchList.IndexOf(SearchValue)
B. Dim objComparer As CompareInfo = _
 New CultureInfo("it-IT").CompareInfo Return objComparer.Compare(SearchList,
 SearchValue)
C. Dim objComparer As CompareInfo = _
 New CultureInfo("it-IT").CompareInfo If SearchList.IndexOf(SearchValue) > 0 Then
 Return True Else
 Return False End If
D. Dim objComparer As CompareInfo = _
 New CultureInfo("it-IT").CompareInfo If objComparer.IndexOf(SearchList,
 SearchValue) > 0 Then
 Return True Else
 Return False End If

Answer: D

Question: 134

You are developing a method to encrypt sensitive data with the Data Encryption Standard (DES) algorithm. Your method accepts the following parameters:

The byte array to be encrypted, which is named message An encryption key, which is named key An initialization vector, which is named iv You need to encrypt the data. You also need to write the encrypted data to a MemoryStream object.
 Which code segment should you use?

A. Dim objDES As New DESCryptoServiceProvider objDES.BlockSize =

```

message.Length
Dim objCrypto As ICryptoTransform = obj
DES.CreateDecryptor(key, iv)
Dim cipherStream As New MemoryStream
Dim cryptoStream As New CryptoStream(cipherStream, objCrypto,
CryptoStreamMode.Write)
B. Dim objDES As New DESCryptoServiceProvider
Dim objCrypto As ICryptoTransform = objDES.CreateDecryptor(key, iv)Dim
cipherStream As New MemoryStream
Dim cryptoStream As New CryptoStream(cipherStream, objCrypto,
CryptoStreamMode.Write)
cryptoStream.Write(message, 0, message.Length)
C. Dim objDES As New DESCryptoServiceProvider
Dim objCrypto As ICryptoTransform = obj
DES.CreateDecryptor()
Dim cipherStream As New MemoryStream
Dim cryptoStream As New CryptoStream(cipherStream, objCrypto,
CryptoStreamMode.Write)
cryptoStream.Write(message, 0, message.Length)
D. Dim objDES As New DESCryptoServiceProvider
Dim objCrypto As ICryptoTransform = obj
DES.CreateEncryptor(key, iv)
Dim cipherStream As New MemoryStream
Dim cryptoStream As New CryptoStream(cipherStream, objCrypto,
CryptoStreamMode.Write)
cryptoStream.Write(message, 0, message.Length)

```

Answer: D

Question: 135

You are developing an application that receives events asynchronously. You create a WqlEventQuery instance to specify the events and event conditions to which the application must respond. You also create a ManagementEventWatcher instance to subscribe to events matching the query. You need to identify the other actions you must perform before the application can receive events asynchronously. Which two actions should you perform? (Each correct answer presents part of the solution. Choose two.)

- A.** Start listening for events by calling the Start method of the ManagementEventWatcher.
- B.** Set up a listener for events by using the EventArrived event of the ManagementEventWatcher.
- C.** Use the WaitForNextEvent method of the ManagementEventWatcher to wait for the events.
- D.** Create an event handler class that has a method that receives an ObjectReadyEventArgs parameter.
- E.** Set up a listener for events by using the Stopped event of the ManagementEventWatcher.

Answer: A, B

Question: 136

You need to serialize an object of type List<int> in a binary format. The object is named data. Which code segment should you use?

- A.** BinaryFormatter formatter = new BinaryFormatter();MemoryStream stream = new MemoryStream();formatter.Serialize(stream, data);
- B.** BinaryFormatter formatter = new BinaryFormatter();MemoryStream stream = new MemoryStream(); for (int i = 0; i < data.Count, i++) { formatter.Serialize(stream, data[i]);}
- C.** BinaryFormatter formatter = new BinaryFormatter();byte[] buffer = new

```
byte[data.Count];MemoryStream stream = new MemoryStream(buffer, true);
formatter.Serialize(stream, data);
D. BinaryFormatter formatter = new BinaryFormatter();MemoryStream stream = new
MemoryStream();data.ForEach(delegate(int num)
{ formatter.Serialize(stream, data); }
);
```

Answer: A

Question: 137

You are writing a method to compress an array of bytes. The bytes to be compressed are passed to the method in a parameter named document.

You need to compress the contents of the incoming parameter.

Which code segment should you use?

```
A. MemoryStream inStream = new MemoryStream(document);GZipStream zipStream =
new GZipStream(inStream,
CompressionMode.Compress); byte[] result = new
Byte[document.Length];zipStream.Write(result, 0, result.Length); return result;
B. MemoryStream Stream = new MemoryStream(document);GZipStream zipStream =
new GZipStream(stream,
CompressionMode.Compress);zipStream.Write(document, 0,
document.Length);zipStream.Close();return stream.ToArray();
C. MemoryStream outStream = new MemoryStream();GZipStream zipStream = new
GZipStream(outStream,
CompressionMode.Compress);zipStream.Write(document, 0,
document.Length);zipStream.Close();return outStream.ToArray();
D. MemoryStream inStream = new MemoryStream(document);GZipStream zipStream =
new GZipStream(inStream,
CompressionMode.Compress); MemoryStream outStream = new MemoryStream();int b;while
((b = zipStream.ReadByte()) != -1) {
outStream.WriteByte((byte)b);} return outStream.ToArray();
```

Answer: C

Question: 138

You write the following code to implement the CompanyClass.MyMethod function.

Public Class NewClass

Public Function MyMethod(ByVal Arg As Integer) As Integer

Return Arg

End FunctionEnd Class You need to call the CompanyClass.MyMethod function

dynamically from an unrelated class in your assembly. Which code segment should you use?

```
A. Dim objNewClass As New NewClassDim objType As Type =
objNewClass.GetTypeDim objInfo As MethodInfo = _
objType.GetMethod("MyMethod")Dim objParams() As Object = {1}Dim i As Integer =
DirectCast(objInfo.Invoke(Me, objParams), Integer)
B. Dim objNewClass As New NewClassDim objType As Type =
objNewClass.GetTypeDim objInfo As MethodInfo =
objType.GetMethod("MyMethod")Dim objParams() As Object = {1}Dim i As Integer =
DirectCast(objInfo.Invoke(objNewClass, objParams), Integer)
C. Dim objNewClass As New NewClassDim objType As Type =
objNewClass.GetTypeDim objInfo As MethodInfo = _
objType.GetMethod("NewClass.MyMethod")Dim objParams() As Object = {1}Dim i As
```

```
Integer = _
DirectCast(objInfo.Invoke(objNewClass, objParams), Integer)
D. Dim objType As Type = Type.GetType("NewClass")Dim objInfo As MethodInfo =
objType.GetMethod("MyMethod")Dim objParams() As Object = {1}Dim i As Integer =
_DirectCast(objInfo.Invoke(Me, objParams), Integer)
```

Answer: B

Question: 139

You are developing a method to decrypt data that was encrypted with the Triple DES Algorithm. The method accepts the following parameters: The byte array to be decrypted, which is named cipherMessageThe key, which is named keyAn initialization vector, which is named iv You need to decrypt the message by using the TripleDES class and place the result in a string. Which code segment should you use?

A. TripleDES^ des = gcnew TripleDESCryptoServiceProvider();des->BlockSize = cipherMessage->Length;
ICryptoTransform^ crypto = des->CreateDecryptor(key, iv);
MemoryStream^ cipherStream = gcnew MemoryStream(cipherMessage);
CryptoStream ^cryptoStream = gcnew CryptoStream(cipherStream, crypto, CryptoStreamMode::Read);
String^ message;StreamReader^ sReader = gcnew StreamReader(cryptoStream);
message = sReader->ReadToEnd();

B. TripleDES^ des = gcnew TripleDESCryptoServiceProvider();
des->FeedbackSize = cipherMessage->Length;
ICryptoTransform^ crypto = des->CreateDecryptor(key, iv);
MemoryStream^ cipherStream = gcnew MemoryStream(cipherMessage);
CryptoStream^ cryptoStream = gcnew CryptoStream(cipherStream, crypto, CryptoStreamMode::Read);
String^ message;StreamReader^ sReader = gcnew StreamReader(cryptoStream);
message = sReader->ReadToEnd();

C. TripleDES^ des = gcnew TripleDESCryptoServiceProvider();
ICryptoTransform^ crypto = des->CreateDecryptor();
MemoryStream^ cipherStream = gcnew MemoryStream(cipherMessage);
CryptoStream^ cryptoStream = gcnew CryptoStream(cipherStream, crypto, CryptoStreamMode::Read);String^ message;
StreamReader^ sReader = gcnew StreamReader(cryptoStream);
message = sReader->ReadToEnd();

D. TripleDES^ des = gcnew TripleDESCryptoServiceProvider();
ICryptoTransform^ crypto = des->CreateDecryptor(key, iv);
MemoryStream^ cipherStream = gcnew MemoryStream(cipherMessage);
CryptoStream^ cryptoStream = gcnew CryptoStream(cipherStream, crypto, CryptoStreamMode::Read);
String^ message;StreamReader^ sReader = gcnew StreamReader(cryptoStream);
message = sReader->ReadToEnd();

Answer: D

Question: 140

You write the following code to call a function from the Win32 Application Programming Interface (API) by using platform invoke.
int rc = MessageBox(hWnd, text, caption, type); You need to define a methon prototype.
Which code segment should you use?

A. [DllImport("user32")]public static extern int MessageBox(int hWnd, String text,

```
String caption, uint type);
B. [DllImport("user32")]public static extern int MessageBoxA(int hWnd, String text,
String caption, uint type);
C. [DllImport("user32")]public static extern int Win32API_User32_MessageBox(
int hWnd, String text, String caption, uint type);
D. [DllImport(@"C:\WINDOWS\system32\user32.dll")]public static extern int
MessageBox(int hWnd, String text,
String caption, uint type);
```

Answer: A

Question: 141

You need to generate a report that lists language codes and region codes. Which code segment should you use?

```
A. foreach (CultureInfo culture in
CultureInfo.GetCultures(CultureTypes.SpecificCultures)) {
// Output the culture information...}
B. CultureInfo culture = new CultureInfo(""); CultureTypes types = culture.Culture Types;
// Output the culture information...
C. foreach (CultureInfo culture in
CultureInfo.GetCultures(CultureTypes.NeutralCultures)) {
// Output the culture information...}
D. foreach (CultureInfo culture in
CultureInfo.GetCultures(CultureTypes.ReplacementCultures)) {
// Output the culture information...}
```

Answer: A

Question: 142

You are developing a fiscal report for a customer. Your customer has a main office in the United States and a satellite office in Mexico.

You need to ensure that when users in the satellite office generate the report, the current date is displayed in Mexican Spanish format. Which code segment should you use?

```
A. DateTimeFormatInfo dtfi = new CultureInfo("es-MX", false).DateTimeFormat;
DateTime dt = new DateTime(DateTime.Today.Year, DateTime.Today.Month,
DateTime.Today.Day); string dateString = dt.ToString(dtfi.LongDatePattern);
B. Calendar cal = new CultureInfo("es-MX", false).Calendar; DateTime dt = new
DateTime(DateTime.Today.Year, DateTime.Today.Month, DateTime.Today.Day);
Strong DateString = dt.ToString();
C. string dateString = DateTimeFormatInfo.CurrentInfo
GetMonthName(DateTime.Today.Month);
D. string dateString = DateTime.Today.Month.ToString("es-MX");
```

Answer: A

Question: 143

You are creating an application that lists processes on remote computers. The application requires a method that performs the following tasks: Accept the remote computer name as a string parameter named strComputer. Return an ArrayList object that contains the names of all processes that are running on that computer. You need to write a code segment that retrieves the name of each process that is running on the remote computer and adds the name to the ArrayList object. Which code segment should you use?

```
A. ArrayList^ al = gcnew ArrayList();array<Process^> procs =
```

```

Process::GetProcessesByName(StrComputer);for each (Process^ proc in procs) {
al->Add(proc);}
B. ArrayList^ al = gcnew ArrayList();array<Process^> procs =
Process::GetProcesses(StrComputer);for each (Process^ proc in procs) {
al->Add(proc);}
C. ArrayList^ al = gcnew ArrayList();array<Process^> procs =
Process::GetProcessesByName(StrComputer);for each (Process^ proc in procs) {
al->Add(proc->ProcessName);}
D. ArrayList^ al = gcnew ArrayList();array<Process^> procs =
Process::GetProcesses(StrComputer);for each (Process^ proc in procs) {
al->Add(proc->ProcessName);}

```

Answer: D

Question: 144

You develop a service application named FileService. You deploy the service application to multiple servers on your network. You implement the following code segment. (Line numbers are included for reference only.)

```

01 Public Sub StartService(ByVal serverName As String)
02 Dim ctrl As ServiceController = _
03 New ServiceController("FileService")
04 If ctrl.Status = ServiceControllerStatus.Stopped Then
05 End If
06 End Sub

```

You need to develop a routine that will start FileService if it stops. The routine must start FileService on the server identified by the serverName input parameter.

Which two lines of code should you add to the code segment? (Each correct answer presents part of the solution. Choose two.)

- A. Insert the following line of code between lines 03 and 04:ctrl.ServiceName = serverName
- B. Insert the following line of code between lines 03 and 04:ctrl.MachineName = serverName
- C. Insert the following line of code between lines 03 and 04:ctrl.Site.Name = serverName
- D. Insert the following line of code between lines 04 and 05:ctrl.Continue()
- E. Insert the following line of code between lines 04 and 05:ctrl.Start()
- F. Insert the following line of code between lines 04 and 05:ctrl.ExecuteCommand(0)

Answer: B,E

Question: 145

You are creating an application that retrieves values from a custom section of the application configuration file. The custom section uses XML as shown in the following block.

```

<ProjectSection name="ProjectCompany">
<role name="administrator" />
<role name="manager" />
<role name="support" />
</ProjectSection>

```

You need to write a code segment to define a class named Role. You need to ensure that the Role class is initialized with values that are retrieved from the custom section of the configuration file. Which code segment should you use?

- A.

```
public class Role : ConfigurationElement {
internal string _ElementName = "name";
[ConfigurationProperty("role")]
public string Name {
get {
return ((string)base["role"]);
}
```

```

}}}
B. public class Role : ConfigurationElement {
internal string _ElementName = "role";
[ConfigurationProperty("name", RequiredValue = true)]
public string Name {
get {
return ((string)base["name"]);
}}}
C. public class Role : ConfigurationElement {
internal string _ElementName = "role";
private String _name;
[ConfigurationProperty("name")]
public string Name {
get {
return _name;
}}}
D. public class Role : ConfigurationElement {
internal string _ElementName = "name";
private String _name;
[ConfigurationProperty("role", RequiredValue = true)]
public string Name {
get {
return _name;
}}}

```

Answer: B

Question: 146

You need to call an unmanaged function from your managed code by using platform invoke services. What should you do?

- A. Create a class to hold DLL functions and then create prototype methods by using managed code.
- B. Register your assembly by using COM and then reference your managed code from COM.
- C. Export a type library for your managed code.
- D. Import a type library as an assembly and then create instances of COM object.

Answer: A

Question: 147

You are developing an application to perform mathematical calculations. You develop a class named CalculationValues. You write a procedure named PerformCalculation that operates on an instance of the class. You need to ensure that the user interface of the application continues to respond while calculations are being performed. You need to write a code segment that calls the PerformCalculation procedure to achieve this goal.

Which code segment should you use?

- A. Private Sub PerformCalculation()...End Sub Private Sub DoWork()
Dim myValues As New CalculationValues()
Dim newThread As New Thread(_
New ThreadStart(AddressOf PerformCalculation))
newThread.Start(myValues)End Sub
- B. Private Sub PerformCalculation()...End Sub Private Sub DoWork()
Dim myValues As New CalculationValues()
Dim delStart As New ThreadStart(_AddressOf PerformCalculation)
Dim newThread As New Thread(delStart)If newThread.IsAlive

```

Then new Thread.Start(myValues) End If End Sub
C. Private Sub PerformCalculation ( _ByVal values As CalculationValues)...End Sub
Private Sub DoWork()
Dim myValues As New CalculationValues()
Application.DoEvents()
PerformCalculation(myValues)
Application.DoEvents() End Sub
D. Private Sub PerformCalculation ( _ByVal values As Object)...End Sub Private Sub
DoWork()
Dim myValues As New CalculationValues()
Dim newThread As New Thread( _
New ParameterizedThreadStart( _AddressOf PerformCalculation))
newThread.Start(myValues) End Sub

```

Answer: D

Question: 148

You are testing a method that examines a running process. This method returns an ArrayList containing the name and full path of all modules that are loaded by the process. You need to list the modules loaded by a process named C:\TestApps\Process1.exe. Which code segment should you use?

```

A. ArrayList^ ar = gcnew ArrayList();array<Process^> procs;ProcessModuleCollection^
modules;procs = Process::GetProcesses(@"Process1");if(procs->Length > 0) {
modules = procs[0]->Modules;
for each (ProcessModule^ mod in modules) {
ar->Add(mod->ModuleName);
}}
B. ArrayList^ ar = gcnew ArrayList();array<Process^> procs;ProcessModuleCollection^
modules;procs = Process::GetProcesses(@"C:\TestApps\Process1.exe");if
(procs->Length > 0) {
modules = procs[0]->Modules;
for each (ProcessModule^ mod in modules) {
ar->Add(mod->ModuleName);
}}
C. ArrayList^ ar = gcnew ArrayList();array<Process^> procs;ProcessModuleCollection^
modules;procs = Process::GetProcesses(@"Process1");if (procs->Length > 0) {
modules = procs[0]->Modules;
for each (ProcessModule^ mod in modules) {
ar->Add(mod->FileName);
}}
D. ArrayList^ ar = gcnew ArrayList();array<Process^> procs;ProcessModuleCollection^
modules;procs = Process->GetProcessesByName(@"C:\TestApps\Process1.exe");if (procs-
>Length > 0) {
modules = procs[0]->Modules;
for each (ProcessModule^ mod in modules) {
ar->Add(mod->FileName);
}}

```

Answer: C

Question: 149

You are developing a method that searches a string for a substring. The method will be localized to Italy. Your method accepts the following parameters: The string to be searched, which is named SearchListThe string for which to search, which is named SearchValue You need to write the

code. Which code segment should you use?

- A.** Return SearchList.IndexOf(SearchValue)
- B.** Dim objComparer As CompareInfo = _
New CultureInfo("it-IT").CompareInfoReturn objComparer.Compare(SearchList,
SearchValue)
- C.** Dim objComparer As CompareInfo = _
New CultureInfo("it-IT").CompareInfoIf SearchList.IndexOf(SearchValue) > 0 Then
Return TrueElse
Return FalseEnd If
- D.** Dim objComparer As CompareInfo = _
New CultureInfo("it-IT").CompareInfoIf objComparer.IndexOf(SearchList,
SearchValue) > 0 Then
Return TrueElse
Return FalseEnd If

Answer: D

Question: 150

You are testing a newly developed method named PersistToDB. This method accepts a parameter of type EventLogEntry. This method does not return a value. You need to create a code segment that helps you to test the method. The code segment must read entries from the application log of local computers and then pass the entries on to the PersistToDB method. The code block must pass only events of type Error or Warning from the source MySource to the PersistToDB method. Which code segment should you use?

- A.** EventLog^ myLog = gcnew EventLog("Application", ".");for each (EventLogEntry^ entry in myLog->Entries) {
if (entry->Source == "MySource") {
PersistToDB(entry);
}}}
- B.** EventLog^ myLog = gcnew EventLog("Application", ".");myLog->Source = "MySource";for each (EventLogEntry^ entry in myLog->Entries) {
if (entry->EntryType == (EventLogEntryType::Error &
EventLogEntryType::Warning)) {
PersistToDB(entry);}}
- C.** EventLog^ myLog = gcnew EventLog("Application", ".");for each (EventLogEntry^ entry in myLog->Entries) {
if (entry->Source == "MySource") {
if (entry->EntryType == EventLogEntryType::Error ||
entry->EntryType == EventLogEntryType::Warning) {
PersistToDB(entry);
}
}
}}
- D.** EventLog^ myLog = gcnew EventLog("Application", ".");myLog->Source = "MySource";for each (EventLogEntry^ entry in myLog->Entries) {
if (entry->EntryType == EventLogEntryType::Error ||
entry->EntryType == EventLogEntryType::Warning) {
PersistToDB(entry);
}
}}

Answer: C

Question: 151

You are creating an application that lists processes on remote computers. The application requires a method that performs the following tasks: Accept the remote computer name as a

string parameter named strComputer. Return an ArrayList object that contains the names of all processes that are running on that computer. You need to write a code segment that retrieves the name of each process that is running on the remote computer and adds the name to the ArrayList object. Which code segment should you use?

- A.** Dim al As New ArrayList()
Dim procs As Process()
= _
Process.GetProcessesByName(strComputer)
Dim proc As Process
For Each proc In procs
al.Add(proc)
Next
- B.** Dim al As New ArrayList()
Dim procs As Process()
= _
Process.GetProcesses(strComputer)
Dim proc As Process
For Each proc In procs
al.Add(proc)
Next
- C.** Dim al As New ArrayList()
Dim procs As Process()
= _
Process.GetProcessesByName(strComputer)
Dim proc As Process
For Each proc In procs
al.Add(proc.ProcessName)
Next
- D.** Dim al As New ArrayList()
Dim procs As Process()
= _
Process.GetProcesses(strComputer)
Dim proc As Process
For Each proc In procs
al.Add(proc.ProcessName)
Next

Answer: D

Question: 152

You are writing a method that returns an ArrayList named al. You need to ensure that changes to the ArrayList are performed in a thread-safe manner. Which code segment should you use?

- A.** Dim al As ArrayList = New ArrayList()
SyncLock al.SyncRoot
Return al
End SyncLock
- B.** Dim al As ArrayList = New ArrayList()
SyncLock al.SyncRoot
GetType()
Return al
End SyncLock
- C.** Dim al As ArrayList = New ArrayList()
Monitor.Enter(al)
Monitor.Exit(al)
Return al
- D.** Dim al As ArrayList = New ArrayList()
Dim sync_al As ArrayList =
ArrayList.Synchronized(al)
Return sync_al

Answer: D

Question: 153

You create a method that runs by using the credentials of the end user. You need to use Microsoft Windows groups to authorize the user. You must add a code segment that identifies whether a user is in the local group named Clerk. Which code segment should you use?

- A.** Dim objUser As WindowsIdentity = WindowsIdentity.GetCurrent()
For Each objGroup As IdentityReference In objUser.Groups
Dim objNT As NTAccount = _
DirectCast(objGroup.Translate(_
Type.GetType("NTAccount")), NTAccount)
Dim blnAuth As Boolean = objNT.Value.Equals(_
Environment.MachineName & "\Clerk")
If blnAuth Then Exit For
Next
- B.** Dim objUser As WindowsPrincipal = _
DirectCast(Thread.CurrentPrincipal, WindowsPrincipal)
Dim blnAuth As Boolean =
objUser.IsInRole("Clerk")
- C.** Dim objUser As GenericPrincipal = _
DirectCast(Thread.CurrentPrincipal, GenericPrincipal)
Dim blnAuth As Boolean =
objUser.IsInRole("Clerk")
- D.** Dim objUser As WindowsPrincipal = _
DirectCast(Thread.CurrentPrincipal, WindowsPrincipal)
Dim blnAuth As Boolean = _

objUser.IsInRole(Environment.MachineName)

Answer: B

Question: 154

You are creating a class named Age.

You need to ensure that the Age class is written such that collections of Age objects can be sorted. Which code segment should you use?

A. public ref class Age {
public : Int32 Value;
public : virtual Object CompareTo(Object^ obj) {
if (obj->GetType() == Age::GetType()) {
Age^ _age = (Age^) obj;
return Value.CompareTo(obj);
}
throw gcnew ArgumentException("object not an Age");
}};

B. public ref class Age {
public : Int32 Value;
public : virtual Object CompareTo(Int32^ iValue) {
try {
return Value.CompareTo(iValue);
} catch (Exception^ ex) {
throw gcnew ArgumentException("object not an Age");
}
}};

C. public ref class Age : public IComparable {
public : Int32 Value;
public : virtual Int32 CompareTo(Object^ obj) {
if (obj->GetType() == Age::GetType()) {
Age^ _age = (Age^) obj;
return Value.CompareTo(_age->Value);
}
throw gcnew ArgumentException("object not an Age");
}};

D. public ref class Age : public IComparable {
public : Int32 Value;
public : virtual Int32 CompareTo(Object^ obj) {
try {
return Value.CompareTo(((Age^) obj)->Value);
} catch (Exception^ ex) {
return -1;
}
}};

Answer: C

Question: 155

You are developing a server application that will transmit sensitive information on a network. You create an X509Certificate object named certificate and a TcpClient object named client.

You need to create an SslStream to communicate by using the Transport Layer Security 1.0 protocol. Which code segment should you use?

A. Dim objSSL As New
SslStream(client.GetStream)objSSL.AuthenticateAsServer(certificate, False, _

SslProtocols.None, True)
B. Dim objSSL As New
 SslStream(client.GetStream)objSSL.AuthenticateAsServer(certificate, False, _
 SslProtocols.Ssl3, True)
C. Dim objSSL As New
 SslStream(client.GetStream)objSSL.AuthenticateAsServer(certificate, False, _
 SslProtocols.Ssl2, True)
D. Dim objSSL As New
 SslStream(client.GetStream)objSSL.AuthenticateAsServer(certificate, False, _
 SslProtocols.Tls, True)

Answer: D

Question: 156

You are using the Microsoft Visual Studio 2005 IDE to examine the output of a method that returns a string. You assign the output of the method to a string variable named fName. You need to write a code segment that prints the following on a single line The message: "Test Failed: " The value of fName if the value of fName does not equal "Company" You also need to ensure that the code segment simultaneously facilitates uninterrupted execution of the application. Which code segment should you use?

A. Debug.Assert(fName == "Company", "Test Failed: ", fName);
B. Debug.WriteLineIf(fName != "Company", fName, "Test Failed");
C. if (fName != "Company") {
 Debug.Print("Test Failed: ");
 Debug.Print(fName);
 }
D. if (fName != "Company") {
 Debug.WriteLine("Test Failed: ");
 Debug.WriteLine(fName);
 }

Answer: B

Question: 157

You are creating a new security policy for an application domain. You write the following lines of code. PolicyLevel ^policy = PolicyLevel::CreateAppDomainLevel();
 PolicyStatement ^noTrustStatement =
 gcnw PolicyStatement(
 policy->GetNamedPermissionSet("Nothing")); PolicyStatement ^fullTrustStatement =
 gcnw PolicyStatement(
 policy->GetNamedPermissionSet("FullTrust")); You need to arrange code groups for the policy so that loaded assemblies default to the Nothing permission set. If the assembly originates from a trusted zone, the security policy must grant the assembly the FullTrust permission set. Which code segment should you use?

A. CodeGroup ^group1 = gcnw FirstMatchCodeGroup(
 gcnw ZoneMembershipCondition(SecurityZone::Trusted),
 fullTrustStatement); CodeGroup ^group2 = gcnw UnionCodeGroup(
 gcnw AllMembershipCondition(),
 noTrustStatement); group1->AddChild(group2);
B. CodeGroup ^group1 = gcnw FirstMatchCodeGroup(
 gcnw AllMembershipCondition(),
 noTrustStatement); CodeGroup ^group2 = gcnw UnionCodeGroup(
 gcnw ZoneMembershipCondition(SecurityZone::Trusted),
 fullTrustStatement); group1->AddChild(group2);

C. CodeGroup ^group = gcnew UnionCodeGroup(
gcnew ZoneMembershipCondition(SecurityZone::Trusted),
fullTrustStatement);
D. CodeGroup ^group = gcnew FirstMatchCodeGroup(
gcnew AllMembershipCondition(),
noTrustStatement);

Answer: B

Question: 158

You are developing an application that will use custom authentication and role-based security. You need to write a code segment to make the runtime assign an unauthenticated principal object to each running thread. Which code segment should you use?

A. AppDomain domain =
AppDomain.CurrentDomain;domain.SetPrincipalPolicy(PrincipalPolicy.WindowsPrincipal);
B. AppDomain domain = AppDomain.CurrentDomain;domain.SetThreadPrincipal(new
WindowsPrincipal(null));
C. AppDomain domain = AppDomain.CurrentDomain;
domain.SetAppDomainPolicy(
PolicyLevel.CreateAppDomainLevel());
D. AppDomain domain = AppDomain.CurrentDomain;domain.SetPrincipalPolicy(
PrincipalPolicy.UnauthenticatedPrincipal);

Answer: D

Question: 159

You are testing a method that examines a running process. This method returns an ArrayList containing the name and full path of all modules that are loaded by the process. You need to list the modules loaded by a process named C:\TestApps\Process1.exe. Which code segment should you use?

A. Dim ar As New ArrayList()
Dim procs As Process()
Dim modules As
ProcessModuleCollectionprocs = Process.GetProcesses("Process1")If procs.Length > 0
Thenmodules = procs(0).Modules
For Each pm As ProcessModule In Modules
ar.Add(pm.ModuleName)
NextEnd If
B. Dim ar As New ArrayList()
Dim procs As Process()
Dim modules As
ProcessModuleCollectionprocs = Process.GetProcesses("C:\TestApps\Process1.exe")If
procs.Length > 0 Thenmodules = procs(0).Modules
For Each pm As ProcessModule In Modules
ar.Add(pm.ModuleName)
Next End If
C. Dim ar As New ArrayList()
Dim procs As Process()
Dim modules As
ProcessModuleCollectionprocs = Process.GetProcessesByName("Process1")If
procs.Length > 0 Thenmodules = procs(0).Modules
For Each pm As ProcessModule In Modules
ar.Add(pm.FileName)
Next End If
D. Dim ar As New ArrayList()
Dim procs As Process()
Dim modules As
ProcessModuleCollectionprocs =
_Process.GetProcessesByName("C:\TestApps\Process1.exe")If procs.Length > 0
Thenmodules = procs(0).Modules
For Each pm As ProcessModule In Modules

```
ar.Add(pm.FileName)
Next End If
```

Answer: C

Question: 160

You are writing a method that accepts a string parameter named message.

Your method must break the message parameter into individual lines of text and pass each line to a second method named Process.

Which code segment should you use?

- A.** `StringReader^ reader = gcnew
StringReader(message);Process(reader->ReadToEnd());reader->Close();`
- B.** `StringReader^ reader = gcnew StringReader(message);while(reader->Peak() != -1) {
String^ line = reader->Read().ToString();
Process(line);}reader->Close();`
- C.** `StringReader^ reader = gcnew
StringReader(message);Process(reader->ToString());reader->Close();`
- D.** `StringReader^ reader = gcnew StringReader(message);while(reader->Peak() != -1) {
Process(reader->ReadLine());}reader->Close();`

Answer: D

Question: 161

You are using the Microsoft Visual Studio 2005 IDE to examine the output of a method that returns a string. You assign the output of the method to a string variable named fName. You need to write a code segment that prints the following on a single line The message: "Test Failed: " The value of fName if the value of fName does not equal "Company" You also need to ensure that the code segment simultaneously facilitates uninterrupted execution of the application. Which code segment should you use?

- A.** `Debug::Assert(fName == "Company", "Test Failed: ", fName);`
- B.** `Debug::WriteLineIf(fName != "Company", fName, "Test Failed");`
- C.** `if (fName != "Company") {
Debug::Print("Test Failed: ");
Debug::Print(fName);}`
- D.** `if (fName != "Company") {
Debug::WriteLine("Test Failed: ");
Debug::WriteLine(fName);}`

Answer: B

Question: 162

You need to create a dynamic assembly named MyAssembly. You also need to save the assembly to disk. Which code segment should you use?

- A.** `AssemblyName^ myAssemblyName = gcnew
AssemblyName();myAssemblyName->Name = "MyAssembly"; AssemblyBuilder^
myAssemblyBuilder =
AppDomain::CurrentDomain->DefineDynamicAssembly(
myAssemblyName,
AssemblyBuilderAccess::Run);myAssemblyBuilder->Save("MyAssembly.dll");`
- B.** `AssemblyName^ myAssemblyName = gcnew
AssemblyName();myAssemblyName->Name = "MyAssembly"; AssemblyBuilder^
myAssemblyBuilder =
AppDomain::CurrentDomain->DefineDynamicAssembly(
myAssemblyName,
AssemblyBuilderAccess::Run);myAssemblyBuilder->Save("MyAssembly.dll");`

```

myAssemblyName,
AssemblyBuilderAccess::Save);myAssemblyBuilder->Save("MyAssembly.dll");
C. AssemblyName^ myAssemblyName = gcnew AssemblyName();AssemblyBuilder^
myAssemblyBuilder =
AppDomain::CurrentDomain->DefineDynamicAssembly(
myAssemblyName,
AssemblyBuilderAccess::RunAndSave);myAssemblyBuilder->Save("MyAssembly.dll");
D. AssemblyName^ myAssemblyName =
gcnew AssemblyName("MyAssembly"); AssemblyBuilder^ myAssemblyBuilder =
AppDomain::CurrentDomain->DefineDynamicAssembly(
myAssemblyName,
AssemblyBuilderAccess::Save);myAssemblyBuilder->Save("c:\\MyAssembly.dll");

```

Answer: B

Question: 163

You write a class named **Employee** that includes the following code segment. **public class**

```

Employee {
string employeeId, employeeName, jobTitleName;
public string GetName() { return employeeName; }
public string GetTitle() { return jobTitleName; }
}

```

You need to expose this class to COM in a type library. The COM interface must also facilitate forward-compatibility across new versions of the **Employee** class. You need to choose a method for generating the COM interface. What should you do?

- A. Add the following attribute to the class definition.
[ClassInterface(ClassInterfaceType.None)]public class Employee {
- B. Add the following attribute to the class definition.
[ClassInterface(ClassInterfaceType.AutoDual)]public class Employee {
- C. Add the following attribute to the class definition.
[ComVisible(true)]public class Employee {
- D. Define an interface for the class and add the following attribute to the class definition.
[ClassInterface(ClassInterfaceType.None)]public class Employee : IEmployee {

Answer: D

Question: 164

You are developing an application to assist the user in conducting electronic surveys. The survey consists of 25 true-or-false questions. You need to perform the following tasks:

Initialize each answer to true.Minimize the amount of memory used by each survey.

Which storage option should you choose?

- A. BitVector32^ answers = gcnew BitVector32(1);
- B. BitVector32^ answers = gcnew BitVector32(-1);
- C. BitArray^ answers = gcnew BitArray(1);
- D. BitArray^ answers = gcnew BitArray(-1);

Answer: B

Question: 165

You need to write a multicast delegate that accepts a **DateTime** argument and returns a **Boolean** value. Which code segment should you use?

- A. public delegate int PowerDeviceOn(bool, DateTime);

- B.** public delegate bool PowerDeviceOn(Object, EventArgs);
- C.** public delegate void PowerDeviceOn(DateTime);
- D.** public delegate bool PowerDeviceOn(DateTime);

Answer: A

Question: 166

You are developing a server application that will transmit sensitive information on a network. You create an X509Certificate object named certificate and a TcpClient object named client. You need to create an SslStream to communicate by using the Transport Layer Security 1.0 protocol. Which code segment should you use?

- A.** SslStream^ ssl = gcnew SslStream(Client->GetStream());ssl->AuthenticateAsServer(certificate, false, SslProtocols::None, true);
- B.** SslStream ^ssl = gcnew SslStream(Client->GetStream());ssl->AuthenticateAsServer(certificate, false, SslProtocols::SSL3, true);
- C.** SslStream ^ssl = gcnew SslStream(Client->GetStream());ssl->AuthenticateAsServer(certificate, false, SslProtocols::SSL2, true);
- D.** SslStream ^ssl = gcnew SslStream(Client->GetStream());ssl->AuthenticateAsServer(certificate, false, SslProtocols::Tls, true);

Answer: D

Question: 167

You need to select a class that is optimized for key-based item retrieval from both small and large collections. Which class should you choose?

- A.** OrderedDictionary class
- B.** HybridDictionary class
- C.** ListDictionary class
- D.** Hashtable class

Answer: B

Question: 168

You are writing a method that returns an ArrayList named al. You need to ensure that changes to the ArrayList are performed in a thread-safe manner. Which code segment should you use?

- A.** ArrayList^ al = gcnew ArrayList();lock (al->SyncRoot){return al;}
- B.** ArrayList^ al = gcnew ArrayList();lock (al->SyncRoot.GetType()){return al;}
- C.** ArrayList^ al = gcnew ArrayList();Monitor::Enter(al);Monitor::Exit(al);return al;
- D.** ArrayList^ al = gcnew ArrayList();ArrayList^ sync_al = ArrayList::Synchronized(al);return sync_al;

Answer: D

Question: 169

You need to write a code segment that transfers the contents of a byte array named dataToSend by using a NetworkStream object named netStream. You need to use a cache of size 8,192

bytes. Which code segment should you use?

- A.** Dim memStream As New MemoryStream(8192)memStream.Write(dataToSend, 0, _
CType(netStream.Length, Integer))
- B.** Dim memStream As New MemoryStream(8192)netStream.Write(dataToSend, 0, _
CType(memStream.Length, Integer))
- C.** Dim bufStream As New BufferedStream(netStream, 8192)
bufStream.Write(dataToSend, 0, dataToSend.Length)
- D.** Dim bufStream As New BufferedStream(netStream)
bufStream.Write(dataToSend, 0, 8192)

Answer: C

Question: 170

You are creating an undo buffer that stores data modifications. You need to ensure that the undo functionality undoes the most recent data modifications first. You also need to ensure that the undo buffer permits the storage of strings only. Which code segment should you use?

- A.** Dim undoBuffer As New Stack(Of String)
- B.** Dim undoBuffer As New Stack()
- C.** Dim undoBuffer As New Queue(Of String)
- D.** Dim undoBuffer As New Queue()

Answer: A

Question: 171

You are creating an undo buffer that stores data modifications. You need to ensure that the undo functionality undoes the most recent data modifications first. You also need to ensure that the undo buffer permits the storage of strings only. Which code segment should you use?

- A.** Stack<string> undoBuffer = new Stack<string>();
- B.** Stack undoBuffer = new Stack();
- C.** Queue<string> undoBuffer = new Queue<string>();
- D.** Queue undoBuffer = new Queue();

Answer: A

Question: 172

You create the definition for a Vehicle class by using the following code segment.

```
public class Vehicle {  
[XmlAttribute(AttributeName = "category")]  
public string vehicleType;  
public string model;  
[XmlIgnore]  
public int year;  
[XmlElement(ElementName = "mileage")]  
public int miles;  
public ConditionType condition;  
public Vehicle() {  
}  
public enum ConditionType {  
[XmlEnum("Poor")] BelowAverage,  
[XmlEnum("Good")] Average,  
[XmlEnum("Excellent")] AboveAverage  
}  
}}
```

You create an instance of the Vehicle class. You populate the public fields of the Vehicle class

instance as shown in the following table:

MemberValue	vehicleType	car	model	racer	year	2002	miles	15000	condition	AboveAverage
-------------	-------------	-----	-------	-------	------	------	-------	-------	-----------	--------------

You need to identify the XML block that is produced when this Vehicle class instance is serialized.

Which block of XML represents the output of serializing the Vehicle instance?

A. `<?xml version="1.0" encoding="utf-8"?>
<Vehicle
 xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
 xmlns:xsd="http://www.w3.org/2001/XMLSchema"
 vehicleType="car">
 <model>racer</model>
 <miles>15000</miles>
 <condition>AboveAverage</condition>
</Vehicle>`

B. `<?xml version="1.0" encoding="utf-8"?>
<Vehicle
 xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
 xmlns:xsd="http://www.w3.org/2001/XMLSchema"
 category="car">
 <model>racer</model>
 <mileage>15000</mileage>
 <condition>Excellent</condition>
</Vehicle>`

C. `<?xml version="1.0" encoding="utf-8"?>
<Vehicle
 xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
 xmlns:xsd="http://www.w3.org/2001/XMLSchema"
 category="car">
 <model>racer</model>
 <mileage>15000</mileage>
 <conditionType>Excellent</conditionType>
</Vehicle>`

D. `<?xml version="1.0" encoding="utf-8"?>
<Vehicle
 xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
 xmlns:xsd="http://www.w3.org/2001/XMLSchema">
 <category>car</category>
 <model>racer</model>
 <mileage>15000</mileage>
 <condition>Excellent</condition>
</Vehicle>`

Answer: B

Question: 173

You are writing code for user authentication and authorization. The username, password, and roles are stored in your application data store.

You need to establish a user security context that will be used for authorization checks such as `IsInRole`. You write the following code segment to authorize the user.

```
if (!TestPassword(userName, password))  
throw new Exception("could not authenticate user");String[] userRolesArray =  
LookupUserRoles(userName); You need to complete this code so that it establishes the user  
security context. Which code segment should you use?
```

A. `GenericIdentity ident = new GenericIdentity(userName);GenericPrincipal currentUser =`

```

new GenericPrincipal(ident, userRolesArray); Thread.CurrentPrincipal = currentUser;
B. WindowsIdentity ident = new WindowsIdentity(userName); WindowsPrincipal currentUser =
new WindowsPrincipal(ident); Thread.CurrentPrincipal = currentUser;
C. NTAccount userNTName = new NTAccount(userName); GenericIdentity ident = new
GenericIdentity(userNTName.Value); GenericPrincipal currentUser = new
GenericPrincipal(ident, userRolesArray); Thread.CurrentPrincipal = currentUser;
D. IntPtr token = IntPtr.Zero; token = LogonUserUsingInterop(username,
encryptedPassword); WindowsImpersonationContext ctx =
WindowsIdentity.Impersonate(token);

```

Answer: A

Question: 174

You are changing the security settings of a file named MyData.xml. You need to preserve the existing inherited access rules. You also need to prevent the access rules from inheriting changes in the future. Which code segment should you use?

```

A. FileSecurity^ security = gcnw
FileSecurity("mydata.xml", AccessControlSections::All); security->SetAccessRuleProtection(
true, true); File::SetAccessControl("mydata.xml", security);
B. FileSecurity^ security = gcnw
FileSecurity(); security->SetAccessRuleProtection(true,
true); File::SetAccessControl("mydata.xml", security);
C. FileSecurity^ security =
File::GetAccessControl("mydata.xml"); security->SetAccessRuleProtection(true, true);
D. FileSecurity^ security =
File::GetAccessControl("mydata.xml"); security->SetAuditRuleProtection(true,
true); File::SetAccessControl("mydata.xml", security);

```

Answer: A

Question: 175

You are testing a component that serializes the Meeting class instances so that they can be saved to the file system. The Meeting class has the following definition:

```

public class Meeting {
private string title;
public int roomNumber;
public string[] invitees;
public Meeting(){
}
public Meeting(string t){
title = t;
}
}

```

The component contains a procedure with the following code segment.

```

Meeting myMeeting = new Meeting("Goals");
myMeeting.roomNumber = 1100;
string[] attendees = new string[2]{ "Company", "Mary" };
myMeeting.invitees = attendees;
XmlSerializer xs = new XmlSerializer(typeof(Meeting));
StreamWriter writer = new StreamWriter(@"C:\Meeting.xml");
Xs.Serialize(writer, myMeeting);
writer.Close();

```

You need to identify the XML block that is written to the C:\Meeting.xml file as a result of running this procedure. Which XML block represents the content that will be written to the C:\Meeting.xml file?

A. <?xml version="1.0" encoding="utf-8"?>

```
<Meeting xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
<title>Goals</title>
<roomNumber>1100</roomNumber>
<invitee>Company</invitee>
<invitee>Mary</invitee>
</Meeting>
```

B. <?xml version="1.0" encoding="utf-8"?>

```
<Meeting xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
<roomNumber>1100</roomNumber>
<invitees>
<string>Company</string>
<string>Mary</string>
</invitees>
</Meeting>
```

C. <?xml version="1.0" encoding="utf-8"?>

```
<Meeting xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
title="Goals">
<roomNumber>1100</roomNumber>
<invitees>
<string>Company</string>
<string>Mary</string>
</invitees>
</Meeting>
```

D. <?xml version="1.0" encoding="utf-8"?>

```
<Meeting xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
<roomNumber>1100</roomNumber>
<invitees>
<string>Company</string>
</invitees>
<invitees>
<string>Mary</string>
</invitees>
</Meeting>
```

Answer: B

Question: 176

You develop a service application that needs to be deployed. Your network administrator creates a specific user account for your service application. You need to configure your service application to run in the context of this specific user account. What should you do?

- A.** Prior to installation, set the StartType property of the ServiceInstaller class.
- B.** Prior to installation, set the Account, Username, and Password properties of the ServiceProcessInstaller class.
- C.** Use the CONFIG option of the net.exe command-line tool to install the service.
- D.** Use the installutil.exe command-line tool to install the service.

Answer: B

Question: 177

You are changing the security settings of a file named MyData.xml. You need to preserve the existing inherited access rules. You also need to prevent the access

**rules from inheriting changes in the future.
Which code segment should you use?**

- A.** FileSecurity security = new FileSecurity("mydata.xml", AccessControlSections.All);security.SetAccessRuleProtection(true, true);File.SetAccessControl("mydata.xml", security);
- B.** FileSecurity security = new FileSecurity();security.SetAccessRuleProtection(true, true);File.SetAccessControl("mydata.xml", security);
- C.** FileSecurity security = File.GetAccessControl("mydata.xml");security.SetAccessRuleProtection(true, true);
- D.** FileSecurity security = File.GetAccessControl("mydata.xml");security.SetAuditRuleProtection(true, true);File.SetAccessControl("mydata.xml", security);

Answer: A

Question: 178

You write the following code to implement the CompanyClass.MyMethod function.

```
public class CompanyClass {  
    public int MyMethod(int arg) {  
        return arg;  
    }  
}
```

You need to call the CompanyClass.MyMethod function dynamically from an unrelated class in your assembly. Which code segment should you use?

- A.** CompanyClass^ myClass = gcnew CompanyClass();Type^ t = CompanyClass::typeid;MethodInfo^m = t->GetMethod("MyMethod");int i = (int)m->Invoke(this, gcnew array<Object^> {1});
- B.** CompanyClass^ myClass = gcnew CompanyClass();Type^ t = CompanyClass::typeid;MethodInfo^m = t->GetMethod("MyMethod");int i = (int)m->Invoke(myClass, gcnew array<Object^> {1});
- C.** CompanyClass^ myClass = gcnew CompanyClass();Type^ t = CompanyClass::typeid;MethodInfo^m = t->GetMethod("CompanyClass.MyMethod");int i = (int)m->Invoke(myClass, gcnew array<Object^> {1});
- D.** Type^ t =Type::GetType("CompanyClass");MethodInfo^m = t->GetMethod("MyMethod");int i = (int)m->Invoke(this, gcnew array<Object^> {1});

Answer: B

Question: 179

You are creating a class to compare a specially-formatted string. The default collation comparisons do not apply. You need to implement the IComparable<string> interface. Which code segment should you use?

- A.** public class Person : IComparable<string>{
 public int CompareTo(string other){
 }
}
- B.** public class Person : IComparable<string>{
 public int CompareTo(object other){
 }
}
- C.** public class Person : IComparable<string>{
 public bool CompareTo(string other){
 }
}
- D.** public class Person : IComparable<string>{

```
public bool CompareTo(object other){  
    }  
}
```

Answer: A

Question: 180

You are developing an application that will perform mathematical calculations.

You need to ensure that the application is able to perform multiple calculations simultaneously.

What should you do?

- A.** Set the `Idempotent` property of the `ProcessThread` object.
- B.** Set the `ProcessorAffinity` property of the `ProcessThread` object.
- C.** For each calculation, call the `QueueUserWorkItem` method of the `ThreadPool` class.
- D.** Set the `Process.GetCurrentProcess().BasePriority` property to `High`.

Answer: C

Question: 181

You are testing a newly developed method named `PersistToDB`. This method accepts a parameter of type `EventLogEntry`. This method does not return a value. You need to create a code segment that helps you to test the method. The code segment must read entries from the application log of local computers and then pass the entries on to the `PersistToDB` method. The code block must pass only events of type `Error` or `Warning` from the source `MySource` to the `PersistToDB` method. Which code segment should you use?

- A.**

```
EventLog myLog = new EventLog("Application", ".");  
foreach (EventLogEntry entry in myLog.Entries) {  
    if (entry.Source == "MySource") {  
        PersistToDB(entry);  
    }  
}
```
- B.**

```
EventLog myLog = new EventLog("Application", ".");  
myLog.Source = "MySource";  
foreach (EventLogEntry entry in myLog.Entries) {  
    if (entry.EntryType == (EventLogEntryType.Error &  
        EventLogEntryType.Warning)) {  
        PersistToDB(entry);  
    }  
}
```
- C.**

```
EventLog myLog = new EventLog("Application", ".");  
foreach (EventLogEntry entry in myLog.Entries) {  
    if (entry.Source == "MySource") {  
        if (entry.EntryType == EventLogEntryType.Error ||  
            entry.EntryType == EventLogEntryType.Warning) {  
            PersistToDB(entry);  
        }  
    }  
}
```
- D.**

```
EventLog myLog = new EventLog("Application", ".");  
myLog.Source = "MySource";  
foreach (EventLogEntry entry in myLog.Entries) {  
    if (entry.EntryType == EventLogEntryType.Error ||  
        entry.EntryType == EventLogEntryType.Warning) {  
        PersistToDB(entry);  
    }  
}
```

Answer: C

Question: 182

You are developing a method to call a COM component. You need to use declarative security to

explicitly request the runtime to perform a full stack walk. You must ensure that all callers have the required level of trust for COM interop before the callers execute your method. Which attribute should you place on the method?

- A.** [SecurityPermission(SecurityAction.Demand, Flags=SecurityPermissionFlag.UnmanagedCode)]
- B.** [SecurityPermission(SecurityAction.LinkDemand, Flags=SecurityPermissionFlag.UnmanagedCode)]
- C.** [SecurityPermission(SecurityAction.Assert, Flags = SecurityPermissionFlag.UnmanagedCode)]
- D.** [SecurityPermission(SecurityAction.Deny, Flags = SecurityPermissionFlag.UnmanagedCode)]

Answer: A

Question: 183

You are using the Microsoft Visual Studio 2005 IDE to examine the output of a method that returns a string. You assign the output of the method to a string variable named fName. You need to write a code segment that prints the following on a single line The message: "Test Failed: " The value of fName if the value of fName does not equal "Company" You also need to ensure that the code segment simultaneously facilitates uninterrupted execution of the application. Which code segment should you use?

- A.** Debug.Assert(fName = "Company", "Test Failed: ", fName)
- B.** Debug.WriteLineIf(fName <> "Company", _ fName, "Test Failed")
- C.** If fName <> "Company" Then
Debug.Print("Test Failed: ")
Debug.Print(fName)End If
- D.** If fName <> "Company" Then
Debug.WriteLine("Test Failed: ")
Debug.WriteLine(fName)End If

Answer: B

Question: 184

You are loading a new assembly into an application. You need to override the default evidence for the assembly. You require the common language runtime (CLR) to grant the assembly a permission set, as if the assembly were loaded from the local intranet zone. You need to build the evidence collection. Which code segment should you use?

- A.** Dim objEvidence As New Evidence(_
Assembly.GetExecutingAssembly.Evidence
- B.** Dim objEvidence As New EvidenceobjEvidence.AddAssembly(_
New Zone(SecurityZone.Intranet))
- C.** Dim objEvidence As New EvidenceobjEvidence.AddHost(_
New Zone(SecurityZone.Intranet))
- D.** Dim objEvidence As New Evidence(_
AppDomain.CurrentDomain.Evidence)

Answer: C

Question: 185

You need to generate a report that lists language codes and region codes. Which code segment should you use?

- A.** `foreach (CultureInfo culture in
CultureInfo.GetCultures(CultureTypes.SpecificCultures)) {
// Output the culture information...}`
- B.** `CultureInfo culture = new CultureInfo(""); CultureTypes types = culture.CultureTypes;
// Output the culture information...`
- C.** `foreach (CultureInfo culture in
CultureInfo.GetCultures(CultureTypes.NeutralCultures)) {
// Output the culture information...}`
- D.** `foreach (CultureInfo culture in
CultureInfo.GetCultures(CultureTypes.ReplacementCultures)) {
// Output the culture information...}`

Answer: A

Question: 186

You are writing code for user authentication and authorization. The username, password, and roles are stored in your application data store.

You need to establish a user security context that will be used for authorization checks such as `IsInRole`. You write the following code segment to authorize the user.

If `TestPassword(Username, Password) = False` Then

Throw New Exception("Could not authenticate user")End If

Dim RolesArray() As String = LookUpUserRoles(Username)

You need to complete this code so that it establishes the user security context. Which code segment should you use?

- A.** `Dim objID As New GenericIdentity(Username)
Dim objUser As New GenericPrincipal(objID, RolesArray)
Thread.CurrentPrincipal = objUser`
- B.** `Dim objID As New WindowsIdentity(Username)
Dim objUser As New WindowsPrincipal(objID)
Thread.CurrentPrincipal = objUser`
- C.** `Dim objNT As New NTAccount(Username)
Dim objID As New GenericIdentity(objNT.Value)
Dim objUser As New GenericPrincipal(objID, RolesArray)
Thread.CurrentPrincipal = objUser`
- D.** `Dim objToken As IntPtr = IntPtr.Zero
objToken = LogonUserUsingInterop(Username, EncryptedPassword)
Dim objContext As WindowsImpersonationContext =
_WindowsIdentity.Impersonate(objToken)`

Answer: A

Question: 187

You are developing a custom-collection class.

You need to create a method in your class. You need to ensure that the method you create in your class returns a type that is compatible with the `Foreach` statement. Which criterion should the method meet?

- A.** The method must return a type of either `IEnumerator` or `IEnumerable`.
- B.** The method must return a type of `IComparable`.
- C.** The method must explicitly contain a collection.
- D.** The method must be the only iterator in the class.

Answer: A

Question: 188

You need to write a code segment that will create a common language runtime (CLR) unit of isolation within an application. Which code segment should you use?

- A. AppDomainSetup mySetup = AppDomain.CurrentDomain.SetupInformation;mySetup.ShadowCopyFiles = "true";
- B. System.Diagnostics.Process myProcess;myProcess = new System.Diagnostics.Process();
- C. AppDomain domain; domain = AppDomain.CreateDomain("CompanyDomain");
- D. System.ComponentModel.Component myComponent;myComponent = new System.ComponentModel.Component();

Answer: C

Question: 189

You need to create a method to clear a Queue named q. Which code segment should you use?

- A. foreach (object e in q) { q.Dequeue();}
- B. foreach (object e in q) { Enqueue(null);}
- C. q.Clear();
- D. q.Dequeue();

Answer: C

Question: 190

You write the following code segment to call a function from the Win32 Application Programming Interface (API) by using platform invoke.

Dim PersonName as String = "N?el"Dim Msg as String = "Welcome " + PersonName + " to club !!!"Dim r As Boolean= User32API.MessageBox(0, Msg, PersonName, 0) You need to define a method prototype that can best marshal the string data. Which code segment should you use?

- A. <DllImport("user32", CharSet:=CharSet.Ansi)> _Public Function MessageBox(ByVal hWnd As Int32, _ByVal text As String, ByVal caption As String, _ByVal t As UInt32) As BooleanEnd Function
- B. <DllImport("user32", EntryPoint:"MessageBoxA", _CharSet:=CharSet.Ansi)> _Public Function MessageBox(ByVal hWnd As Int32, _<MarshalAs(UnmanagedType.LPWStr)> ByVal text As String, _<MarshalAs(UnmanagedType.LPWStr)> ByVal caption As String, _ByVal t As UInt32) As BooleanEnd Function
- C. <DllImport("user32", CharSet:=CharSet.Unicode)> _Public Function MessageBox(ByVal hWnd As Int32, _ByVal text As String, ByVal caption As String, _ByVal t As UInt32) As BooleanEnd Function
- D. DllImport("user32", EntryPoint:"MessageBoxA", _CharSet:=CharSet.Unicode)> _Public Function MessageBox(ByVal hWnd As Int32, _<MarshalAs(UnmanagedType.LPWStr)> ByVal text As String, _<MarshalAs(UnmanagedType.LPWStr)> ByVal caption As String, _ByVal t As UInt32) As BooleanEnd Function

Answer: C

Question: 191

You are writing a method to compress an array of bytes. The bytes to be compressed are passed to the method in a parameter named document.

You need to compress the contents of the incoming parameter. Which code segment should you use?

- A.** MemoryStream^ inputStream = gcnew MemoryStream(document);GZipStream^ zipStream = gcnew GZipStream(inputStream, CompressionMode::Compress); array<Byte>^ result = gcnew array<Byte>(document->Length);zipStream->Write(result, 0, result->Length); return result;
- B.** MemoryStream^ stream = gcnew MemoryStream(document);GZipStream^ zipStream = gcnew GZipStream(stream, CompressionMode::Compress); zipStream->Write(document, 0, document->Length);zipStream->Close();return stream->ToArray();
- C.** MemoryStream^ outputStream = gcnew MemoryStream();GZipStream^ zipStream = gcnew GZipStream(outputStream, CompressionMode::Compress); zipStream->Write(document, 0, document->Length);zipStream->Close();return outputStream->ToArray();
- D.** MemoryStream^ inputStream = gcnew MemoryStream(document);GZipStream^ zipStream = gcnew GZipStream(inputStream, CompressionMode::Compress); MemoryStream^ outputStream = gcnew MemoryStream();int b; while ((b = zipStream->ReadByte()) != -1) { outputStream->WriteByte((Byte)b);} return outputStream->ToArray();

Answer: C

Question: 192

You are creating a class that uses unmanaged resources. This class maintains references to managed resources on other objects. You need to ensure that users of this class can explicitly release resources when the class instance ceases to be needed. Which three actions should you perform? (Each correct answer presents part of the solution. Choose three.)

- A.** Define the class such that it inherits from the WeakReference class.
- B.** Define the class such that it implements the IDisposable interface.
- C.** Create a class destructor that calls methods on other objects to release the managed resources.
- D.** Create a class destructor that releases the unmanaged resources.
- E.** Create a Dispose method that calls System.GC.Collect to force garbage collection.
- F.** Create a Dispose method that releases unmanaged resources and calls methods on other objects to release the managed resources.

Answer: B, D, F

Question: 193

Your company uses an application named Application1 that was compiled by using the .NET Framework version 1.0. The application currently runs on a shared computer on which the .NET Framework versions 1.0 and 1.1 are installed.

You need to move the application to a new computer on which the .NET Framework versions 1.1 and 2.0 are installed. The application is compatible with the .NET Framework 1.1, but it is incompatible with the .NET Framework 2.0. You need to ensure that the application will use the .NET Framework version 1.1 on the new computer. What should you do?

- A.** Add the following XML element to the application configuration file.
<configuration>
<startup>
<supportedRuntime version="1.1.4322" />
</startup>
</configuration>
- B.** Add the following XML element to the application configuration file.

```

<configuration>
<runtime>
<assemblyBinding
xmlns="urn:schemas-microsoft-com:asm.v1">
<dependentAssembly>
<assemblyIdentity name="Application1"
publicKeyToken="32ab4ba45e0a69a1"
culture="neutral" />
<bindingRedirect oldVersion="1.0.3075.0"
newVersion="1.1.4322.0"/>
</dependentAssembly>
</assemblyBinding>
</runtime>
</configuration>

```

C. Add the following XML element to the machine configuration file.

```

<configuration>
<startup>
<requiredRuntime version="1.1.4322" />
<startup>
</configuration>

```

D. Add the following XML element to the machine configuration file.

```

<configuration>
<runtime>
<assemblyBinding
xmlns="urn:schemas-microsoft-com:asm.v1">
<dependentAssembly>
<assemblyIdentity name="Application1"
publicKeyToken="32ab4ba45e0a69a1"
culture="neutral" />
<bindingRedirect oldVersion="1.0.3075.0"
newVersion="1.1.4322.0"/>
</dependentAssembly>
</assemblyBinding>
</runtime>
</configuration>

```

Answer: A

Question: 194

You create a method that runs by using the credentials of the end user. You need to use Microsoft Windows groups to authorize the user. You must add a code segment that identifies whether a user is in the local group named Clerk. Which code segment should you use?

A. `WindowsIdentity^ currentUser = WindowsIdentity::GetCurrent();` For each `(IdentityReference^ grp in currentUser->Groups)` {
`NTAccount^ grpAccount =`
`safe_cast<NTAccount^>(grp->Translate(NTAccount::typeid));`
`isAuthorized = grpAccount->Value->Equals(`
`Environment::MachineName + "\\Clerk");`
`if(isAuthorized) break;}`

B. `WindowsPrincipal^ currentUser =`
`safe_cast<WindowsPrincipal^>(Thread::CurrentPrincipal);` `isAuthorized = currentUser-`
`>IsInRole("Clerk");`

C. `GenericPrincipal^ currentUser =`
`safe_cast<GenericPrincipal^>(Thread::CurrentPrincipal);` `isAuthorized = currentUser-`

```
>IsInRole("Clerk");
D. WindowsPrincipal^ currentUser =
safe_cast<WindowsPrincipal^>(Thread::CurrentPrincipal);isAuthorized =
currentUser->IsInRole(
Environment::MachineName);
```

Answer: B

Question: 195

You are writing code for user authentication and authorization. The username, password, and roles are stored in your application data store. You need to establish a user security context that will be used for authorization checks such as IsInRole. You write the following code segment to authorize the user.

```
if (!TestPassword(userName, password))
throw new Exception("could not authenticate user");String[] userRolesArray =
LookupUserRoles(userName);
```

You need to complete this code so that it establishes the user security context. Which code segment should you use?

- A. GenericIdentity ident = new GenericIdentity(userName);GenericPrincipal currentUser = new GenericPrincipal(ident, userRolesArray);Thread.CurrentPrincipal = currentUser;
- B. WindowsIdentity ident = new WindowsIdentity(userName);WindowsPrincipal currentUser = new WindowsPrincipal(ident);Thread.CurrentPrincipal = currentUser;
- C. NTAccount userNTName = new NTAccount(userName);GenericIdentity ident = new GenericIdentity(userNTName.Value);GenericPrincipal currentUser = new GenericPrincipal(ident, userRolesArray);Thread.CurrentPrincipal = currentUser;
- D. IntPtr token = IntPtr.Zero;token = LogonUserUsingInterop(username, encryptedPassword);WindowsImpersonationContext ctx = WindowsIdentity.Impersonate(token);

Answer: A

Question: 196

You write a class named Employee that includes the following code segment.

```
public ref
class Employee{
String^ employeeId;
String^ employeeName;
String^ jobTitleName;public:
String^ GetName() { return employeeName; }
String^ GetJobTitle() { return jobTitleName; }
```

You need to expose this class to COM in a type library. The COM interface must also facilitate forward-compatibility across new versions of the Employee class. You need to choose a method for generating the COM interface. What should you do?

- A. Add the following attribute to the class definition.[ClassInterface(ClassInterfaceType::None)]public class Employee {
- B. Add the following attribute to the class definition.[ClassInterface(ClassInterfaceType::AutoDual)]public class Employee {
- C. Add the following attribute to the class definition.[ComVisible(true)]public class Employee {
- D. Define an interface for the class and add the following attribute to the class definition.[ClassInterface(ClassInterfaceType::None)]public class Employee : IEmployee {

Answer: D

Question: 197

You are developing a method to hash data for later verification by using the MD5 algorithm. The data is passed to your method as a byte array named `message`. You need to compute the hash of the incoming parameter by using MD5. You also need to place the result into a byte array. Which code segment should you use?

- A. `HashAlgorithm ^algo = HashAlgorithm::Create("MD5");hash = algo->ComputeHash(message);`
- B. `HashAlgorithm ^algo = HashAlgorithm::Create("MD5");hash = BitConverter::GetBytes(algo->GetHashCode());`
- C. `HashAlgorithm ^algo;algo = HashAlgorithm::Create(message->ToString());hash = algo->Hash;`
- D. `HashAlgorithm ^algo = HashAlgorithm::Create("MD5");hash = nullptr;algo->TransformBlock(message, 0, message->Length, hash, 0);`

Answer: A

Question: 198

You create a class library that contains the class hierarchy defined in the following code segment. (Line numbers are included for reference only.)

01

`Public Class Group` 02

`Public Employees As Employee()` 03

`End Class` 0405

`Public Class Employee` 06

`Public Name As String` 07

`End Class` 0809

`Public Class Manager` 10

`Inherits Employee` 11

`Public Level As Integer` 12 `End Class` You create an instance of the `Group` class. You populate the fields of the instance. When you attempt to serialize the instance by using the `Serialize` method of the `XmlSerializer` class, you receive `InvalidOperationException`.

You also receive the following error message: "There was an error generating the XML document."

You need to modify the code segment so that you can successfully serialize instances of the `Group` class by using the `XmlSerializer` class. You also need to ensure that the XML output contains an element for all public fields in the class hierarchy. What should you do?

- A. Insert the following code between lines 1 and 2 of the code segment:

`<XmlArrayItem(Type:=GetType(Employee))> _`

`<XmlArrayItem(Type:=GetType(Manager))> _`

- B. Insert the following code between lines 1 and 2 of the code segment:

`<XmlElement(Type:=GetType(Employee))> _`

- C. Insert the following code between lines 1 and 2 of the code segment:

`<XmlArray(ElementName:="Employees")> _`

- D. Insert the following code between lines 5 and 6 of the code segment:

`<XmlElement(Type:=GetType(Employee))>`

and insert the following code between lines 10 and 11 of the code segment:

`<XmlElement(Type:=GetType(Manager))>`

Answer: A

Question: 199

You are testing a method that examines a running process. This method returns an `ArrayList` containing the name and full path of all modules that are loaded by the process.

You need to list the modules loaded by a process named `C:\TestApps\Process1.exe`.

Which code segment should you use?

```

A. ArrayList ar = new ArrayList();Process[] procs;ProcessModuleCollection modules;procs =
Process.GetProcesses(@"Process1");if (procs.Length > 0) {modules = porcs[0].Modules;
foreach (ProcessModule mod in modules) {
ar.Add(mod.ModuleName);
}}
B. ArrayList ar = new ArrayList();Process[] procs;ProcessModuleCollection modules;procs =
Process.GetProcesses(@"C:\TestApps\Process1.exe");if (procs.Length > 0) {modules =
porcs[0].Modules;
foreach (ProcessModule mod in modules) {
ar.Add(mod.ModuleName);
}}
C. ArrayList ar = new ArrayList();Process[] procs;ProcessModuleCollection modules;procs =
Process.GetProcessesByName(@"Process1");if (procs.Length > 0) {modules =
porcs[0].Modules;
foreach (ProcessModule mod in modules) {
ar.Add(mod.FileName);
}}
D. ArrayList ar = new ArrayList();Process[] procs;ProcessModuleCollection modules;procs =
Process.GetProcessesByName(@"C:\TestApps\Process1.exe");if
(procs.Length > 0) {
modules = porcs[0].Modules;
foreach (ProcessModule mod in modules) {
ar.Add(mod.FileName);
}}

```

Answer: C

Question: 200

You are developing a method that searches a string for a substring. The method will be localized to Italy.

Your method accepts the following parameters: The string to be searched, which is named searchListThe string for which to search, which is named searchValue You need to write the code. Which code segment should you use?

```

A. return searchLish->IndexOf(searchValue);
B. CompareInfo^ comparer =
gnew CultureInfo("it-IT")::CompareInfo; return comparer->Compare(searchLish, searchValue);
C. CultureInfo^ comparer = gnew CultureInfo("it-IT");if
(searchList->IndexOf(searchValue)
> 0) {
return true;} else {
return false;}
D. CompareInfo^ comparer =
gnew CultureInfo("it-IT")::CompareInfo; if(comparer->IndexOf(searchList,
searchValue) > 0) {
return true;} else {
return false;}

```

Answer: D

Question: 201

You need to create a dynamic assembly named MyAssembly. You also need to save the assembly to disk. Which code segment should you use?

```

A. Dim objAssembly As New AssemblyName()objAssembly.Name =

```

```

"MyAssembly"Dim objBuilder As AssemblyBuilder =
_AppDomain.CurrentDomain.DefineDynamicAssembly( _objAssembly,
AssemblyBuilderAccess.Run)objBuilder.Save("MyAssembly.dll")
B. Dim objAssembly As New AssemblyName(objAssembly.Name =
"MyAssembly"Dim objBuilder As AssemblyBuilder =
_AppDomain.CurrentDomain.DefineDynamicAssembly( _objAssembly,
AssemblyBuilderAccess.Save)objBuilder.Save("MyAssembly.dll")
C. Dim objAssembly As New AssemblyName(objAssembly.Name =
"MyAssembly"Dim objBuilder As AssemblyBuilder =
_AppDomain.CurrentDomain.DefineDynamicAssembly( _objAssembly,
AssemblyBuilderAccess.RunAndSave)objBuilder.Save("MyAssembly.dll")
D. Dim objAssembly As New AssemblyName(objAssembly.Name =
"MyAssembly"Dim objBuilder As AssemblyBuilder =
_AppDomain.CurrentDomain.DefineDynamicAssembly( _objAssembly,
AssemblyBuilderAccess.Save)objBuilder.Save("c:\MyAssembly.dll")

```

Answer: B

Question: 202

You write the following code.

```

Public Delegate Sub FaxDocs(ByVal sender As Object, _
ByVal args as FaxArgs)

```

You need to create an event that will invoke FaxDocs. Which code segment should you use?

```

A. Public Shared Event Fax As FaxDocs
B. Public Shared Event FaxDocs As FaxArgs
C. Public Class FaxArgs
Inherits EventArgs
Private coverPageInfo As String
Public Sub New(ByVal coverInfo As String)
Me.coverPageInfo = coverInfo
End Sub
Public ReadOnly Property CoverPageInformation As String
Get
Return Me.coverPageInfo
End Get
End PropertyEnd Class
D. Public Class FaxArgs
Inherits EventArgs
Private coverPageInfo As String
Public ReadOnly Property CoverPageInformation As String
Get
Return Me.coverPageInfo
End Get
End PropertyEnd Class

```

Answer: A

Question: 203

You are developing a method to encrypt sensitive data with the Data Encryption Standard (DES) algorithm. Your method accepts the following parameters:

The byte array to be encrypted, which is named messageAn encryption key, which is named keyAn initialization vector, which is named iv

You need to encrypt the data. You also need to write the encrypted data to a MemoryStream object.

Which code segment should you use?

A. DES^ des = gcnew DESCryptoServiceProvider();
des->BlockSize = message->Length;
ICryptoTransform^ crypto = des->CreateEncryptor(key, iv);
MemoryStream ^cipherStream = gcnew MemoryStream();
CryptoStream ^cryptoStream = gcnew CryptoStream(cipherStream,crypto,
CryptoStreamMode::Write);
cryptoStream->Write(message, 0, message->Length);

B. DES^ des = gcnew DESCryptoServiceProvider();
ICryptoTransform^ crypto = des->CreateDecryptor(key, iv);
MemoryStream ^cipherStream = gcnew MemoryStream();
CryptoStream ^cryptoStream = gcnew CryptoStream(cipherStream, crypto,
CryptoStreamMode::Write);
cryptoStream->Write(message, 0, message->Length);

C. DES^ des = gcnew DESCryptoServiceProvider();ICryptoTransform^ crypto = des->CreateDecryptor();
MemoryStream ^cipherStream = gcnew MemoryStream();CryptoStream ^cryptoStream
= gcnew CryptoStream(cipherStream,crypto,
CryptoStreamMode::Write);cryptoStream->Write(message, 0, message->Length);

D. DES^ des = gcnew DESCryptoServiceProvider();ICryptoTransform^ crypto = des->CreateEncryptor(key, iv);
MemoryStream ^cipherStream = gcnew MemoryStream();CryptoStream ^cryptoStream
= gcnew CryptoStream(cipherStream, crypto, CryptoStreamMode::Write);
cryptoStream->Write(message, 0, message->Length);

Answer: D

Question: 204

You need to generate a report that lists language codes and region codes. Which code segment should you use?

A. For Each objCulture As CultureInfo In
_CultureInfo.GetCultures(CultureTypes.SpecificCultures)
...Next

B. Dim objCulture As New CultureInfo("")
Dim objTypes As CultureTypes = obj
Culture.CultureTypes
...

C. For Each objCulture As CultureInfo In
_CultureInfo.GetCultures(CultureTypes.NeutralCultures)
...Next

D. For Each objCulture As CultureInfo In
_CultureInfo.GetCultures(CultureTypes.ReplacementCultures)
...Next

Answer: A

Question: 205

You create an application that stores information about your customers who reside in various regions. You are developing internal utilities for this application. You need to gather regional information about your customers in Canada. Which code segment should you use?

A. For Each objCulture As CultureInfo In
_CultureInfo.GetCultures(CultureTypes.SpecificCultures)
...Next

B. Dim objCulture As New CultureInfo("CA")
 ...
C. Dim objRegion As New RegionInfo("CA")
 ...
D. Dim objRegion As New RegionInfo("")If objRegion.Name = "CA" Then
 ...End If

Answer: C

Question: 206

You need to write a multicast delegate that accepts a DateTime argument. Which code segment should you use?

A. public delegate int PowerDeviceOn(bool result, DateTime autoPowerOff);
B. public delegate bool PowerDeviceOn(object sender, EventArgs autoPowerOff);
C. public delegate void PowerDeviceOn(DateTime autoPowerOff);
D. public delegate bool PowerDeviceOn(DateTime autoPowerOff);

Answer: C

Question: 207

You are writing a method to compress an array of bytes. The array is passed to the method in a parameter named document. You need to compress the incoming array of bytes and return the result as an array of bytes. Which code segment should you use?

A. Dim objStream As New MemoryStream(document)
 Dim objDeflate As New DeflateStream(objStream, CompressionMode.Compress)
 Dim result(document.Length) As Byteobj
 Deflate.Write(result, 0, result.Length)Return result
B. Dim objStream As New MemoryStream(document)
 Dim objDeflate As New DeflateStream(objStream, CompressionMode.Compress)obj
 Deflate.Write(document, 0, document.Length)obj
 Deflate.Close()Return objStream.ToArray
C. Dim objStream As New MemoryStream()
 Dim objDeflate As New DeflateStream(objStream, CompressionMode.Compress)obj
 Deflate.Write(document, 0, document.Length)obj
 Deflate.Close()Return objStream.ToArray
D. Dim objStream As New MemoryStream()
 Dim objDeflate As New DeflateStream(objStream, CompressionMode.Compress)
 Dim outStream As New MemoryStreamDim b As IntegerWhile (b =
 objDeflate.ReadByte)
 outStream.WriteByte(CByte(b))
 End
 WhileReturn outStream.ToArray

Answer: C

Question: 208

You create the definition for a Vehicle class by using the following code segment.

```
public ref class Vehicle {
public : [XmlAttribute(AttributeName = "category")]
String^ vehicleType;
String^ model;
[XmlIgnore]
```

```

int year;
[XmlElement(ElementName = "mileage")]
int miles;
Condition Type condition;
Vehicle() {}
enum ConditionType {
[XmlEnum("Poor")] BelowAverage,
[XmlEnum("Good")] Average,
[XmlEnum("Excellent")] AboveAverage
};

```

You create an instance of the Vehicle class. You populate the public fields of the Vehicle class instance as shown in the following table:

Exhibit:

Member	Value
vehicle Type	car
model	racer
year	2002
miles	15000
condition	AboveAverage

You need to identify the XML block that is produced when this Vehicle class instance is serialized.

Which block of XML represents the output of serializing the Vehicle instance?

A. <?xml version="1.0" encoding="utf-8"?>
<Vehicle
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema"
vehicleType="car">
<model>racer</model>
<miles>15000</miles>
<condition>AboveAverage</condition>
</Vehicle>

B. <?xml version="1.0" encoding="utf-8"?>
<Vehicle
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema"
category="car">
<model>racer</model>
<mileage>15000</mileage>
<condition>Excellent</condition>
</Vehicle>

C. <?xml version="1.0" encoding="utf-8"?>
<Vehicle
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema"
category="car">
<model>racer</model>
<mileage>15000</mileage>
<conditionType>Excellent</conditionType>
</Vehicle>

D. <?xml version="1.0" encoding="utf-8"?>
<Vehicle
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
<category>car</category>
<model>racer</model>
<mileage>15000</mileage>
<condition>Excellent</condition>

</Vehicle>

Answer: B

Question: 209

You need to identify a type that meets the following criteria: ?

Is always a number.?

Is not greater than 65,535. Which type should you choose?

A. System.UInt16

B. int

C. System.String

D. System.IntPtr

Answer: A

Question: 210

Your application uses two threads, named threadOne and threadTwo.

You need to modify the code to prevent the execution of threadOne until threadTwo completes execution.

What should you do?

A. Configure threadOne to run at a lower priority.

B. Configure threadTwo to run at a higher priority.

C. Use a WaitCallback delegate to synchronize the threads.

D. Call the Sleep method of threadOne.

E. Call the SpinLock method of threadOne.

Answer: C

Question: 211

You need to call an unmanaged function from your managed code by using platform invoke services. What should you do?

A. Create a class to hold DLL functions and then create prototype methods by using managed code.

B. Register your assembly by using COM and then reference your managed code from COM.

C. Export a type library for your managed code.

D. Import a type library as an assembly and then create instances of COM object.

Answer: A

Question: 212

You are developing a fiscal report for a customer. Your customer has a main office in the United States and a satellite office in Mexico.

You need to ensure that when users in the satellite office generate the report, the current date is displayed in Mexican Spanish format. Which code segment should you use?

A. DateTimeFormatInfo dtfi = new CultureInfo("es-MX", false).DateTimeFormat;

DateTime dt = new DateTime(DateTime.Today.Year, DateTime.Today.Month, DateTime.Today.Day); string dateString = dt.ToString(dtfi.LongDatePattern);

B. Calendar cal = new CultureInfo("es-MS", false).Calendar; DateTime dt = new DateTime(DateTime.Today.Year, DateTime.Today.Month, DateTime.Today.Day); Strong dateString = dt.ToString();

**C. string dateString = DateTimeFormatInfo.CurrentInfo
GetMonthName(DateTime.Today.Month);**

D. `string dateString = DateTime.Today.Month.ToString("es_MX");`

Answer: A

Question: 213

You are developing a class library that will open the network socket connections to computers on the network. You will deploy the class library to the global assembly cache and grant it full trust.

You write the following code to ensure usage of the socket connections.

`SocketPermission^ permission =`

`gcnew SocketPermission(PermissionState::Unrestricted);permission->Assert();` Some of the applications that use the class library might not have the necessary permissions to open the network socket connections.

You need to cancel the assertion.

Which code segment should you use?

A. `CodeAccessPermission::RevertAssert();`

B. `CodeAccessPermission::RevertDeny();`

C. `permission->Deny();`

D. `permission->PermitOnly();`

Answer: A

Question: 214

You are creating an undo buffer that stores data modifications. You need to ensure that the undo functionality undoes the most recent data modifications first. You also need to ensure that the undo buffer permits the storage of strings only. Which code segment should you use?

A. `Stack<String^> undoBuffer = gcnew Stack<String^>();`

B. `Stack undoBuffer = gcnew Stack();`

C. `Queue<String^> undoBuffer = gcnew Queue<String^>();`

D. `Queue undoBuffer = gcnew Queue();`

Answer: A

Question: 215

You need to generate a report that lists language codes and region codes.

Which code segment should you use?

A. `for each (CultureInfo^ culture in
CultureInfo::GetCultures(CultureTypes::SpecificCultures)) {
// Output the culture information...}`

B. `CultureInfo^ culture = gcnew CultureInfo(""); CultureTypes^ types = culture->CultureTypes;
// Output the culture information...`

C. `for each (CultureInfo^ culture in
CultureInfo::GetCultures(CultureTypes::NeutralCultures)) {
// Output the culture information...}`

D. `for each (CultureInfo^ culture in
CultureInfo::GetCultures(CultureTypes::ReplacementCultures)) {
// Output the culture information...}`

Answer: A

Question: 216

You are creating an application that retrieves values from a custom section of the application configuration file. The custom section uses XML as shown in the following block.

`<ProjectSection name="ProjectCompany">`

```

<role name="administrator" />
<role name="manager" />
<role name="support" />
</ProjectSection>

```

You need to write a code segment to define a class named Role. You need to ensure that the Role class is initialized with values that are retrieved from the custom section of the configuration file. Which code segment should you use?

A. Public Class RoleInherits ConfigurationElementFriend _ElementName As String = "name"

```

<ConfigurationProperty("role")> _
Public ReadOnly Property Name() As String
Get
Return CType(Me("role"), String)
End Get
End PropertyEnd Class

```

B. Public Class Role

```

Inherits ConfigurationElement
Friend _ElementName As String = "role"
<ConfigurationProperty("name", IsRequired:=True)> _
Public ReadOnly Property Name() As String
Get
Return CType(Me("name"), String)
End Get
End PropertyEnd Class

```

C. Public Class Role

```

Inherits ConfigurationElement
Friend _ElementName As String = "role"
Private _name As String
<ConfigurationProperty("name")> _
Public ReadOnly Property Name() As String
Get
Return _name
End Get
End PropertyEnd Class

```

D. Public Class Role

```

Inherits ConfigurationElement
Friend _ElementName As String = "name"
Private _name As String
<ConfigurationProperty("role", IsRequired:=True)> _
Public ReadOnly Property Name() As String
Return _name
End Get
End PropertyEnd Class

```

Answer: B

Question: 217

You are developing a custom event handler to automatically print all open documents. The event handler helps specify the number of copies to be printed. You need to develop a custom event arguments class to pass as a parameter to the event handler. Which code segment should you use?

A. public ref class PrintingArgs {
public :
int Copies;

```

PrintingArgs (int numberOfCopies) {
this->Copies = numberOfCopies;
};
B. public ref class PrintingArgs : public EventArgs {
public :
int Copies;
PrintingArgs(int numberOfCopies) {
this->Copies = numberOfCopies;
};
C. public ref class PrintingArgs {
public :
EventArgs Args;
PrintingArgs(EventArgs ea) {
this->Args = ea;
};
D. public ref class PrintingArgs : public EventArgs {
public :
int Copies;};

```

Answer: B

Question: 218

You are creating a class to compare a specially-formatted string. The default collation comparisons do not apply. You need to implement the IComparable(Of String) interface. Which code segment should you use?

```

A. Public Class Person
Implements IComparable(Of String)Public Function CompareTo(ByVal other As String)
As _Integer Implements IComparable(Of String).CompareTo...End FunctionEnd Class
B. Public Class Person
Implements IComparable(Of String)Public Function CompareTo(ByVal other As Object)
As _Integer Implements IComparable(Of String).CompareTo...End FunctionEnd Class
C. Public Class Person
Implements IComparable(Of String)Public Function CompareTo(ByVal other As String)
_As Boolean Implements IComparable(Of String).CompareTo...End FunctionEnd Class
D. Public Class Person
Implements IComparable(Of String)Public Function CompareTo(ByVal other As Object)
_As Boolean Implements IComparable(Of String).CompareTo...End FunctionEnd Class

```

Answer: A

Question: 219

You write the following custom exception class named CustomException.

```

Public Class CustomException
Inherits ApplicationException
Public Shared COR_E_ARGUMENT As Int32 = &H80070057
Public Sub New(ByVal strMessage As String)
MyBase.New(strMessage)
HResult = COR_E_ARGUMENT
End SubEnd Class

```

You need to write a code segment that will use the CustomException class to immediately return control to the COM caller. You also need to ensure that the caller has access to the error code. Which code segment should you use?

```

A. Return Marshal.GetExceptionForHR(_
CustomException.COR_E_ARGUMENT)

```

- B. Return CustomException.COR_E_ARGUMENT
- C. Marshal.ThrowExceptionForHR(_ CustomException.COR_E_ARGUMENT)
- D. Throw New CustomException("Argument is out of bounds")

Answer: D

Question: 220

You create a class library that is used by applications in three departments of your company. The library contains a Department class with the following definition.

```
Public Class Department
Public name As String
Public manager As String
End Class
```

Each application uses a custom configuration section to store department-specific values in the application configuration file as shown in the following code.

```
<Department>
<name>Hardware</name>
<manager>Company</manager>
</Department>
```

You need to write a code segment that creates a Department object instance by using the field values retrieved from the application configuration file. Which code segment should you use?

- A. Public Class deptElement
Inherits ConfigurationElement
Protected Overrides Sub DeserializeElement(_
ByVal reader As XmlReader, _
ByVal serializeCollectionKey As Boolean)
Dim dept As Department = New Department()
dept.name = ConfigurationManager.AppSettings("name")
dept.manager = _
ConfigurationManager.AppSettings("manager")
End Sub
End Class
- B. Public Class deptElement
Inherits ConfigurationElement
Protected Overrides Sub DeserializeElement(_
ByVal reader As XmlReader, _
ByVal serializeCollectionKey As Boolean)
Dim dept As Department = New Department()
dept.name = reader.GetAttribute("name")
dept.manager = reader.GetAttribute("manager")
End Sub
End Class
- C. Public Class deptHandler
Implements IConfigurationSectionHandler
Public Function Create(ByVal parent As Object, _
ByVal configContext As Object, _
ByVal section As System.Xml.XmlNode) As Object _
Implements IConfigurationSectionHandler.Create
Dim dept As Department = new Department()
dept.name = section.SelectSingleNode("name").InnerText
dept.manager = _
section.SelectSingleNode("manager").InnerText
Return dept
End Function

```

End Class
D. Public Class deptHandler
Implements IConfigurationSectionHandler
Public Function Create(ByVal parent As Object, _
ByVal configContext As Object, _
ByVal section As System.Xml.XmlNode) As Object _
Implements IConfigurationSectionHandler.Create
Dim dept As Department = new Department()
dept.name = section.Attributes("name").Value
dept.manager = section.Attributes("manager").Value
Return dept
End Function
End Class

```

Answer: C

Question: 221

You are working on a debug build of an application.

You need to find the line of code that caused an exception to be thrown. Which property of the Exception class should you use to achieve this goal?

- A. Data**
- B. Message**
- C. StackTrace**
- D. Source**

Answer: C

Question: 222

You develop a service application named PollingService that periodically calls long-running procedures. These procedures are called from the DoWork method.

You use the following service application code:

```

Partial Class PollingService Inherits ServiceBase
Dim blnExit As Boolean = False Protected Overrides Sub OnStart(ByVal args() As
String)
Do
DoWork()
Loop While Not blnExit
End Sub
Protected Overrides Sub OnStop()
blnExit = True
End Sub
Private Sub DoWork()
End SubEnd Class

```

When you attempt to start the service, you receive the following error message: Could not start the PollingService service on the local computer. Error 1053: The service did not respond to the start or control request in a timely fashion. You need to modify the service application code so that the service starts properly. What should you do?

- A. Move the loop code into the constructor of the service class from the OnStart method.**
- B. Drag a timer component onto the design surface of the service. Move the calls to the longrunning procedure from the OnStart method into the Tick event procedure of the timer, set the Enabled property of the timer to True, and call the Start method of the timer in the OnStart method.**
- C. Add a class-level System.Timers.Timer variable to the service class code. Move the call to the DoWork method into the Elapsed event procedure of the timer, set the Enabled property**

of the timer to True, and call the Start method of the timer in the OnStart method.
D. Move the loop code from the OnStart method into the DoWork method.

Answer: C

Question: 223

You are creating a new security policy for an application domain. You write the following lines of code.

```
Dim objPolicy As PolicyLevel = PolicyLevel.CreateAppDomainLevelDim
```

```
noTrustStatement As New PolicyStatement( _
```

```
objPolicy.GetNamedPermissionSet("Nothing"))
```

```
Dim fullTrustStatement As New PolicyStatement( _
```

```
objPolicy.GetNamedPermissionSet("FullTrust"))
```

You need to arrange code groups for the policy so that loaded assemblies default to the Nothing permission set. If the assembly originates from a trusted zone, the security policy must grant the assembly the FullTrust permission set. Which code segment should you use?

A. Dim objGroup1 As CodeGroup = New FirstMatchCodeGroup(_
New ZoneMembershipCondition(SecurityZone.Trusted), _
fullTrustStatement)Dim objGroup2 As CodeGroup = New UnionCodeGroup(_
New AllMembershipCondition, noTrustStatement)

B. Dim objGroup1 As CodeGroup = New FirstMatchCodeGroup(_
New AllMembershipCondition, noTrustStatement)Dim objGroup2 As CodeGroup =
New UnionCodeGroup(_
New ZoneMembershipCondition(SecurityZone.Trusted), _
fullTrustStatement)

C. Dim objGroup As CodeGroup = New UnionCodeGroup(_
New ZoneMembershipCondition(SecurityZone.Trusted), _
fullTrustStatement)

D. Dim objGroup As CodeGroup = New FirstMatchCodeGroup(_
New ZoneMembershipCondition(SecurityZone.Trusted), _
fullTrustStatement)

Answer: B

Question: 224

You write the following custom exception class named CustomException.

```
public class CustomException : ApplicationException {
```

```
public static int COR_E_ARGUMENT =
```

```
unchecked((int)0x80070057);
```

```
public CustomException(string msg) : base(msg) {
```

```
HRESULT = COR_E_ARGUMENT;
```

```
}} You need to write a code segment that will use the CustomException class to immediately  
return control to the COM caller. You also need to ensure that the caller has access to the error  
code. Which code segment should you use?
```

A. return Marshal.GetExceptionForHR(
CustomException.COR_E_ARGUMENT);

B. return CustomException.COR_E_ARGUMENT;

C. Marshal.ThrowExceptionForHR(
CustomException.COR_E_ARGUMENT);

D. throw new CustomException("Argument is out of bounds");

Answer: D

Question: 225

You are developing a method to call a COM component. You need to use declarative security to explicitly request the runtime to perform a full stack walk. You must ensure that all callers have the required level of trust for COM interop before the callers execute your method. Which attribute should you place on the method?

- A. <SecurityPermission(_
SecurityAction.Demand, _
Flags:=SecurityPermissionFlag.UnmanagedCode) _>
- B. <SecurityPermission(_
SecurityAction.LinkDemand, _
Flags:=SecurityPermissionFlag.UnmanagedCode) _>
- C. <SecurityPermission(_
SecurityAction.Assert, _
Flags:=SecurityPermissionFlag.UnmanagedCode) _>
- D. <SecurityPermission(_
SecurityAction.Deny, _
Flags:=SecurityPermissionFlag.UnmanagedCode) _>

Answer: A

Question: 226

You are defining a class named `CompanyClass` that contains several child objects. `CompanyClass` contains a method named `ProcessChildren` that performs actions on the child objects. `CompanyClass` objects will be serializable. You need to ensure that the `ProcessChildren` method is executed after the `CompanyClass` object and all its child objects are reconstructed. Which two actions should you perform? (Each correct answer presents part of the solution. Choose two.)

- A. Apply the `OnDeserializing` attribute to the `ProcessChildren` method.
- B. Specify that `CompanyClass` implements the `IDeserializationCallback` interface.
- C. Specify that `CompanyClass` inherits from the `ObjectManager` class.
- D. Apply the `OnSerialized` attribute to the `ProcessChildren` method.
- E. Create a `GetObjectData` method that calls `ProcessChildren`.
- F. Create an `OnDeserialization` method that calls `ProcessChildren`.

Answer: B, F

Question: 227

You create a class library that is used by applications in three departments of your company. The library contains a `Department` class with the following definition.

```
public class Department {  
    public string name;  
    public string manager;  
}
```

Each application uses a custom configuration section to store department-specific values in the application configuration file as shown in the following code.

```
<Department>  
<name>Hardware</name>  
<manager>Company</manager>  
</Department>
```

You need to write a code segment that creates a `Department` object instance by using the field values retrieved from the application configuration file. Which code segment should you use?

- A.

```
public class deptElement : ConfigurationElement {  
    protected override void DeserializeElement()
```

```

XmlReader reader, bool serializeCollectionKey) {
    Department dept = new Department();
    dept.name = ConfigurationManager.AppSettings["name"];
    dept.manager =
    ConfigurationManager.AppSettings["manager"];
    return dept;
}}
B. public class deptElement: ConfigurationElement {
    protected override void DeserializeElement(
    XmlReader reader, bool serializeCollectionKey) {
    Department dept = new Department();
    dept.name = reader.GetAttribute("name");
    dept.manager = reader.GetAttribute("manager");
    }}
C. public class deptHandler : IConfigurationSectionHandler {
    public object Create(object parent, object configContext,
    System.Xml.XmlNode section) {
    Department dept = new Department();
    dept.name = section.SelectSingleNode("name").InnerText;
    dept.manager =
    section.SelectSingleNode("manager").InnerText;
    return dept;
    }}
D. public class deptHandler : IConfigurationSectionHandler {
    public object Create(object parent, object configContext,
    System.Xml.XmlNode section) {
    Department dept = new Deptment();
    dept.name = section.Attributes["name"].Value;
    dept.manager = section.Attributes["manager"].Value;
    return dept;
    }
}

```

Answer: C

Question: 228

You write the following custom exception class named CustomException.

```
public ref class CustomException : ApplicationException {public:
```

```
    literal int COR_E_ARGUMENT = (int)0x80070057;
```

```
    CustomException(String^ msg) : ApplicationException(msg)
```

```
{
```

```
    HRESULT = COR_E_ARGUMENT;
```

```
}};
```

You need to write a code segment that will use the CustomException class to immediately return control to the COM caller. You also need to ensure that the caller has access to the error code.

Which code segment should you use?

- A.** return Marshal::GetExceptionForHR(CustomException::COR_E_ARGUMENT);
- B.** return CustomException::COR_E_ARGUMENT;
- C.** Marshal::ThrowExceptionForHR(CustomException::COR_E_ARGUMENT);
- D.** throw gcnew CustomException("Argument is out of bounds");

Answer: D

Question: 229

You are writing a method that returns an ArrayList named al. You need to ensure that changes to the ArrayList are performed in a thread-safe manner. Which code segment should you use?

- A. ArrayList al = new ArrayList();lock (al.SyncRoot){
return al;}
- B. ArrayList al = new ArrayList();lock (al.SyncRoot.GetType()){
return al;}
- C. ArrayList al = new ArrayList();Monitor.Enter(al);Monitor.Exit(al);return al;
- D. ArrayList al = new ArrayList();ArrayList sync_al = ArrayList.Synchronized(al);return sync_al;

Answer: D

Question: 230

You are using the Microsoft Visual Studio 2005 IDE to examine the output of a method that returns a string. You assign the output of the method to a string variable named fName. You need to write a code segment that prints the following on a single line The message: "Test Failed: " The value of fName if the value of fName does not equal "Company" You also need to ensure that the code segment simultaneously facilitates uninterrupted execution of the application. Which code segment should you use?

- A. Debug.Assert(fName == "Company", "Test Failed: ", fName);
- B. Debug.WriteLineIf(fName != "Company", fName, "Test Failed");
- C. if (fName != "Company") {
Debug.Print("Test Failed: ");
Debug.Print(fName);
}
- D. if (fName != "Company") {
Debug.WriteLine("Test Failed: ");
Debug.WriteLine (fName);
}

Answer: B

Question: 231

You are developing a utility screen for a new client application. The utility screen displays a thermometer that conveys the current status of processes being carried out by the application. You need to draw a rectangle on the screen to serve as the background of the thermometer as shown in the exhibit. The rectangle must be filled with gradient shading. (Click the Exhibit button.) Which code segment should you choose?

Exhibit:



- A. Dim objRect As New Rectangle(10, 10, 450, 25)
Dim objBrush As New LinearGradientBrush(_objRect, Color.AliceBlue, Color.CornflowerBlue, _LinearGradientMode.ForwardDiagonal)
Dim objPen As New Pen(objBrush)Dim g As Graphics = myForm.CreateGraphicsg.DrawRectangle(objPen, objRect)
- B. Dim objRect As New Rectangle(10, 10, 450, 25)
Dim objBrush As New LinearGradientBrush(_objRect, Color.AliceBlue, Color.CornflowerBlue, _LinearGradientMode.ForwardDiagonal)
Dim objPen As New Pen(objBrush)
Dim g As Graphics = myForm.CreateGraphicsg.FillRectangle(objBrush, objRect)
- C. Dim objRect As New RectangleF(10.0F, 10.0F, 450.0F, 25.0F)
Dim points() As System.Drawing.Point = _

```
{New Point(0, 0), New Point(110, 145)}
Dim objBrush As New LinearGradientBrush( _
objRect, Color.AliceBlue, Color.CornflowerBlue, _
LinearGradientMode.ForwardDiagonal)
Dim objPen As New Pen(objBrush)
Dim g As Graphics = myForm.CreateGraphicsg.DrawPolygon(objPen, points)
D. Dim objRect As New Rectangle(10, 10, 450, 25)
Dim objBrush As New SolidBrush(Color.AliceBlue)
Dim objPen As New Pen(objBrush)Dim g As Graphics =
myForm.CreateGraphicsg.DrawRectangle(objPen, objRect)
```

Answer: B

Question: 232

You create an application that stores information about your customers who reside in various regions. You are developing internal utilities for this application. You need to gather regional information about your customers in Canada. Which code segment should you use?

- A.** foreach (CultureInfo culture in
CultureInfo.GetCultures(CultureTypes.SpecificCultures)) { // Output the region
information...}
- B.** CultureInfo cultureInfo = new CultureInfo("CA"); // Output the region information...
- C.** RegionInfo regionInfo = new RegionInfo("CA"); // Output the region information...
- D.** RegionInfo regionInfo = new RegionInfo("");if(regionInfo.Name == "CA") {
// Output the region information...}

Answer: C

Question: 233

You are developing an application to assist the user in conducting electronic surveys. The survey consists of 25 true-or-false questions. You need to perform the following tasks: Initialize each answer to true.Minimize the amount of memory used by each survey. Which storage option should you choose?

- A.** BitVector32 answers = new BitVector32(1);
- B.** BitVector32 answers = new BitVector32(-1);
- C.** BitArray answers = new BitArray(1);
- D.** BitArray answers = new BitArray(-1);

Answer: B

Question: 234

You are writing a method to compress an array of bytes. The array is passed to the method in a parameter named document. You need to compress the incoming array of bytes and return the result as an array of bytes. Which code segment should you use?

- A.** MemoryStream^ strm = gcnw MemoryStream(document);
DeflateStream^ deflate = gcnw DeflateStream(strm,
CompressionMode::Compress);
array<Byte>^ result = gcnw array<Byte>(document->Length);
deflate->Write(result, 0, result->Length);
return result;
- B.** MemoryStream^ strm = gcnw MemoryStream(document);
DeflateStream^ deflate = gcnw DeflateStream(strm,
CompressionMode::Compress);

```

deflate->Write(document, 0, document->Length);
deflate->Close();return strm->ToArray();
C. MemoryStream^ strm = gcnew MemoryStream();
DeflateStream^ deflate = gcnew
DeflateStream(strm,CompressionMode::Compress);deflate->Write(document, 0, document-
>Length);
deflate->Close();
return strm->ToArray();
D. MemoryStream^ inStream = gcnew MemoryStream(document);DeflateStream^
deflate = gcnew DeflateStream(inStream,
CompressionMode::Compress);
MemoryStream^ outStream = gcnew MemoryStream()
;int b;
while ((b = deflate->ReadByte()) != -1) {
outStream->WriteByte((Byte)b);
}
return outStream->ToArray();

```

Answer: C

Question: 235

You need to read the entire contents of a file named Message.txt into a single string variable. Which code segment should you use?

```

A. string result = null;StreamReader reader = new StreamReader("Message.txt");result =
reader.Read().ToString();
B. string result = null;StreamReader reader = new StreamReader("Message.txt");result =
reader.ReadToEnd();
C. string result = string.Empty;StreamReader reader = new StreamReader("Message.txt"); while
(!reader.EndOfStream) {
result += reader.ToString();}
D. string result = null;StreamReader reader = new StreamReader("Message.txt");result =
reader.ReadLine();

```

Answer: B

Question: 236

You are defining a class named CompanyClass that contains several child objects. CompanyClass contains a method named ProcessChildren that performs actions on the child objects. CompanyClass objects will be serializable. You need to ensure that the ProcessChildren method is executed after the CompanyClass object and all its child objects are reconstructed. Which two actions should you perform? (Each correct answer presents part of the solution. Choose two.)

```

A. Apply the OnDeserializing attribute to the ProcessChildren method.
B. Specify that CompanyClass implements the IDeserializationCallback interface.
C. Specify that CompanyClass inherits from the ObjectManager class.
D. Apply the OnSerialized attribute to the ProcessChildren method.
E. Create a GetObjectData method that calls ProcessChildren.
F. Create an OnDeserialization method that calls ProcessChildren.

```

Answer: B, F

Question: 237

You are writing a custom dictionary. The custom-dictionary class is named

MyDictionary. You need to ensure that the dictionary is type safe. Which code segment should you use?

- A. public ref class MYDictionary : public Dictionary<String^, String^>{};
- B. public ref class MYDictionary : public Hashtable{};
- C. public ref class MYDictionary : public IDictionary{};
- D. public ref class MYDictionary {};Dictionary<String^, String^>t = gcnew Dictionary<String^, String^>();MyDictionary dictionary = (MyDictionary)t;

Answer: A

Question: 238

You develop a service application named **FileService**. You deploy the service application to multiple servers on your network. You implement the following code segment. (Line numbers are included for reference only.)

```
01 public :
02 void StartService(String^ serverName){
03
04 ServiceController^ ctrl = gcnew
05 ServiceController("FileService");
06 if (ctrl->Status == ServiceControllerStatus::Stopped){}
07 }
```

You need to develop a routine that will start **FileService** if it stops. The routine must start **FileService** on the server identified by the **serverName** input parameter.

Which two lines of code should you add to the code segment? (Each correct answer presents part of the solution. Choose two.)

- A. Insert the following line of code between lines 03 and 04:ctrl.ServiceName = serverName;
- B. Insert the following line of code between lines 03 and 04:ctrl.MachineName = serverName;
- C. Insert the following line of code between lines 03 and 04:ctrl.Site.Name = serverName;
- D. Insert the following line of code between lines 04 and 05:ctrl.Continue();
- E. Insert the following line of code between lines 04 and 05:ctrl.Start();
- F. Insert the following line of code between lines 04 and 05:ctrl.ExecuteCommand(0);

Answer: B, E

Question: 239

You are loading a new assembly into an application. You need to override the default evidence for the assembly. You require the common language runtime (CLR) to grant the assembly a permission set, as if the assembly were loaded from the local intranet zone.

You need to build the evidence collection. Which code segment should you use?

- A. Evidence^ evidence = gcnew Evidence(Assembly::GetExecutingAssembly()->Evidence);
- B. Evidence^ evidence = gcnew Evidence();evidence->AddAssembly(gcnew Zone(SecurityZone::Intranet));
- C. Evidence^ evidence = gcnew Evidence();evidence->AddHost(gcnew Zone(SecurityZone::Intranet));
- D. Evidence^ evidence = gcnew Evidence(AppDomain::CurrentDomain->Evidence);

Answer: C

Question: 240

You are creating a class named **Age**.

You need to ensure that the **Age** class is written such that collections of **Age** objects can be sorted. Which code segment should you use?

```

A. public class Age {
public int Value;
public object CompareTo(object obj) {
if (obj is Age) {
Age_age = (Age) obj;
return Value.CompareTo(obj);
}
throw new ArgumentException("object not an Age");
}}
B. public class Age {
public int Value;
public object CompareTo(int iValue) {
try {
return Value.CompareTo(iValue);
} catch {
throw new ArgumentException("object not an Age");
}}
C. public class Age : IComparable {
public int Value;
public int CompareTo(object obj) {
if (obj is Age) {
Age_age = (Age) obj;
return Value.CompareTo(_age.Value);
}
throw new ArgumentException("object not an Age");
}}
D. public class Age : IComparable {
public int Value;
public int CompareTo(object obj) {
try {
return Value.CompareTo(((Age) obj).Value);
} catch {
return -1;
}}}

```

Answer: C

Question: 241

You need to write a code segment that transfers the first 80 bytes from a stream variable named stream1 into a new byte array named byteArray. You also need to ensure that the code segment assigns the number of bytes that are transferred to an integer variable named bytesTransferred. Which code segment should you use?

```

A. bytesTransferred = stream1.Read(byteArray, 0, 80)
B. For i As Integer = 1 To 80
stream1.WriteByte(byteArray(i))
bytesTransferred = i
If Not stream1.CanWrite Then
Exit For
End IfNext
C. While bytesTransferred < 80
stream1.Seek(1, SeekOrigin.Current)
byteArray(bytesTransferred) = _
Convert.ToByte(stream1.ReadByte())bytesTransferred += 1End While
D. stream1.Write(byteArray, 0, 80)bytesTransferred = byteArray.Length

```

Answer: A

Question: 242

You are developing a class library. Portions of your code need to access system environment variables.

You need to force a runtime `SecurityException` only when callers that are higher in the call stack do not have the necessary permissions.

Which call method should you use?

- A. `Demand()`
- B. `Assert()`
- C. `PermitOnly()`
- D. `Deny()`

Answer: A

Question: 243

You are developing an application to assist the user in conducting electronic surveys. The survey consists of 25 true-or-false questions. You need to perform the following tasks:

Initialize each answer to true. Minimize the amount of memory used by each survey.

Which storage option should you choose?

- A. `Dim answers As New BitVector32(1)`
- B. `Dim answers As New BitVector32(-1)`
- C. `Dim answers As New BitArray(1)`
- D. `Dim answers As New BitArray(-1)`

Answer: B

Question: 244

You need to select a class that is optimized for key-based item retrieval from both small and large collections. Which class should you choose?

- A. `OrderedDictionary` class
- B. `HybridDictionary` class
- C. `ListDictionary` class
- D. `Hashtable` class

Answer: B

Question: 245

You write the following code to implement the `CompanyClass.MyMethod` function.

```
public class CompanyClass {  
    public int MyMethod(int arg) {  
        return arg;  
    }  
}
```

You need to call the `CompanyClass.MyMethod` function dynamically from an unrelated class in your assembly. Which code segment should you use?

- A. `CompanyClass myClass = new CompanyClass();`
`Type t = typeof(CompanyClass);`
`MethodInfo m = t.GetMethod("MyMethod");`
`int i = (int)m.Invoke(this, new object[] { 1 });`
- B. `CompanyClass myClass = new CompanyClass();`
`Type t = typeof(CompanyClass);`

```

MethodInfo m = t.GetMethod("MyMethod");
int i = (int) m.Invoke(myClass, new object[] { 1 });
C. CompanyClass myClass = new CompanyClass();
Type t = typeof(CompanyClass);
MethodInfo m = t.GetMethod("CompanyClass.MyMethod");
int i = (int)m.Invoke(myClass, new object[] { 1 });
D. Type t = Type.GetType("CompanyClass");
MethodInfo m = t.GetMethod("MyMethod");
int i = (int)m.Invoke(this, new object[] { 1 });

```

Answer: B

Question: 246

You create a class library that contains the class hierarchy defined in the following code segment. (Line numbers are included for reference only.)

```

01 public class Group {
02     public Employee[] Employees;
03 }
04 public class Employee {
05     public string Name;
06 }
07 public class Manager : Employee {
08     public int Level;
09 }

```

You create an instance of the Group class. You populate the fields of the instance. When you attempt to serialize the instance by using the Serialize method of the XmlSerializer class, you receive InvalidOperationException. You also receive the following error message: "There was an error generating the XML document."

You need to modify the code segment so that you can successfully serialize instances of the Group class by using the XmlSerializer class. You also need to ensure that the XML output contains an element for all public fields in the class hierarchy. What should you do?

A. Insert the following code between lines 1 and 2 of the code segment:

```

[XmlAttribute(Type = typeof(Employee))]
[XmlAttribute(Type = typeof(Manager))]

```

B. Insert the following code between lines 1 and 2 of the code segment:

```

[XmlElement(Type = typeof(Employees))]

```

C. Insert the following code between lines 1 and 2 of the code segment:

```

[XmlAttribute(ElementName="Employees")]

```

D. Insert the following code between lines 3 and 4 of the code segment:

```

[XmlElement(Type = typeof(Employee))]

```

and insert the following code between lines 6 and 7 of the code segment:

```

[XmlElement(Type = typeof(Manager))]

```

Answer: A

Question: 247

You are creating an assembly named Company1. Company1 contains a public method.

The global cache contains a second assembly named Company2.

You must ensure that the public method is only called from Company2.

Which permission class should you use?

- A. GacIdentityPermission
- B. PublisherIdentityPermission
- C. DataProtectionPermission
- D. StrongNameIdentityPermission

Answer: A

Question: 248

You are testing a newly developed method named `PersistToDB`. This method accepts a parameter of type `EventLogEntry`. This method does not return a value. You need to create a code segment that helps you to test the method. The code segment must read entries from the application log of local computers and then pass the entries on to the `PersistToDB` method. The code block must pass only events of type `Error` or `Warning` from the source `MySource` to the `PersistToDB` method.

Which code segment should you use?

- A.** `Dim myLog As New EventLog("Application", ".")`
`For Each entry As EventLogEntry In myLog.Entries`
`If entry.Source = "MySource" Then`
`PersistToDB(entry)`
`End If`
`Next`
- B.** `Dim myLog as New EventLog("Application", ".")`
`myLog.Source = "MySource"`
`For Each entry As EventLogEntry In myLog.Entries`
`If entry.EntryType = (EventLogEntryType.Error And _`
`EventLogEntryType.Warning) Then`
`PersistToDB(entry)`
`End If`
`Next`
- C.** `Dim myLog as New EventLog("Application", ".")`
`For Each entry As EventLogEntry In myLog.Entries`
`If entry.Source = "MySource" Then`
`If (entry.EntryType = EventLogEntryType.Error) Or _`
`(entry.EntryType = EventLogEntryType.Warning) Then`
`PersistToDB(entry)`
`End If`
`End If`
`Next`
- D.** `Dim myLog as New EventLog("Application", ".")`
`myLog.Source = "MySource"`
`For Each entry As EventLogEntry In myLog.Entries`
`If (entry.EntryType = EventLogEntryType.Error) Or _`
`(entry.EntryType = EventLogEntryType.Warning) Then`
`PersistToDB(entry)`
`End If`
`Next`

Answer: C

Question: 249

You are testing a newly developed method named `PersistToDB`. This method accepts a parameter of type `EventLogEntry`. This method does not return a value. You need to create a code segment that helps you to test the method. The code segment must read entries from the application log of local computers and then pass the entries on to the `PersistToDB` method. The code block must pass only events of type `Error` or `Warning` from the source `MySource` to the `PersistToDB` method. Which code segment should you use?

- A.** `EventLog^ myLog = gcnew EventLog("Application", ".");`
`for each (EventLogEntry^ entry in myLog->Entries) {`

```

if (entry->Source == "MySource") {
PersistToDB(entry);
}}
B. EventLog^ myLog = gcnew EventLog("Application", ".");
myLog->Source = "MySource";
for each (EventLogEntry^ entry in myLog->Entries) {
if (entry->EntryType == (EventLogEntryType::Error &
EventLogEntryType::Warning)) {
PersistToDB(entry);}}
C. EventLog^ myLog = gcnew EventLog("Application", ".");
for each (EventLogEntry^ entry in myLog->Entries) {
if (entry->Source == "MySource") {
if (entry->EntryType == EventLogEntryType::Error ||
entry->EntryType == EventLogEntryType::Warning) {
PersistToDB(entry);
}
}}
D. EventLog^ myLog = gcnew EventLog("Application", ".");
myLog->Source = "MySource";
for each (EventLogEntry^ entry in myLog->Entries) {
if (entry->EntryType == EventLogEntryType::Error ||
entry->EntryType == EventLogEntryType::Warning) {
PersistToDB(entry);
}}

```

Answer: C

Question: 250

You are creating an application that lists processes on remote computers. The application requires a method that performs the following tasks: Accept the remote computer name as a string parameter named strComputer. Return an ArrayList object that contains the names of all processes that are running on that computer. You need to write a code segment that retrieves the name of each process that is running on the remote computer and adds the name to the ArrayList object. Which code segment should you use?

```

A. ArrayList al = new ArrayList();Process[] procs =
Process.GetProcessesByName(strComputer);foreach (Process proc in procs) {
al.Add(proc);}
B. ArrayList al = new ArrayList();Process[] procs = Process.GetProcesses(strComputer);foreach
(Process proc in procs) {
al.Add(proc);}
C. ArrayList al = new ArrayList();Process[] procs =
Process.GetProcessesByName(strComputer);foreach (Process proc in procs) {
al.Add(proc.ProcessName);}
D. ArrayList al = new ArrayList();Process[] procs = Process.GetProcesses(strComputer);foreach
(Process proc in procs) {
al.Add(proc.ProcessName);}

```

Answer: D

Question: 251

You are developing a method to decrypt data that was encrypted with the Triple DES Algorithm. The method accepts the following parameters: The byte array to be decrypted, which is named cipherMessageThe key, which is named key An initialization vector, which is named iv You need to decrypt the message by using the TripleDES class and place the result in a string. Which code segment should you use?

A. TripleDES des = new TripleDESCryptoServiceProvider();des.BlockSize = cipherMessage.Length;ICryptoTransform crypto = des.CreateDecryptor(key, iv);MemoryStream cipherStream = new MemoryStream(cipherMessage);CryptoStream cryptoStream = new CryptoStream(cipherStream, crypto, CryptoStreamMode.Read); string message;message = new StreamReader(cryptoStream).ReadToEnd();

B. TripleDES des = new TripleDESCryptoServiceProvider();des.FeedbackSize = cipherMessage.Length;ICryptoTransform crypto = des.CreateDecryptor(key, iv);MemoryStream cipherStream = new MemoryStream(cipherMessage);CryptoStream cryptoStream = new CryptoStream(cipherStream, crypto, CryptoStreamMode.Read); string message;message = new StreamReader(cryptoStream).ReadToEnd();

C. TripleDES des = new TripleDESCryptoServiceProvider();ICryptoTransform crypto = des.CreateDecryptor();MemoryStream cipherStream = new MemoryStream(cipherMessage);CryptoStream cryptoStream = new CryptoStream(cipherStream, crypto, CryptoStreamMode.Read); string message;message = new StreamReader(cryptoStream).ReadToEnd();

D. TripleDES des = new TripleDESCryptoServiceProvider();ICryptoTransform crypto = des.CreateDecryptor(key, iv);MemoryStream cipherStream = new MemoryStream(cipherMessage);CryptoStream cryptoStream = new CryptoStream(cipherStream, crypto, CryptoStreamMode.Read); string message;message = new StreamReader(cryptoStream).ReadToEnd();

Answer: D

Question: 252

You need to create a class definition that is interoperable along with COM. You need to ensure that COM applications can create instances of the class and can call the GetAddress method. Which code segment should you use?

A. public ref class Customer {
string addressString;public:
Customer(string address) : addressString(address) { }
String^ GetAddress() { return addressString; }}

B. public ref class Customer {
static string addressString;public:
Customer() { }
static String^ GetAddress() { return addressString; }}

C. public ref class Customer {
string addressString;
public: Customer() { }
String^ GetAddress() { return addressString; }}

D. public ref class Customer {
string addressString;public:
Customer() { }private:
String^ GetAddress() { return addressString; }}

Answer: C

Question: 253

You need to return the contents of an isolated storage file as a string. The file is machine-scoped

and is named Settings.dat. Which code segment should you use?

- A.** IsolatedStorageFileStream isoStream;isoStream = new IsolatedStorageFileStream("Settings.dat", FileMode.Open); string result = new StreamReader(isoStream).ReadToEnd();
- B.** IsolatedStorageFile isoFile;isoFile = IsolatedStorageFile.GetMachineStoreForAssembly(); IsolatedStorageFileStream isoStream;isoStream = new IsolatedStorageFileStream("Settings.dat", FileMode.Open, isoFile); string result = new StreamReader(isoStream).ReadToEnd();
- C.** IsolatedStorageFileStream isoStream;isoStream = new IsolatedStorageFileStream("Settings.dat", FileMode.Open); string result = isoStream.ToString();
- D.** IsolatedStorageFile isoFile;isoFile = IsolatedStorageFile.GetMachineStoreForAssembly(); IsolatedStorageFileStream isoStream;isoStream = new IsolatedStorageFileStream("Settings.dat", FileMode.Open, isoFile); string result = isoStream.ToString();

Answer: B

Question: 254

You need to read the entire contents of a file named Message.txt into a single string variable. Which code segment should you use?

- A.** String^ result = nullptr;StreamReader^ reader = gcnew StreamReader("Message.txt");result = reader->Read().ToString();
- B.** String^ result = nullptr;StreamReader^ reader = gcnew StreamReader("Message.txt");result = reader->ReadToEnd();
- C.** String^ result =String::Empty;StreamReader^ reader = gcnew StreamReader("Message.txt"); while (!reader->EndOfStream) { result += reader->ToString();}
- D.** String^ result = nullptr;StreamReader^ reader = gcnew StreamReader("Message.txt"); result = reader->ReadLine();

Answer: B

Question: 255

You are writing a method to compress an array of bytes. The bytes to be compressed are passed to the method in a parameter named document.

You need to compress the contents of the incoming parameter.

Which code segment should you use?

- A.** Dim inStream As New MemoryStream(document)Dim zipStream As New GZipStream(_inStream, CompressionMode.Compress)Dim result(document.Length) As BytezipStream.Write(result, 0, result.Length)Return result
- B.** Dim objStream As New MemoryStream(document)Dim zipStream As New GZipStream(_objStream, CompressionMode.Compress)zipStream.Write(document, 0, document.Length)zipStream.Close()Return objStream.ToArray
- C.** Dim outputStream As New MemoryStreamDim zipStream As New GZipStream(_outStream, CompressionMode.Compress)zipStream.Write(document, 0, document.Length)zipStream.Close()Return outputStream.ToArray
- D.** Dim objStream As New MemoryStream(document)Dim zipStream As New GZipStream(_objStream, CompressionMode.Compress)Dim outputStream As New MemoryStreamDim b As IntegerWhile (b = zipStream.ReadByte)outputStream.WriteByte(CByte(b))End WhileReturn outputStream.ToArray

Answer: C

End of Document